



Sparkle Power Inc.

A Leading Power Supply Manufacturer

Web site: www.sparklepower.com

FSP060-DBAE1

(Efficiency Level V, RoHS Compliant)

60 Watts Power Adapter



Features

- High efficiency and reliability
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- Complies with FCC part 15, and CISPR 22 class B
- Approved by CUL/UL60950-1 2nd TUV EN60950-1 2nd, CB 60950-1 2nd, FCC, EMC

Specification

- **Temperature Range:** Operating: 0°C ~ +40°C
- **Humidity:** 80% on operating, 90% on storage
- **Average Efficiency:** Efficiency Level V & ErP Teir 2
- **No Load Power Consumption:** Less than 0.1W
- **Dimensions (LxWxH):** 110x62x31.5mm
/4.33x2.44x1.24inch

Output Characteristics

SPI Model	Output Voltage	Output Current	Connecter Type	Connecter IDxODxL	Dc cable Length (mm)
AD060DBAE1-J21	12V	5A	Barrel 180°	2.1x5.5x9.5	1500
AD060-DBAE1-J25R	12V	5A	Barrel 90°	2.5x5.5x10	1500

Sparkle Power Inc.
Main Office
 1000 Rock Avenue
 San Jose, CA 95131
 TEL: 408-519-8888
 FAX: 408-519-9999
 E-MAIL: info@sparklepower.com

Sparkle Power Inc.
Los Angeles Office
 17071 Green Drive
 City of Industry, CA 91745
 TEL: 626-839-7180
 FAX: 626-839-3395