


PASTERNAK ENTERPRISES PE-S330



IMPEDANCE: 100 OHMS

INNER CONDUCTOR DIAMETER: .037" (7 STRANDS .0125")

INNER CONDUCTOR MATERIAL: TINNED COPPER/BARE COPPER

DIELECTRIC DIAMETER: .236"

DIELECTRIC MATERIAL: POLYETHYLENE

NUMBER OF SHIELDS: 2

SHIELD MATERIAL: TINNED COPPER/FOIL

OUTER DIAMETER: .330"

JACKET MATERIAL: BLACK POLYVINYLCHLORIDE, NON CONTAMINATING

NOMINAL CAPACITANCE (pf/ft): 15.5

OPERATING TEMPERATURE: -30 TO +75° C

MAX OPERATING VOLTAGE (VOLTS RMS): 300

NOMINAL ATTENUATION (PER 100 FEET)

10 MHz	1.2dB
100 MHz	4.1dB
400 MHz	10.2dB



PASTERNAK ENTERPRISES, INC.

P.O BOX 16759, IRVINE, CA 92623
PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE-S330

DES. COAXIAL BULK CABLE, IMPEDANCE: 100 OHMS

REV. -

FSCM NO. 53919

CAD FILE 042809

SCALE N/A

SIZE A

127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.