

BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin



ATS Part#: **ATS042042010-SF-14I**
 Description: 42.00 x 42.00 x 10.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin
 Heat Sink Type: **Straight Fin**
 Heat Sink Attachment: **superGRIP**
 Equivalent Part Number: **N/A**

**Image above is for illustration purpose only.*

Features & Benefits

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Features a low profile, slant fin array that offers many of the performance benefits of **maxiFLOW™** at a great value
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

Thermal Performance

| AIR VELOCITY | | @200 LFM 1.0 M/S | @300 LFM 1.5 M/S | @400 LFM 2.0 M/S | @500 LFM 2.5 M/S | @600 LFM 3.0 M/S | @700 LFM 3.5 M/S | @800 LFM 4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 7.83 °C/W | 4.5 °C/W | 3.3 °C/W | 2.6 °C/W | 2.3 °C/W | 2 °C/W | 1.9 °C/W |
| | Ducted Flow | 2.3 | 1.9 | 1.6 | 1.5 | 1.4 | 1.3 | 1.2 |

Product Detail

| Schematic Image | Dimension A | Dimension B | Dimension C | Dimension D | TIM | Finish |
|---|-------------|-------------|-------------|-------------|-----|----------------|
| | 42.00 mm | 42.00 mm | 10.00 mm | 42 mm | N/A | BLACK-ANODIZED |
| <p>Notes:</p> <ul style="list-style-type: none"> • Dimension A and B refer to component size. • Dimension C is the heat sink height from the bottom of the base to the top of the fin field. • Dimension D is fin tip to fin tip. • Thermal performance data are provided for reference only. Actual performance may vary by application. • ATS reserves the right to update or change its products without notice to improve the design or performance. • ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant. • Contact ATS to learn about custom options available. | | | | | | |

**Image above is for illustration purpose only.*

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA

