

Part Number: C9012A

Revision Date: 9/4/2012

6C 22 AWG 7/30 TC PVC / PVC



A. CONSTRUCTION

Conductor: #22 AWG 7/.0096" Tinned Copper
 Insulation: .010" Polyvinyl Chloride (PVC)
 Cable Core: Cable 6/C @ 2.25" LHL w/ clear polyester wrap, 100% coverage
 Jacket: ".032"" Polyvinyl Chloride (PVC) jacket
 Ripcord under Jacket"

DIAMETERS

.029" Nom
 .049" Nom
 .152" Nom
 .216" Nom

Print Legend: **CAROL® EXZEL™ -- C9012A -- 6C 22 AWG
 E105765-H (UL) TYPE CM 105C OR AWM 2464 80C 300V
 VW-1 --- LL69381 CSA TYPE CMG 105C FT4 -- CE --
 -- ROHS -- MADE IN USA
 (DATE CODE) (TRUMARK SEQUENTIAL FOOTAGE)**

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	CM/CMG: 105C, AWM: 80C
Suggested Working Voltage:	300V
Conductor DCR:	16.89 Ohms/M' @ 20°C
Mutual Capacitance:	24.5 pF/ft. @ 1 kHz

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	BROWN
3	RED
4	ORANGE
5	YELLOW
6	GREEN