

APPLICATION

GMLI chip inductors can be used in a variety of electronics including:

- CD-ROMs
- Hard disks
- Modems
- Computers
- Printers
- Televisions

FEATURES

GMLI chip inductors are Mag.Layers line of high quality ferrite chip inductors. Using the latest innovations in multilayer technology, we have developed reliable chip inductors that have high quality characteristics.

- **High Performance Characteristics**
GMLI chips exhibit low DC resistance and high Q at high frequency.
- **Wide Inductance Range**
GMLI chip inductors cover a wide range of inductance values from 0.047 μ H to 220 μ H.
- **High Reliability**
GMLI chip inductors have a monolithic inorganic material construction that effectively minimizes electromagnetic interference.
- **High Soldering Heat Resistance**
GMLI chip inductors have high quality termination allowing both flow and reflow soldering methods to be used.


PRODUCT IDENTIFICATION

G M L I - 2 0 1 2 0 9 - 1 R 0 J ☐

① ② ③ ④ ⑤

- ① Product Code
- ② Dimension Code
- ③ Inductance
- ④ Tolerance Code: J=±5%, K=±10%, M=±20%
- ⑤ Code for Special Specification

PRODUCT DIMENSION



NOTE : Dimensions in mm

PRODUCT NO.	A	B	C	D
GMLI-201212 (0805)	2.0±0.20 (0.079±0.008)	1.2±0.20 (0.047±0.008)	1.2±0.20 (0.047±0.008)	0.5±0.30 (0.020±0.012)
GMLI-201209 (0805)	2.0±0.20 (0.079±0.008)	1.2±0.20 (0.047±0.008)	0.9±0.20 (0.035±0.008)	0.5±0.30 (0.020±0.012)




ELECTRICAL REQUIREMENTS

Part Number	Inductance (μH)	Q Min.	Test Freq. (MHz)	S.R.F. (MHz) Min.	R _{DC} (Ω) Max.	Rated Current (mA) Max.
GMLI-201209-47N□	0.047	15	50	320	0.20	300
GMLI-201209-68N□	0.068			280		
GMLI-201209-82N□	0.082			255		
GMLI-201209-R10□	0.10	20	25	235	0.30	250
GMLI-201209-R12□	0.12			220	0.40	
GMLI-201209-R15□	0.15			200		
GMLI-201209-R18□	0.18			185		
GMLI-201209-R22□	0.22			170		
GMLI-201209-R27□	0.27			150		
GMLI-201209-R33□	0.33			145	0.55	
GMLI-201209-R39□	0.39	25		135	0.65	200
GMLI-201209-R47□	0.47			125	0.65	
GMLI-201209-R56□	0.56			115	0.45	150
GMLI-201209-R68□	0.68			105	0.80	
GMLI-201209-R82□	0.82			100	1.00	
GMLI-201209-1R0□	1.0	45	10	75	0.40	50
GMLI-201209-1R2□	1.2			65	0.50	
GMLI-201209-1R5□	1.5			60		
GMLI-201209-1R8□	1.8			55	0.60	
GMLI-201209-2R2□	2.2			50	0.65	30
GMLI-201209-2R7□	2.7			45	0.75	
GMLI-201209-3R3□	3.3			41	0.80	
GMLI-201209-3R9□	3.9	45	10	38	0.90	15
GMLI-201212-4R7□	4.7			35	1.00	
GMLI-201212-5R6□	5.6	50	4	32	0.90	
GMLI-201212-6R8□	6.8			29	1.00	
GMLI-201212-8R2□	8.2			26	1.10	
GMLI-201212-100□	10		2	24	1.15	
GMLI-201212-120□	12		1	22	1.25	
GMLI-201212-150□	15	30		19	0.80	5
GMLI-201212-180□	18			18	0.90	
GMLI-201212-220□	22			16	1.10	
GMLI-201212-270□	27			14	1.15	
GMLI-201212-330□	33		0.4	13	1.25	

- Inductance change should be less than $\pm 10\%$ when rated current is applied.



TYPICAL ELECTRICAL CHARACTERISTICS (T=25°C)



MEASURING METHOD / CONDITION

● Test Instrument:

L/Q: Agilent 4291B Impedance Analyzer

Test Fixture: Agilent 16192

Osc. Level: 500mV for $L \leq 8.2 \mu\text{H}$

100mV for $L \geq 10 \mu\text{H}$

SRF: Agilent 4291B Impedance Analyzer

R_{DC}: Agilent 34401A

● Test Condition:

< Unless otherwise specified >

Temperature: 15°C to 35°C Humidity: 25% to 85% RH

< In case of doubt >


Temperature: 25°C ± 2°C Humidity: 60% to 70% RH



MAG.LAYERS


PACKAGING

● Peel-off Force




The force for peeling off cover tape is 10 grams in the arrow direction.

● Dimension (Unit: mm)



TYPE	A	B	C	D	E	F
8 mm	178±1	60 +0.5 -0	-	13 ±0.2	9 ±0.5	12 ±0.5
12 mm	178±0.3	60 ±0.2	19.3 ±0.1	13.5 ±0.1	13.6 ±0.1	-




TYPE	SIZE	A	B	W	P	T		CHIPS/REEL
GMLI	201209	1.5	2.3	8	4	1.3,	*0.95±0.10	4000
	201212	1.5	2.3	8	4	1.3		4000

*For Paper Reels




MAG.LAYERS



● Taping Quantity

SERIES	2012
PCS/Reel	4000


● Tape Packing Case



No. of Reels	W	L	H
2	18±0.5	18±0.5	2.4±0.2
3	18±0.5	18±0.5	3.6±0.2
4	18±0.5	18±0.5	4.8±0.2
5	18±0.5	18±0.5	6.0±0.2

Unit: cm

RECOMMENDED PCB LAYOUT



Unit: mm



Type	2012
Size	L
	2.0
W	1.2
	0.8~1.2
A	0.8~1.2
B	0.8~1.2
C	0.9~1.6



MAG.LAYERS

RELIABILITY TEST

•MECHANICAL PERFORMANCE TEST

ITEM	SPECIFICATION	TEST CONDITION		
Solderability	More than 90% of the terminal electrode shall be covered with fresh solder.	Solder: Sn-3.0Ag-0.5Cu Solder Temperature: $245 \pm 5^{\circ}\text{C}$ Flux: Rosin Dip Time: 3 ± 1 Seconds		
Soldering Heat Resistance	The chip shall not crack. More than 75% of the terminal electrode shall be covered with solder.	Solder temperature : $260 \pm 5^{\circ}\text{C}$ Flux: Rosin Dip time: 10 ± 1 seconds		
Terminal Strength	The terminal electrode shall not be broken off nor the ferrite damaged. 	TYPE	W(KGF)	Time (Sec)
		GMLI-201209/12	0.6	30 ± 5
Bending Strength	No mechanical damage. The ferrite shall not be damaged. 	TYPE	A(MM)	P(KGF)
		GMLI-201209/12	1.4	1.0


• CLIMATIC TEST

ITEM	SPECIFICATION	TEST CONDITION		
Thermal Shock (Temperature Cycle)	No mechanical damage. Inductance shall be within $\pm 5\%$ of the initial value, and Q (shall be) within $\pm 30\%$ of the initial value.	Temperature: -40°C , 85°C for 30 minutes each, 100 cycles.		
Humidity Resistance		Temperature : 60°C Humidity: 95% RH Time: 1000 ± 12 HOURS		
High Temperature Resistance		Temperature : $85^{\circ}\text{C} \pm 2^{\circ}\text{C}$ Time: 1000 ± 12 hours		
Low Temperature Resistance		Temperature : $-40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ Time: 1000 ± 12 hours		

1. Operating Temperature Range: -55°C TO $+125^{\circ}\text{C}$
2. Storage Condition: The temperature should be within $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ and humidity should be less than 75% RH. The product should be used within 6 months from the time of delivery.



RECOMMENDED REFLOW SOLDERING PROFILE



Profile Feature		Sn-Pb	Pb-Free
Preheat	ts	60~120 seconds	60~180 seconds
	Tsmin	100°C	150°C
	Tsmax	150°C	200°C
Average ramp-up rate (Tsmax to TP)		3°C/second max.	3°C/second max.
Time main above	Temperature (TL)	183°C	217°C
	Time (tL)	60~150 seconds	60~150 seconds
Peak temperature (TP)		230°C	250~260°C
Time within 5 °C of actual peak temperature (tp)		10 seconds	10 seconds
Ramp-down rate		6°C/sec max.	6°C/sec max.
Time 25°C to peak temperature		6 minutes max.	8 minutes max.

NOTES

The contents of this data sheet are subject to change without notice. Please confirm the specifications and delivery conditions when placing your order.

