



CKT. NO. 1 INDICATOR RIB




HOUSING MATERIAL: 94V-0 UNFILLED POLYESTER
COLOR: WHITE

TERMINAL MATERIAL: PHOSPHOR BRONZE

SECTION A-A

SECTION B-B



NOTES:

1. ASSEMBLY NO. 71690-23** SHOWN FOR ILLUSTRATION.
2. MATES WITH PART NUMBER 71694-****.
3. SEE SHEET 2 FOR PART NUMBERS AND THEIR CONFIGURATIONS.
4. PLATINGS:
 - (185) .000100/(0.00254) MIN. TIN LEAD OVERALL, OVER NICKEL OVERALL.
 - (578) .000015/(0.00038) MIN. SELECT GOLD AND .000150/(0.00380) MIN. SELECT TIN/LEAD OVER NICKEL OVERALL.
5. ITEM NUMBERS PRECEDED BY AN "X" IN THE CHART ARE NOT AVAILABLE.
6. RECOMMENDED FOR USE WITH UL # 1007 STYLE WIRE.
7. OPTIONAL COVER NUMBERS: 71161-***01 (FEED THRU) OR -***02 (FEED TO VERSION).
8. SEE SHEET 7 FOR PANEL CUTOUT DETAIL.
9. PART CONFORMS TO SPECIFICATION NO. PS-71690-001.
10. RECYCLE LOGO: >PBT< FR TO BE LOCATED IN THIS AREA.
11. IDT SLOT IDENTIFIER COLOR STRIPE TO BE LOCATED ON THIS SURFACE. ID PER CHART BELOW.

WIRE GAUGE	ID COLOR
18	FLRSCNT MAGENTA
20	BLUE
22	GREEN
24	BLACK

12. SEE SMES-71690-0000 FOR TERMINATION SPECIFICATIONS.
13. PACKAGE PER PK-71690-0000.

K	CHANGE PROD SPEC ECR UDT2001-0195 KMS 9/22/2000
J	ALL WHITE MAT'L PER ECR # U71026 ELO 9/7/2/26
I	18 AWG CLR CHANGE PER ECR UT0413 ELO 10/23/96
H	REVISED PER ECR U61437 PAR 05/15/96
G	REVISED PER ECR U61185 TSE 03/27/96
F	ADD GOLD ASSY'S PER ECR U51189 08/30/95 sas
E	REV CHARTS/D DIM PER ECR U60094 07/26/95 sas
D	ADD HOLE/NOTE 12 PER ECR U50939 04/17/95 sas
C	ADD DIM/REV NOTE PER ECR U40914 8/10/94 sas
B	ADD NOTE 11 PER ECR U40717 6/29/94 sas
A	FINAL RELEASE PER ECR U40514 4/25/94 sas

MFG. SH.	REV.	LTR.	REVISIONS
8	J	D	ADD HOLE/NOTE 12 PER ECR U50939 04/17/95 sas
7	H	C	ADD DIM/REV NOTE PER ECR U40914 8/10/94 sas
6	H	C	ADD DIM/REV NOTE PER ECR U40914 8/10/94 sas
5	H	C	ADD DIM/REV NOTE PER ECR U40914 8/10/94 sas
4	H	B	ADD NOTE 11 PER ECR U40717 6/29/94 sas
3	H	B	ADD NOTE 11 PER ECR U40717 6/29/94 sas
2	H	A	FINAL RELEASE PER ECR U40514 4/25/94 sas
1	K	A	FINAL RELEASE PER ECR U40514 4/25/94 sas

DIMENSIONS SHOWN (METRIC) INCH	
UNLESS OTHERWISE SPECIFIED TOLERANCES ANGULAR ± 1/2°	
3 PLACE ± .010	---
2 PLACE ± .014	± 0.25
1 PLACE ---	± 0.36

REVISION ONLY ON CAD SYSTEM

TITLE: MINI-FIT IDT SINGLE ROW PLUG SALES ASSEMBLY

MOLEX INCORPORATED SHEET NO. DATE
U.S.A. 1 OF 8 01/28/93


FILE NAME: S71690X1.DWG
SCALE: 4:1

SEE CHART SDA-71690-****

DRWG. NO. DIV. 1512
MOLX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION TC C

J	CKT SIZE	S T A T	ASSEMBLY ITEM NUMBER	PANEL MOUNTS	CONTACT PLATING	WIRE AWG	WIRE DESCRIPTION	DIMENSION A		DIMENSION B		DIMENSION C	
								INCH	(MM)	INCH	(MM)	INCH	(MM)
					TIN								
	2		71690-1001	NO	185	18	SOLID,FUSED STRANDED,STRANDED	0.490	(12.45)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1003	NO	185	20		0.490	(12.45)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1004	NO	185	22		0.490	(12.45)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1005	NO	185	24		0.490	(12.45)	0.378	(9.60)	0.1654	(4.20)
I					GOLD								
	2		71690-1007	NO	578	18		0.490	(12.45)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1009	NO	578	20		0.490	(12.45)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1010	NO	578	22		0.490	(12.45)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1011	NO	578	24		0.490	(12.45)	0.378	(9.60)	0.1654	(4.20)
H					TIN								
	2		71690-1101	YES	185	18		0.821	(20.48)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1103	YES	185	20		0.821	(20.48)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1104	YES	185	22		0.821	(20.48)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1105	YES	185	24		0.821	(20.48)	0.378	(9.60)	0.1654	(4.20)
G					GOLD								
	2		71690-1107	YES	578	18		0.821	(20.48)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1109	YES	578	20		0.821	(20.48)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1110	YES	578	22		0.821	(20.48)	0.378	(9.60)	0.1654	(4.20)
	2		71690-1111	YES	578	24		0.821	(20.48)	0.378	(9.60)	0.1654	(4.20)
F					TIN								
	3		71690-1401	NO	185	18		0.655	(16.65)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1403	NO	185	20		0.655	(16.65)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1404	NO	185	22		0.655	(16.65)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1405	NO	185	24		0.655	(16.65)	0.543	(13.80)	0.3307	(8.40)
					GOLD								
E					TIN								
	3		71690-1407	NO	578	18		0.655	(16.65)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1409	NO	578	20		0.655	(16.65)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1410	NO	578	22		0.655	(16.65)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1411	NO	578	24		0.655	(16.65)	0.543	(13.80)	0.3307	(8.40)
D					TIN								
	3		71690-1501	YES	185	18		0.986	(25.05)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1503	YES	185	20		0.986	(25.05)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1504	YES	185	22		0.986	(25.05)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1505	YES	185	24		0.986	(25.05)	0.543	(13.80)	0.3307	(8.40)
					GOLD								
C					TIN								
	3		71690-1507	YES	578	18		0.986	(25.05)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1509	YES	578	20		0.986	(25.05)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1510	YES	578	22		0.986	(25.05)	0.543	(13.80)	0.3307	(8.40)
	3		71690-1511	YES	578	24	SOLID,FUSED STRANDED,STRANDED	0.986	(25.05)	0.543	(13.80)	0.3307	(8.40)


WITHOUT PANEL MOUNTS



H	SEE SHEET I
F	SEE SHEET I
D	SEE SHEET I
C	SEE SHEET I
A	SEE SHEET I
4	SEE SHEET I
3	SEE SHEET I
2	SEE SHEET I
I	SEE SHEET I

71690

POLARIZATION SCHEME



DIMENSIONS SHOWN (METRIC) INCH UNLESS OTHERWISE SPECIFIED TOLERANCES ANGULAR ± 1/2°		TITLE MINI-FIT IDT SINGLE ROW PLUG ASSEMBLY	
3 PLACE ± .010	---	MOLEX INCORPORATED	SHEET NO. 2
2 PLACE ± .014	± 0.25	135E.JLL	DATE 01/28/93
1 PLACE ---	± 0.36	69532	U.S.A.
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		PART NO. SEE CHART	
DRWG. NO. SDA-71690-*****		DRWG. NO. SDA-71690-*****	
DRWL. BY RWB	CHK'D. BY SAS	FILE NAME S71690X2	DIV. DIV.
APP'D. BY	SCALE :	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
		TC	C

CKT SIZE	S T A T	ASSEMBLY ITEM NUMBER	PANEL MOUNTS	CONTACT PLATING	WIRE AWG	WIRE DESCRIPTION	DIMENSION A		DIMENSION B		DIMENSION C	
							INCH	(MM)	INCH	(MM)	INCH	(MM)
8		71690-3401	NO	TIN 185	18	SOLID, FUSED STRANDED, STRANDED	1.482	(37.65)	1.370	(34.80)	1.1578	(29.40)
8		71690-3403	NO	185	20		1.482	(37.65)	1.370	(34.80)	1.1578	(29.40)
8		71690-3404	NO	185	22		1.482	(37.65)	1.370	(34.80)	1.1578	(29.40)
8		71690-3405	NO	185	24		1.482	(37.65)	1.370	(34.80)	1.1578	(29.40)
				GOLD								
8		71690-3407	NO	578	18		1.482	(37.65)	1.370	(34.80)	1.1578	(29.40)
8		71690-3409	NO	578	20		1.482	(37.65)	1.370	(34.80)	1.1578	(29.40)
8		71690-3410	NO	578	22		1.482	(37.65)	1.370	(34.80)	1.1578	(29.40)
8		71690-3411	NO	578	24		1.482	(37.65)	1.370	(34.80)	1.1578	(29.40)
				TIN								
8		71690-3501	YES	185	18		1.813	(46.05)	1.370	(34.80)	1.1578	(29.40)
8		71690-3503	YES	185	20		1.813	(46.05)	1.370	(34.80)	1.1578	(29.40)
8		71690-3504	YES	185	22		1.813	(46.05)	1.370	(34.80)	1.1578	(29.40)
8		71690-3505	YES	185	24		1.813	(46.05)	1.370	(34.80)	1.1578	(29.40)
				GOLD								
8		71690-3507	YES	578	18		1.813	(46.05)	1.370	(34.80)	1.1578	(29.40)
8		71690-3509	YES	578	20		1.813	(46.05)	1.370	(34.80)	1.1578	(29.40)
8		71690-3510	YES	578	22		1.813	(46.05)	1.370	(34.80)	1.1578	(29.40)
8		71690-3511	YES	578	24		1.813	(46.05)	1.370	(34.80)	1.1578	(29.40)
				TIN								
9		71690-3801	NO	185	18		1.648	(41.85)	1.535	(39.00)	1.3232	(33.60)
9		71690-3803	NO	185	20		1.648	(41.85)	1.535	(39.00)	1.3232	(33.60)
9		71690-3804	NO	185	22		1.648	(41.85)	1.535	(39.00)	1.3232	(33.60)
9		71690-3805	NO	185	24		1.648	(41.85)	1.535	(39.00)	1.3232	(33.60)
				GOLD								
9		71690-3807	NO	578	18		1.648	(41.85)	1.535	(39.00)	1.3232	(33.60)
9		71690-3809	NO	578	20		1.648	(41.85)	1.535	(39.00)	1.3232	(33.60)
9		71690-3810	NO	578	22		1.648	(41.85)	1.535	(39.00)	1.3232	(33.60)
9		71690-3811	NO	578	24		1.648	(41.85)	1.535	(39.00)	1.3232	(33.60)
				TIN								
9		71690-3901	YES	185	18		1.978	(50.25)	1.535	(39.00)	1.3232	(33.60)
9		71690-3903	YES	185	20		1.978	(50.25)	1.535	(39.00)	1.3232	(33.60)
9		71690-3904	YES	185	22		1.978	(50.25)	1.535	(39.00)	1.3232	(33.60)
9		71690-3905	YES	185	24		1.978	(50.25)	1.535	(39.00)	1.3232	(33.60)
				GOLD								
9		71690-3907	YES	578	18		1.978	(50.25)	1.535	(39.00)	1.3232	(33.60)
9		71690-3909	YES	578	20		1.978	(50.25)	1.535	(39.00)	1.3232	(33.60)
9		71690-3910	YES	578	22		1.978	(50.25)	1.535	(39.00)	1.3232	(33.60)
9		71690-3911	YES	578	24	SOLID, FUSED STRANDED, STRANDED	1.978	(50.25)	1.535	(39.00)	1.3232	(33.60)

71690	
H	SEE SHEET I
F	SEE SHEET I
E	SEE SHEET I
A	SEE SHEET I
4	SEE SHEET I
2	SEE SHEET I
1	SEE SHEET I

MFG.	SH.	REV.	LTR.	REVISIONS
------	-----	------	------	-----------

DIMENSIONS SHOWN (METRIC) INCH
UNLESS OTHERWISE SPECIFIED
TOLERANCES ANGULAR ± 1/2°

3 PLACE ± .010	---
2 PLACE ± .014	± 0.25
1 PLACE ---	± 0.36

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DRWG. BY: RWB CHK'D. BY: SAS
APP'D. BY: SCALE: ;

MOLEX INCORPORATED
1151E, ILL. 60532 U.S.A.

DATE: 03/10/93

PART NO. SDA-71690-****

SEE CHART

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.



MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

WIRE TERMINATION SPECIFICATION

1.0 APPLICABLE DRAWINGS:

THIS SPECIFICATION APPLIES TO A-71690 AND A-71694 SERIES OF INSULATION DISPLACEMENT CONNECTORS.

2.0 SCOPE:

THIS SPECIFICATION IS DESIGNED TO INSURE THE PROPER TERMINATION AND PERFORMANCE OF THE A-71690 AND A-71694 SERIES OF INSULATION DISPLACEMENT CONNECTORS.

3.0 GENERAL:

THE .1654/(4.20) CENTER INSULATION DISPLACEMENT CONNECTOR SYSTEM IS DESIGNED TO INTERCONNECT DISCRETE WIRE AS OUTLINED IN THIS SPECIFICATION.

4.0 CONDUCTOR REQUIREMENTS:

4.1 CONDUCTOR SIZE IDENTIFICATION:

CONDUCTOR SIZE	CONDUCTOR STYLE	HOUSING ID COLOR (SEE FIG. 4)	TERMINAL ID HOLE POSITION (SEE FIG.8; SHT.5)
18 AWG	STRANDED WITH TOPCOAT,FUSED, SOLID	RED	POSITION 1
20 AWG	STRANDED WITH TOPCOAT,FUSED, SOLID	BLUE	POSITION 2
22 AWG	STRANDED WITH TOPCOAT,FUSED, SOLID	GREEN	POSITION 3
24 AWG	STRANDED WITH TOPCOAT,FUSED, SOLID	BLACK	POSITION 4

RECOMMENDED UL STYLE: 1007, 1061

4.2 INSULATION REQUIREMENTS:

INSULATION DIAMETER: .090 MAX

INSULATION HARDNESS: 85 MAX ON THE SHORE A SCALE

5.0 TERMINATION REQUIREMENTS:

5.1 CABLE INSERTION DEPTH:

THE CABLE SHOULD BE INSERTED TO DEPTH OF .140/(3.56)* FROM THE TOP OF THE HOUSING TO THE TOP OF THE WIRE (SEE FIGURE 2). WIRE MUST BE LOCATED BELOW THE BOTTOM OF EAGLES.

* TERMINATION DEPTH FOR THE 24 AWG WIRES IN THE FOLLOWING ASSEMBLIES TO BE .138±.005/(3.51±0.13); 71690-6008 AND 71694-2402.

STRAIN RELIEF




FIGURE 2

REV.	B	A	B	B	B
SHT.	1	2	3	4	5

FILE NAME

T71690X1

□ = 0

◼ = 0

REVISE ONLY ON CAD SYSTEM

REV.

B

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT.

1 OF 5

DRWG. NO. SMES-71690-0000

DRWG. NO. SMES-71690-0000



WIRE TERMINATION SPECIFICATION

5.2 WIRE CUT OFF

IN THE FEED-TO VERSION THE WIRE MUST BE DISPLACED IN BOTH INSULATION DISPLACEMENT SLOTS AND MUST PROTRUDE THROUGH THE SECONDARY SLOT BY $(1.52)/.060$ MIN. AS SHOWN IN FIGURE 3.




FIGURE 3

5.3 HORIZONTAL PULL OUT FORCE

THE CONNECTOR MUST MAINTAIN THE FOLLOWING MIN. PULL OUT VALUES WHEN A FORCE IS APPLIED AT A RATE OF 1 INCH PER MINUTE TO THE CABLE IN A DIRECTION PERPENDICULAR TO THE INSULATION DISPLACEMENT SECTION. AS SHOWN IN FIGURE 4. (NOTE CABLE MUST BE SLIT TO FORM INDIVIDUAL CONDUCTORS AFTER TERMINATION BUT PRIOR TO TESTING).

AWG	PULL FORCE
18 AWG	14.0 LBS. MIN.
20 AWG	TBD
22 AWG	TBD
24 AWG	8.0 LBS. MIN.




FIGURE 4

5.4 VERTICAL PULL OUT FORCE

THE CONNECTOR MUST MAINTAIN THE FOLLOWING MIN. PULL OUT VALUES WHEN A FORCE IS APPLIED AT A RATE OF 1 INCH PER MINUTE TO THE CABLE IN A DIRECTION PARALLEL TO THE INSULATION DISPLACEMENT SECTION. AS SHOWN IN FIGURE 5. (NOTE CABLE MUST BE SLIT TO FORM INDIVIDUAL CONDUCTORS AFTER TERMINATION BUT PRIOR TO TESTING).

AWG	PULL FORCE
18 AWG	5.0 LBS. MIN.
20 AWG	TBD
22 AWG	TBD
24 AWG	2.4 LBS. MIN.




FIGURE 5

REV.

SHT.

FILE NAME
T71690X2

REVISE ONLY ON CAD SYSTEM

REV.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT.




MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

WIRE TERMINATION SPECIFICATION

5.5 TORSIONAL RESISTANCE:

CONNECTOR MUST WITHSTAND A MAXIMUM TWIST ON A TERMINATED CABLE OF 130° WITHOUT DISTURBING THE INSULATION DISPLACEMENT INTERFACE IN THE PRIMARY OR SECONDARY SLOTS (SEE FIGURE 3) (NOTE CABLE MUST BE SLIT TO FORM INDIVIDUAL CONDUCTORS AFTER TERMINATION BUT PRIOR TO TESTING).




5.6 VISUAL INSPECTION:

AFTER TERMINATION, INSULATION DISPLACEMENT SECTION OF THE TERMINAL TO BE FREE OF TOOL MARKS FROM TERMINATION EQUIPMENT.

6.0 TERMINATION EVALUATION PROCEDURE:

STEP 1 - STRAIN RELIEF REMOVAL
REMOVE SHADED PORTION OF THE STRAIN RELIEF USING A RAZOR BLADE



STEP 2 - REMOVAL OF TERMINAL

INSERT THE REMOVAL TOOL (#HT60630A) INTO THE FRONT OF OF THE CONNECTOR (AROUND THE TERMINAL) TO DEPRESS LOCK TANGS. PUSH THE TERMINAL/WIRE OUT THE BACK OF THE CONNECTOR.

REV.

SHT.

FILE NAME
T71690X3



= 0



= 0

REVISE ONLY ON CAD SYSTEM

REV.

B

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT.

3

DRWG. NO. SMES-71690-0000


DRWG. NO. SMES-71690-0000




MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

WIRE TERMINATION SPECIFICATION


STEP 3 -CONDUCTOR REMOVAL
USING A SMALL PAIR OF PLIERS SPREAD THE I.D.T. SLOT
AND REMOVE CONDUCTOR BY PUSHING IN DIRECTION SHOWN



STEP 4 -REMOVING INSULATION
INSULATION TO BE REMOVED WITHOUT DISTURBING I.D.T. AREA



STEP 5 -CONDUCTOR INSPECTION
FOUR DEFORMATION POINTS MUST BE CLEARLY VISIBLE WHEN
USING 10X MAGNIFICATION



DRWG. NO. SMES-71690-0000

DRWG. NO. SMES-71690-0000

REV.	
SHT.	
FILE NAME T71690X4	

REVISE ONLY ON CAD SYSTEM

REV. B

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO
MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT. 4



MOLEX INCORPORATED
LISLE, ILL. 60532 U.S.A.

WIRE TERMINATION SPECIFICATION

LTR.	REVISIONS
A	RELEASED PER ECR U51189 09/15/95 SAS
B	UPDATED PER ECR U70308 ELO 09/20/96

STEP 1 -REMOVAL OF TERMINAL

INSERT THE REMOVAL TOOL(*HT60630A) INTO THE FRONT OF OF THE CONNECTOR (AROUND THE TERMINAL) TO DEPRESS LOCK TANGS.
PUSH THE TERMINAL/WIRE OUT THE BACK OF THE CONNECTOR.

STEP 2 -WIRE GAGE PER CHART

ID LETTER	WIRE GAGE
D	18 AWG
C	20 AWG
B	22 AWG
A	24 AWG




FIGURE 8

DRWG. NO. SMES-71690-0000

DRWG. NO. SMES-71690-0000

REV.
SHT.

FILE NAME
T71690X5

△ C = 0 ▴ = 0 REVISE ONLY ON CAD SYSTEM

REV. B

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SHT. 5