


RC4558, RC4558Y, RM4558, RV4558 DUAL GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS073 – MARCH 1976 – REVISED AUGUST 1991

- Continuous-Short-Circuit Protection
- Wide Common-Mode and Differential Voltage Ranges
- No Frequency Compensation Required
- Low Power Consumption
- No Latch-Up
- Unity Gain Bandwidth . . . 3 MHz Typ
- Gain and Phase Match Between Amplifiers
- Low Noise . . . 8 nV/√Hz Typ at 1 kHz
- Designed To Be Interchangeable With Raytheon RC4558, RM4558, and RV4558

D, DB, JG, P, OR PW PACKAGE
(TOP VIEW)



description

The RC4558, RM4558, and RV4558 are dual general-purpose operational amplifiers with each half electrically similar to the μ A741 except that offset null capability is not provided.

The high common-mode input voltage range and the absence of latch-up make these amplifiers ideal for voltage-follower applications. The devices are short-circuit protected and the internal frequency compensation ensures stability without external components.

The RC4558 is characterized for operation from 0°C to 70°C, the RM4558 is characterized for operation over the full military temperature range of -55°C to 125°C, and the RV4558 is characterized for operation from -40°C to 85°C.

AVAILABLE OPTIONS

TA	V _{IO} max AT 25°C	PACKAGED DEVICES					CHIP FORM (Y)
		SMALL OUTLINE (D)	SSOP (DBLE)	CERAMIC DIP (JG)	PLASTIC DIP (P)	SSOP (PWLE)	
0°C to 70°C	6 mV	RC4558D	RC4558DBLE	—	RC4558P	RC4558PWLE	RC4558Y
-40°C to 85°C	6 mV	RV4558D	—	—	RV4558P	—	—
-55°C to 125°C	6 mV	—	—	RM4558JG	—	—	—

The D package is available taped and reeled. Add the suffix R to the device type (e.g., RC4558DR). The DB and PW packages are available only left-end taped and reeled. RC4558Y is tested at 25°C.

8961724 0106213 579

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1991, Texas Instruments Incorporated

3-105



RC4558, RC4558Y, RM4558, RV4558 DUAL GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS073 – MARCH 1976 – REVISED AUGUST 1991

RC4558Y chip information

These chips, properly assembled, display characteristics similar to the RC4558. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. Chips may be mounted with conductive epoxy or a gold-silicon preform.

BONDING PAD ASSIGNMENTS



CHIP THICKNESS: 15 TYPICAL

BONDING PADS: 4 × 4 MINIMUM

$T_{jmax} = 150^{\circ}\text{C}$

TOLERANCES ARE $\pm 10\%$.

ALL DIMENSIONS ARE IN MILS.

PIN (4) IS INTERNALLY CONNECTED
TO BACKSIDE OF CHIP.

8961724 0106214 405


 **TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

RC4558, RC4558Y, RM4558, RV4558 DUAL GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS073 – MARCH 1976 – REVISED AUGUST 1991

schematic (each amplifier)



absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

	RC4558	RM4558	RV4558	UNIT
Supply voltage V_{CC+} (see Note 1)	18	22	18	V
Supply voltage V_{CC-} (see Note 1)	-18	-22	-18	V
Differential input voltage (see Note 2)	± 30	± 30	± 30	V
Input voltage (any input, see Notes 1 and 3)	± 15	± 15	± 15	V
Duration of output short circuit to ground, one amplifier at a time (see Note 4)	unlimited	unlimited	unlimited	
Continuous total dissipation	See Dissipation Rating Table			
Operating free-air temperature range	0 to 70	-55 to 125	-40 to 85	$^{\circ}\text{C}$
Storage temperature range	-65 to 150	-65 to 150	-65 to 150	$^{\circ}\text{C}$
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: JG package		300		$^{\circ}\text{C}$
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D, DB, P, or PW package	260		260	$^{\circ}\text{C}$

- NOTES: 1. All voltage values, unless otherwise noted, are with respect to the midpoint between V_{CC+} and V_{CC-} .
2. Differential voltages are at $\text{IN}+$ with respect to $\text{IN}-$.
3. The magnitude of the input voltage must never exceed the magnitude of the supply voltage or 15 V, whichever is less.
4. Temperature and/or supply voltages must be limited to ensure that the dissipation rating is not exceeded.

DISSIPATION RATING TABLE

	$T_A \leq 25^{\circ}\text{C}$	DERATING FACTOR	DERATE	$T_A = 70^{\circ}\text{C}$	$T_A = 85^{\circ}\text{C}$	$T_A = 125^{\circ}\text{C}$
PACKAGE	POWER RATING	ABOVE $T_A = 25^{\circ}\text{C}$	ABOVE T_A	POWER RATING	POWER RATING	POWER RATING
D	680 mW	5.8 mW/ $^{\circ}\text{C}$	33 $^{\circ}\text{C}$	464 mW	377 mW	N/A
DB or PW	525 mW	4.2 mW/ $^{\circ}\text{C}$	25 $^{\circ}\text{C}$	336 mW	N/A	N/A
JG	680 mW	8.4 mW/ $^{\circ}\text{C}$	69 $^{\circ}\text{C}$	672 mW	546 mW	210 mW
P	680 mW	8.0 mW/ $^{\circ}\text{C}$	65 $^{\circ}\text{C}$	640 mW	520 mW	N/A

8961724 0106215 341



**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

3-107

RC4558, RC4558Y, RM4558, RV4558 DUAL GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS073 – MARCH 1976 – REVISED AUGUST 1991

recommended operating conditions

	MIN	MAX	UNIT
Supply voltage, V_{CC+}	5	15	V
Supply voltage, V_{CC-}	-5	-15	V

electrical characteristics at specified free-air temperature, $V_{CC+} = 15$ V, $V_{CC-} = -15$ V

PARAMETER			TEST CONDITIONS†	RC4558			RM4558			RV4558			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
V _{IO}	Input offset voltage	V _O = 0	25°C	0.5		6	0.5		5	0.5		6	mV
			Full range			7.5			6			7.5	
I _{IO}	Input offset current	V _O = 0	25°C	5		200	5		200	5		200	nA
			Full range			300			500			500	
I _{IB}	Input bias current	V _O = 0	25°C	150		500	140		500	140		500	nA
			Full range			800			1500			1500	
V _{ICR}	Common-mode input voltage range		25°C	±12	±14		±12	±14		±12	±14		V
V _{OM}	Maximum output voltage swing	R _L = 10 kΩ	25°C	±12	±14		±12	±14		±12	±14		V
		R _L = 2 kΩ	25°C	±10	±13		±10	±13		±10	±13		
		R _L ≥ 2 kΩ	Full range	±10			±10			±10			
A _{VD}	Large-signal differential voltage amplification	R _L ≥ 2 kΩ, V _O = ±10 V	25°C	20	300		50	350		20	300		V/mV
			Full range	15			25			15			
B ₁	Unity-gain bandwidth		25°C			3	2	3.5				3	MHz
r _i	Input resistance		25°C	0.3	5		0.3	5		0.3	5		MΩ
CMRR	Common-mode rejection ratio		25°C	70	90		70	90		70	90		dB
k _{SVS}	Supply voltage sensitivity (ΔV _{IO} /ΔV _{CC})	V _{CC} = ±15 V to ±9 V	25°C		30	150		30	150		30	150	μV/V
V _n	Equivalent input noise voltage (closed loop)	A _{VD} = 100, R _S = 100 Ω, f = 1 kHz, BW = 1 Hz	25°C			8			8			8	nV/√Hz
I _{CC}	Supply current (both amplifiers)	V _O = 0, No load	25°C		2.5	5.6		2.5	5.6		2.5	5.6	mA
			MIN T _A		3	6.6		3	6.6		3	6.6	
			MAX T _A		2.3	5		2	5		2.3	5	
P _D	Total power dissipation (both amplifiers)	V _O = 0, No load	25°C		75	170		75	170		75	170	mW
			MIN T _A		90	200		90	200		90	200	
			MAX T _A		70	150		60	150		70	150	
V _{O1} /V _{O2}	Crosstalk attenuation	Open loop	R _S = 1 kΩ, f = 10 kHz	25°C	85		85		85		dB		
		A _{VD} = 100		105		105		105					

† All characteristics are measured under open-loop conditions with zero common-mode input voltage unless otherwise specified. Full range is 0°C to 70°C for RC4558, -55°C to 125°C for RM4558, and -40°C to 85°C for RV4558. Minimum T_A is 0°C for RC4558, -55°C for RM4558, and -40°C for RV4558. Maximum T_A is 70°C for RC4558, 125°C for RM4558, and 85°C for RV4558.

8961724 0106216 288



RC4558, RC4558Y, RM4558, RV4558 DUAL GENERAL-PURPOSE OPERATIONAL AMPLIFIERS

SLOS073 – MARCH 1976 – REVISED AUGUST 1991

operating characteristics, $V_{CC+} = 15\text{ V}$, $V_{CC-} = -15\text{ V}$, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
t_r Rise time	$V_I = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$, $C_L = 100\text{ pF}$	0.13			ns
Overshoot		5%			
SR Slew rate at unity gain	$V_I = 10\text{ V}$, $R_L = 2\text{ k}\Omega$, $C_L = 100\text{ pF}$	1.1	1.7		V/ μs

electrical characteristics, $V_{CC+} = 15\text{ V}$, $V_{CC-} = -15\text{ V}$, $T_A = 25^\circ\text{C}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	RC4558Y			UNIT
		MIN	TYP	MAX	
V_{IO} Input offset voltage	$V_O = 0$	0.5	6		mV
I_{IO} Input offset current	$V_O = 0$	5	200		nA
I_{IB} Input bias current	$V_O = 0$	150	500		nA
V_{ICR} Common-mode input voltage range		± 12	± 14		V
V_{OM} Maximum output voltage swing	$R_L = 10\text{ k}\Omega$	± 12	± 14		V
	$R_L = 2\text{ k}\Omega$	± 12	± 13		
A_{VD} Large-signal differential voltage amplification	$R_L = 2\text{ k}\Omega$, $V_O = \pm 10\text{ V}$	20	300		V/mV
B_1 Unity-gain bandwidth		3			MHz
r_i Input resistance		0.3	5		M Ω
CMRR Common-mode rejection ratio		70	90		dB
k_{SVS} Supply voltage sensitivity ($\Delta V_{IO}/\Delta V_{CC}$)	$V_{CC} = \pm 15\text{ V}$ to $\pm 9\text{ V}$	30	150		$\mu\text{V/V}$
V_n Equivalent input noise voltage (closed-loop)	$A_{VD} = 100$, $R_S = 100\text{ }\Omega$, $f = 1\text{ kHz}$, $BW = 1\text{ Hz}$	8			nV $\sqrt{\text{Hz}}$
I_{CC} Supply current (both amplifiers)	$V_O = 0$, No load	2.5	5.6		mA
P_D Total power dissipation (both amplifiers)	$V_O = 0$, No load	75	170		mW
V_{O1}/V_{O2} Crosstalk attenuation	Open loop	85			dB
	$A_{VD} = 100$	105			

† All characteristics are measured under open-loop conditions with zero common-mode input voltage unless otherwise specified.

operating characteristics, $V_{CC+} = 15\text{ V}$, $V_{CC-} = -15\text{ V}$, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
t_r Rise time	$V_I = 20\text{ mV}$, $R_L = 2\text{ k}\Omega$, $C_L = 100\text{ pF}$	0.13			ns
Overshoot		5%			
SR Slew rate at unity gain	$V_I = 10\text{ V}$, $R_L = 2\text{ k}\Omega$, $C_L = 100\text{ pF}$	1.1	1.7		V/ μs

8961724 0106217 114



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265