

Phase Control Thyristor Stud Types N0416S#020 to N0416S#080

The data sheet on the subsequent pages of this document is a scanned copy of existing data for this product.
(Rating Report 93NR1 Issue 1)

This data reflects the old part number for this product which is: N275PH02-08.
This part number must **NOT** be used for ordering purposes – please use the ordering particulars detailed below.

The limitations of this data are as follows:
Only SC outline drawing (W18) in datasheet
No reverse recovery information available

The following links will direct you to the appropriate outline drawings
[Outline W18](#) – 3/4" Ceramic stud
[Outline W25](#) – 3/4" Ceramic stud removed

Where any information on the product matrix page differs from that in the following data, the product matrix must be considered correct

An electronic data sheet for this product is presently in preparation.

For further information on this product, please contact your local ASM or distributor.

Alternatively, please contact Westcode as detailed below.

Ordering Particulars			
N0416	S#	◆◆	0
Fixed Type Code	SC – 3/4" Ceramic stud SD – 3/4" Ceramic stud removed	Voltage code V _{RRM} /100 02-08	Fixed Code
Typical Order Code: N0416SC080, 3/4" Ceramic stud, 800V V _{RRM} /V _{DRM}			

<p>IXYS Semiconductor GmbH Edisonstraße 15 D-68623 Lampertheim Tel: +49 6206 503-0 Fax: +49 6206 503-627 E-mail: marcom@ixys.de</p>	<p style="margin: 0;">An IXYS Company</p> <p style="margin: 0;">www.westcode.com</p> <p style="margin: 0;">www.ixys.com</p>	<p>Westcode Semiconductors Ltd Langley Park Way, Langley Park, Chippenham, Wiltshire, SN15 1GE. Tel: +44 (0)1249 444524 Fax: +44 (0)1249 659448 E-mail: WSL.sales@westcode.com</p>	
<p>IXYS Corporation 3540 Bassett Street Santa Clara CA 95054 USA Tel: +1 (408) 982 0700 Fax: +1 (408) 496 0670 E-mail: sales@ixys.net</p>		<p>Westcode Semiconductors Inc 3270 Cherry Avenue Long Beach CA 90807 USA Tel: +1 (562) 595 6971 Fax: +1 (562) 595 8182 E-mail: WSI.sales@westcode.com</p>	
<p>The information contained herein is confidential and is protected by Copyright. The information may not be used or disclosed except with the written permission of and in the manner permitted by the proprietors Westcode Semiconductors Ltd.</p> <p>In the interest of product improvement, Westcode reserves the right to change specifications at any time without prior notice.</p> <p>Devices with a suffix code (2-letter, 3-letter or letter/digit/letter combination) added to their generic code are not necessarily subject to the conditions and limits contained in this report.</p>			<p>© Westcode Semiconductors Ltd.</p>

QUALITY AND EVALUATION LABORATORY

Rating Report: 93TR1

Date: 28th June, 1993

Origin: Q.E.L.

Pages: 12

Thyristor Type N275PH02-08

Written by: *M. Baker*
M. Baker

Checked: *BH*

Approved: *[Signature]*

RATINGS

Voltage Grades

V_{DSM}	: 02-08
V_{RSM}	: 200-800V
V_{DRM}, V_{RRM}	: 300-900V
$I_{T(AV)}$: Single phase; 50 Hz, 180° sinewave $T_{CASE} = 94^{\circ}C$: 200-800V
$I_{T(rms)}$ Max.	: 226A
$I_{T d.c.}$ Max.	: 355A
I_{TSM} : t = 10 ms half sinewave; $T_{J(initial)} = 125^{\circ}C$; $V_{RM} = 0.6 V_{RRM(MAX)}$: 355A
I_{TSM} : t = 10 ms half sinewave; $T_{J(initial)} = 125^{\circ}C$; $V_{RM} \leq 10V$: 6000A
I^2t : t = 10 ms; $T_{J(initial)} = 125^{\circ}C$; $V_{RM} = 0.6V_{RRM(MAX)}$: 6600A
I^2t : t = 10 ms; $T_{J(initial)} = 125^{\circ}C$; $V_{RM} \leq 10V$: 180 x 10 ³ A ² SECS
I^2t : t = 3 ms; $T_{J(initial)} = 125^{\circ}C$; $V_{RM} \leq 10V$: 218 x 10 ³ A ² SECS
di/dt : (Repetitive) $T_J = 125^{\circ}C$; Gate: 20V, 20ohms Rise time 1 μ S	: 165 x 10 ³ A ² SECS
I_{FGM} : Anode positive with respect to cathode	: 500A/ μ S
V_{FGM} : Anode positive with respect to cathode	: 19A
V_{RGM} :	: 18V
$P_G(AV)$:	: 5V
P_{GM} :	: 2W
V_{GD} :	: 100W
T_C operating range	: 0.25V
T_{stg} Non operating	: -40°C to 125°C
	: -40°C to 150°C

R.R. No.	93TR1
R.R. Issue	1
Page Issue	1

CHARACTERISTICS (maximum values unless stated otherwise)

I_{GT} : $T_J = 25^\circ C$)		
I_H : $T_J = 25^\circ C$)	$V_A = 6V; I_A = 1A$: 150mA
V_{GT} : $T_J = 25^\circ C$)		: 400mA
V_O : $T_J = 125^\circ C$: 3V
r_T : $T_J = 125^\circ C$: 0.85V
A : $T_J = 25^\circ C$: 0.535m Ω
B : $T_J = 25^\circ C$:
C : $T_J = 25^\circ C$:
D : $T_J = 25^\circ C$:
A : (Constant) $T_J = 125^\circ C$:
B : (B x ln (i)) $T_J = 125^\circ C$:
C : (C x i) $T_J = 125^\circ C$:
D : (D x \sqrt{i}) $T_J = 125^\circ C$:
V_{TM} : $I_{TM} = 690A. T_J = 125^\circ C$: 1.22V
$R_{th(J-C)}$: 0.12 K/W
$R_{th(C-HS)}$: 0.04 K/W
dv/dt : Linear ramp to $0.8V_{DRM(max)}$; $T_J = 125^\circ C$; Gate O/C repetitive		: 200V/ μS *
I_{DRM} : $T_J = 125^\circ C$; $V_{DM} = V_{DRM(max)}$: 20mA
I_{RRM} : $T_J = 125^\circ C$; $V_{RM} = V_{RRM(max)}$: 20mA
Q_{RA} : $I_{TM} =$: dI/dt = A/ μS , 50% chord value $V_{RM} = 50V; T_J = 125^\circ C$:
t_q : $I_{TM} =$: dI/dt = A/ μS ; $T_J = 125^\circ C$; $V_{RM} = 50V$ dv/dt = 200V/ μS to $0.8 V_{DRM}$ dv/dt = 20V/ μS to $0.8 V_{DRM}$:
Mounting Torque		: 2.50 - 2.77 Kgm
Outline Drawing		: 101A225
Outline (JEDEC No.)		:

Extension of Turn-off Time

This Report is applicable to other t_q /reapplied dv/dt combinations when supply has been agreed by Sales/Production.

*Repetitive dv/dt

Higher dv/dt selections are available up to 1000V/ μS on request.

R.R. No.	93TR1
R.R. Issue	1
Page Issue	1

<u>CONTENTS</u>	<u>Page</u>
Ratings	1
Characteristics	2
Contents	3
Voltage Ratings	4
Dissipation and Heatsink Temperature vs Mean Current	5, 6
Limit On-state Characteristics	7
Transient Thermal Impedance Characteristics	8
Gate Characteristics and Gate Trigger Limits	9, 10
Surge Current and I^2t vs Duration of Surge	11
Outline Drawing	12

R.R. No.	93TR1
R.R. Issue	1
Page Issue	1

Voltage Ratings


Voltage Grade 'H'	V_{DSM}	V_{DRM} V	V_{RRM}	V_{RSM} V	V_D V_R DC
02		200		300	140
03		300		400	210
04		400		500	260
06		600		700	420
08		800		900	560

Extension of Voltage Grades


This report is applicable to other and higher voltage grades when supply has been agreed by Sales/Production.

SINE WAVE



MAXIMUM FORWARD DISSIPATION (Watts)




MAXIMUM PERMISSIBLE CASE TEMP. (°C)




SQUARE WAVE




ON-STATE CHARACTERISTIC OF LIMIT DEVICE







GATE CHARACTERISTICS AT 25°C JUNCTION TEMPERATURE



GATE TRIGGERING CHARACTERISTICS
 (TRIGGER POINTS OF ALL THYRISTORS LIE IN THE AREAS SHOWN)



MAXIMUM NON REPETITIVE SURGE CURRENT AT INITIAL JUNCTION TEMPERATURE 125°C
 GATE MAY TEMPORARILY LOSE CONTROL OF CONDUCTION ANGLE



TOTAL PEAK HALF SINE SURGE CURRENT (KA)

DURATION OF SURGE (me)

DURATION OF SURGE (cycles at 50 Hz)


SCALE	1/1
DRN	<i>[Signature]</i>
CHKD	<i>[Signature]</i>
APPD	
S	NI

INTERNATIONAL OUTLINE No.
 WEIGHT. 280 GRAMS APPX.
 FINISH. BRIGHT NICKEL PLATE. - 12 -
 DEVICE MARKING INCLUDES MONOGRAM, TYPE No., SPEC.
 No. AND POLARITY SYMBOL.
 DEVICE MOUNTING: MOUNTING TORQUE
 27-24.5 Nm (2.77-2.5 kgF-m).
 THREAD MUST NOT BE LUBRICATED.

TYPE NUMBER	
N170P	P200P
N195P	P202P
N275P	P204P
	P205P
	P214P
	P215P
	P270P

NOTES.

G.A. DRG. No. 103A162



THE INFORMATION CONTAINED IN THIS DRAWING IS SUPPLIED IN CONFIDENCE AND IS PROTECTED BY COPYRIGHT. THE INFORMATION MAY NOT BE DISCLOSED EXCEPT WITH THE WRITTEN PERMISSION OF AND IN MANNER PERMITTED BY THE PROPRIETORS, WESTINGHOUSE BRAKE AND SIGNAL CO. LTD.

WESTINGHOUSE BRAKE AND SIGNAL CO. LTD.
 CHIPPENHAM, WILTSHIRE, SN15 1JD, ENGLAND.

 WESTCODE®
 SEMICONDUCTORS

THIRD ANGLE PROJECTION


DIMNS. IN MILLIMETRES

DRG. No. 101A225

ISS	REVISIONS
1	19.9.78
2	17.11.78 M670 TYPE N° ADDED
3	Ø 8.8/8.2 HOLE WAS 10.7/10.2 H44
4	17.12.79 M817 19 WAS 21.4 H44
5	27.11.84 M1218 FIN WAS ET. PK
6	10.10.88. RED & WHITE WERE VIOLET & ORANGE. A4/F