

TV-Stereo Sound

TDA 6612-2



Preliminary Data

Bipolar IC

Features

The TDA 6612-2 represents a complete TV-stereo system controlled by the I²C Bus according to German TV-Stereo standard.

- All functions inclusive matrix adjustment are I²C Bus controlled
- Inputs for AM sound or NICAM
- SCART-interface
- Independent headphones
- Universal clock generation circuit build-in
- Clipping detector build-in
- Volume control
- High signal-to-noise ratio
- Extremely low total harmonic distortions
- High security for the detection of the identification signals because of the digital interference suppression and the very narrow bandwidth



Type	Ordering Code	Package
TDA 6612-2	Q67000-A5097	P-DIP-28-3
TDA 6612-2X	Q67000-A5194	P-DSO-28-1

The IC is divided into three functional blocks

1 Stereo Sound Processing with High Performance (exceeds DIN 45500; suitable for NICAM and CD)

- a) Matrix for G-standard with crosstalk compensation controlled via the I²C Bus
- b) Additional single channel AF input (for e.g. AF signal according to L-standard)
- c) Stereo SCART interface according to FTZ-official specification
- d) Stereo loudspeaker signal section with Ch1/Ch2 switch, bass/treble control, quasi stereo/stereo base width expansion and separate loudspeaker volume control for left and right (balance)
- e) Separate stereo head phone signal section with Ch1/Ch2 switch and volume control

2 TV-Sound Identification Signal Decoder Consisting of:

- a) Active pilot signal filter
- b) Phase independent rectifier with very narrow bandwidth for evaluation of the identification signal
- c) Digital integrator to reduce interferences by noise
- d) Multiplexer for cyclical switch over between "stereo" or "dual" evaluation
- e) Reference signal generation with externally synchronized PLL
 - synchronization with external H-sync pulse or 62.5-kHz clock
 - build-in crystal oscillator and external 4-MHz crystal
 - external 4-MHz (or 1-MHz) clock signal

3 Control Section for:

- a) I²C Bus interface with listen/talk function
- b) Control of the complete AF-sound signal detector
- c) Read access to the clipping detector
- d) Control of the identification signal decoder
- e) Reading of the status of the identification signal decoder
- f) Test modes

Circuit Description**Signal Section**

The audio signal processing in the matrix and the switch-over for multi channel TV-sound signals according to the two carrier system used in Germany takes place in the matrix and switching sections. Crosstalk compensation is carried out in the sound 1 input stage. The crosstalk compensation range has an adjustment range of ± 3 dB with a step width of 0.2 dB. In addition to the two inputs for the demodulated sound carrier a two channel SCART-input and an additional mono input (e.g. for demodulated L-standard sound) are provided. The two AF (pin 1 and pin 2) inputs can be bypassed internally in such a way that decoded stereo sound of other audio systems (NICAM) can be processed. The switching section includes also the SCART-output with the possibility to select the sound 1 or 2 during the "dual" mode. The Ch1/Ch2-switches for the loudspeaker and headphone outputs are independently switchable.

In the signal path for the volume control unit output there is the Ch1/Ch2-switch followed by two different volume control units. The first has a control range from 0 to -15 dB with a step width of 1.25 dB. In conjunction with the main volume control after bass and treble control a high immunity against overdriving the output stage is reached. The first volume control is used as a "pre-stage" of the main volume control in conjunction with the clipping detector. This section is followed by a switchable quasi stereo stage which provides a stereophonic audio effect with mono signals due to a 180° phase shift at medium frequencies (about 1 kHz) in one channel. The following bass control has a control range of $+15/-12$ dB with a step width of 3 dB. The cut-off frequency for each channel is set with an external capacitor. The implemented switchable circuit for stereo base width expansion provides a three dimensional aural reception. This is realized with a 50% frequency dependent crosstalk with opposite phase of the signal between both channels. The circuit operates with the same cut-off frequency as the bass control, but the function is widely independent. The treble control has a step width of 3 dB with a control range of $+/-12$ dB. The cut-off frequency of the treble control is derived from one capacitor for each channel. The loudspeaker signal path is terminated with the loudspeaker control, independently adjustable for left and right. With 57 steps of 1.25 dB the adjustment range is 70 dB, where step 57 activates the "MUTE" function. Functions such as "balance" or "loudness" are realized by software and adjustment of the appropriate tone and volume controls. In the volume control unit there is a clipping detector. The status of the clipping detector can be evaluated via the I²C Bus. Therefore it is possible to implement an automatic volume control using the clipping detector and software implemented into the controller.

After every evaluation the clipping bit is reset. Therefore after a read access to the clipping bit a new evaluation of the clipping detector status is possible.

The signal path for the headphones contains a volume control after the Ch1/Ch2-switch with a common adjustment for left and right. Thirty two steps of 2 dB give an adjustment range of 62 dB (31 x 2 dB = 62 dB, the 32nd step is MUTE).

Identification Signal Decoder

The input of the identification signal decoder consists of an op-amp for the pilot signal with its side bands. An external LC-circuit is used. The signal is then passed to a phase independent active band-pass filter with a very narrow bandwidth (adjustable externally). This filter detects whether the lower side band of the pilot carrier, which is modulated with the identification signal, is present. The

center frequency of the filter is switched between "dual" and "stereo" by a multiplexer. The multiplexing frequency is adjustable by software. If a side band is detected, the multiplexer stops. The interferences on the first "detected" criterion are suppressed by a digital integrator with a following comparator and can be read out via I²C Bus (talk mode) as the "stereo" or "dual" mode. The control of the corresponding signal can be either directly internally or through the µC. All the necessary clock signal are derived from a fast setting PLL which is synchronized by a reference frequency. This reference frequency must be sufficiently close to the horizontal frequency, but a **rigid phase coupling is not required**. Therefore, alternatively the use of a crystal controlled 62.5-kHz frequency commonly found in PLL-tuning systems is possible. A further alternative for the clock signal generation is a build-in crystal oscillator with an external 4-MHz crystal or the use an external 1- or 4-MHz clock frequency.

Control Section

All functions are controlled via an I²C Bus interface with "listen" / "talk" functions. The data bytes currently used are stored in a block of latches.

The telegram structure is formed in the following manner:

start condition - chip address - any number of bytes - stop condition

The following conditions apply to the data bytes:

Before the actual data byte (with the adjustment information), **always** an I²C Bus sub-address byte has to be transmitted. The I²C Bus interface however is interpreting this sub-address byte as a data byte.

Example: The headphone volume is to be increased in a number of steps.

Right	Wrong
Start condition	Start condition
Chip address 84 (Hex)	Chip address 84 (Hex)
Sub-addr. vol. HP 03 (Hex)	Sub-addr. vol. HP 03 (Hex)
Vol. step 8 08 (Hex)	Vol. step 8 08 (Hex)
Sub-addr. vol. HP 03 (Hex)	Vol. step 9 09 (Hex)
Vol. step 9 09 (Hex)	Vol. step 10 0A (Hex)
Sub-addr. vol. HP 03 (Hex)	Stop condition
Vol. step 10 0A (Hex)	
Stop condition	

Within a telegram (i.e. without a new start condition) any different sub-addresses can be accessed. The changeover between "listen" and "talk" access to the IC however must always occur using the following sequence: stop condition - start condition - chip address. Before each read access always a start condition and chip address (talk) must be transmitted. The data to be read out are then loaded into the I²C Bus interface and can be transferred to the µC.

Chip Address

MSB	LSB
1	0	0	0	0	1	0	R/W

R/W = 0 → Read (Listen)

R/W = 1 → Write (Talk)

Subaddress Bytes

	MSB	LSB	
Volume input control	X	X	X	X	X	1	0	0
Volume of left speaker	X	X	X	X	X	0	0	1
Volume of right speaker	X	X	X	X	X	0	1	0
Volume of headphones	X	X	X	X	X	0	1	1
Treble / bass	X	X	X	X	X	1	0	1
Switch byte I	X	X	X	X	X	1	1	1
Switch byte II	X	X	X	X	X	0	0	0
Crosstalk adjustment	X	X	X	X	X	1	1	0

Control Bytes**a) Volume Input Control**

	MSB	LSB
Maximum volume	Qu-H	Ch1/Ch2EN	Ch1/Ch2sc	0	0	0	MUTE III
Max - 1	Qu-H	Ch1/Ch2EN	Ch1/Ch2sc	0	0	0	MUTE III
Min + 1	Qu-H	Ch1/Ch2EN	Ch1/Ch2sc	1	0	1	MUTE III
Minimum volume	Qu-H	Ch1/Ch2EN	Ch1/Ch2sc	1	1	0	MUTE III
Power ON	0	0	0	0	0	0	1

Qu-H = 0 PLL synchronization with H-pulse; power ON

Qu-H = 1 PLL synchronization with crystal oscillator,

additionally the bit "H-pulse" has to be set to "H" in switch byte II

Ch1/Ch2EN	Ch1/Ch2sc	SCART output pin 9	SCART output pin 10
0	0	sound 1	sound 2
0	1	sound 2	sound 1
1	0	sound 1	sound 1
1	1	sound 2	sound 2

Ch1/Ch2EN, Ch1/Ch2sc are only activated if the matrix is in the dual mode
(switch byte II: matrix 0 = 1 and matrix 1 = 0 or matrix 0 = 1 , matrix 1 = 1 and the identification decoder is in the mode "dual")

MUTE III = 0 SCART output are muted.

MUTE III = 1 SCART output ON; power ON

(will be overwritten by MUTE 1 = 0 equal to all audio outputs muted)

MUTE III is "or" wired with MUTE I.

b) Volume of Left / Right Loudspeaker

	MSB	LSB
Maximum volume	X	X	1	1	1	1	1	1
Max -1	X	X	1	1	1	1	1	0
Max -15	X	X	1	1	0	0	0	0
Max -55	X	X	0	0	1	0	0	0
MUTE	X	X	0	0	0	1	1	1
MUTE	X	X	0	0	0	0	0	0
MUTE	X	X	0	0	0	X	X	X
Power ON	0	0	0	0	0	0	0	1

c) Volume of Headphones

	MSB	LSB
Maximum volume	T2	T1	T0	1	1	1	1	1
Max -1	T2	T1	T0	1	1	1	1	0
Max -15	T2	T1	T0	1	0	0	0	0
Max -31	T2	T1	T0	0	0	0	0	1
MUTE	T2	T1	T0	0	0	0	0	0
Power ON	0	0	0	0	0	0	0	1

T0, T2 are test bits; these must be set to 0 for normal operation

d) Crosstalk Compensation Matrix (sound 1)

	MSB	LSB
Max. amplification	0	0	0	1	1	1	1	1
Max -1	0	0	0	1	1	1	1	0
Gain 0 dB	0	0	0	1	0	0	0	0
Min. gain	0	0	0	0	0	0	0	1
Min. gain	0	0	0	0	0	0	0	X
Power ON	0	0	0	0	0	0	0	1

e) Treble/Bass

	MSB	LSB
Linear	1	0	0	0	1	0	0	0
Max. treble, lin. bass	1	1	0	0	1	0	0	0
Max. treble, lin. bass	1	1	X	X	1	0	0	0
Min. treble, lin. bass	0	1	0	0	1	0	0	0
Min. treble, lin. bass	0	0	X	X	1	0	0	0
Lin. treble, max. bass	1	0	0	0	1	1	0	1
Lin. treble, max. bass	1	0	0	0	1	1	X	1
Lin. treble, max. bass	1	0	0	0	1	1	1	X
Lin. treble, min. bass	1	0	0	0	0	1	0	0
Lin. treble, min. bass	1	0	0	0	0	0	X	X
Max. treble, max. bass	1	1	X	X	1	1	X	1
Min. treble, min. bass	0	0	X	X	0	0	X	X
Power ON	0	0	0	0	0	0	0	1

MSB treble	LSB treble	MSB bass	LSB bass

f) Switch Byte I

MSB	LSB
MUTE I	MUTE II	CH1/CH2ls	CH1/CH2KH	Mono	SCART	SCART-D	AM	

MUTE I = 0 All AF-outputs are muted (speakers, headphones, SCART); power ON

MUTE I = 1 All AF-outputs ON

MUTE II = 0 Loudspeaker outputs muted; power ON

MUTE II = 1 Loudspeaker outputs ON

MUTE I and MUTE II are OR gated with respect to the loudspeaker outputs

MUTE I and MUTE III are OR gated with respect to the SCART output

MUTE I	MUTE II	MUTE III	Loudspeaker output	Headphone output	SCART output
0	0	0	muted	muted	muted
0	0	1	muted	muted	muted
0	1	0	muted	muted	muted
0	1	1	muted	muted	muted
1	0	0	muted	ON	muted
1	0	1	muted	ON	ON
1	1	0	ON	ON	muted
1	1	1	ON	ON	ON

Ch1/Ch2ls = 0 Sound 1 on the loudspeaker outputs; power ON

Ch1/Ch2ls = 1 Sound 2 on the loudspeaker outputs

Ch1/Ch2KH = 0 Sound 1 on the headphone outputs; power ON

Ch1/Ch2KH = 1 Sound 2 on the headphone outputs

Ch1/Ch2ls and Ch1/Ch2KH are only effective if the matrix is set to the position "dual sound".

Mono = 0 identification signal decoder is set to the position mono and held; power ON

Mono = 1 normal operation if ID-signal decoder

SCART = 0 normal TV-operation; power ON

SCART = 1 SCART playback; connection of SCART inputs - AF - outputs
SCART = 1 has priority over AM = 1 (loudspeaker and headphones)

SCART-D = 0 SCART-playback stereo (mono); power ON

SCART-D = 1 Enable for the Ch1/Ch2 switch during SCART playback. (only effective when SCART = 1)

AM = 0 Normal operation (G-standard)

AM = 1 AM AF-input is activated; power ON
AM = 1 has priority over bypass = 1

Qu-H, Ch1/Ch2EN, Ch1/Ch2sc MUTE III see chapter Control Bytes a).

g) Switch Byte II

MSB	•	•	•	•	•	•	LSB
MPX0	MPX1	Quasi-st	BS	H-pulse	Matrix 0	Matrix 1	Bypass
MPX0	MPX1	MPX-period			recommended	$C_{25,26}$	permissible crystal tolerance
0	0	2 s		power ON	1 μ F		
0	1	4 s			2.2 μ F		
1	0	8 s			4.7 μ F		
special for crystal operation recommended adjustments:							
0	0	2 s			470 nF		± 40 ppm
0	1	4 s			330 nF		± 70 ppm

MPX period = 2 s signifies: ID-signal decoder searches 1 second dual and 1 second stereo.
 It is principle permitted to make with given $C_{25,26}$ the MPX-period higher than indicated, but not lower.

Quasi stereo	=	0	Quasi stereo OFF; power ON
Quasi stereo	=	1	Quasi stereo ON
Bb	=	0	Stereo base width expansion OFF; power ON
Bb	=	1	Stereo base width expansion ON;
H-pulse	=	0	ID-signal decoder synchronization with $f_H = 15.625$ kHz; power ON
H-pulse	=	1	ID-synchronization with $4 \times f_H$ (has to be set to 1 during operation with crystal or 4-MHz reference frequency)
Matrix 0		Matrix 1	Matrix status
0		0	mono power ON
0		1	stereo
1		0	dual
1		1	automatic according to ID-signal decoder
Bypass =	0	Normal operations (G-standard)	
Bypass =	1	Matrix is bridge so that left/right signals can be fed; power ON (AM = 1 has priority over bypass = 1)	

Priority List of Setting Bits

1. MUTE I
2. MUTE II (only with regard to the loudspeaker output)
3. SCART
4. AM
5. Bypass
6. Matrix 0, 1


h) Talk Mode



MS	LSB
St	D	T3	T4	T5	CL	X	X	
0	0	decoder detects mono						
1	0	decoder detects stereo						
0	1	decoder detects dual						
1	1	internally inhibited						
CL = 1 The signal path for the loudspeaker reached the clipping level (The bit CL is automatical reset)								



T3 - T5 are test bits



Pin Functions



Pin No.	Function
1	AF-input mono, left, sound 1 (may be balanced)
2	Bias for AF-operating point
3	AF-input right, sound 2
4	54-kHz input
5	54-kHz filter
6	AF-input (L-standard)
7	AF-input SCART left (sound 1)
8	AF-input SCART right (sound 2)
9	AF-output SCART (mono, sound 1, left)
10	AF-output SCART (mono, sound 2, right)
11	Phase shifter quasi stereo
12	Phase shifter quasi stereo
13	Cut-off frequency bass (base width) left
14	Cut-off frequency bass (base width) right
15	AF-output, loudspeaker right
16	AF-output, loudspeaker left
17	Cut-off frequency treble left
18	Cut-off frequency treble right
19	AF-output, headphones right
20	AF-output, headphones left
21	+ V _S (supply voltage)
22	I ² C Bus SCL
23	I ² C Bus SDA
24	Input H-pulse (4 x H-pulse), crystal oscillator
25	Filter ID-signal decoder
26	Filter ID-signal decoder
27	PLL-filter ID-signal decoder
28	Ground






**PLL Filter ID-Signal Decoder (Pin 27)****Filter ID-Signal Decoder (Pin 25/26)**



**H-Pulse/Crystal Oscillator (Pin 24)****I²C Bus SDA (Pin 23)**



**I²C Bus SCL (Pin 22)****AF-Outputs Headphones (Pin 19/20)
Loudspeaker (Pin 15/16)
SCART (Pin 9/10)**

**Cut-Off Frequency Treble (Pin 17/18)****Cut-Off Frequency Bass (Pin 13/14)**

**Phase Advancer Quasi Stereo (Pin 11/12)**

**AF-Inputs SCART (Pin 7/8)****AF-Input AM (Pin 6)**

**54-kHz Filter (Pin 4/5)****AF-Input (Pin 3)**

**Input for AF-Unit Bias Blocking Capacitor (Pin 2)****AF-Input (Pin 1)**

Absolute Maximum Ratings $T_A = 0$ to 70°C ; all voltages relatives to V_{ss}

Parameter	Symbol	Limit Values		Unit	Remarks
		min.	max.		
Supply voltage	V_{21}	0	14	V	
Max. DC-voltage	V_1	0	V_{21}	V	
Max. DC-voltage	V_2	0	V_{21}	V	
Max. DC-voltage	V_3	0	V_{21}	V	
Max. DC-voltage	V_4	0	V_{21}	V	
Max. DC-voltage	V_6	0	V_{21}	V	
Max. DC-voltage	V_7	0	V_{21}	V	
Max. DC-voltage	V_8	0	V_{21}	V	
Max. DC-voltage	V_{11}	0	V_{21}	V	
Max. DC-voltage	V_{12}	0	V_{21}	V	
Max. DC-voltage	V_{13}	0	V_{21}	V	
Max. DC-voltage	V_{14}	0	V_{21}	V	
Max. DC-voltage	V_{17}	0	V_{21}	V	
Max. DC-voltage	V_{18}	0	V_{21}	V	
Max. DC-voltage	V_{22}	0	V_{21}	V	
Max. DC-voltage	V_{23}	0	V_{21}	V	
Max. DC-voltage	V_{24}	0	V_{21}	V	
Max. DC-voltage	V_{25}	0	V_{21}	V	
Max. DC-voltage	V_{26}	0	V_{21}	V	
Max. DC-current	I_5	0	2	mA	
Max. DC-current	I_9	0	2	mA	
Max. DC-current	I_{10}	0	2	mA	
Max. DC-current	I_{15}	0	2	mA	
Max. DC-current	I_{16}	0	2	mA	
Max. DC-current	I_{19}	0	2	mA	
Max. DC-current	I_{20}	0	2	mA	
Max. DC-current	I_{27}	0	1	mA	

Absolute Maximum Ratings (cont'd)

Parameter	Symbol	Limit Values		Unit	Remarks
		min.	max.		
ESD-voltage	V_{ESD}	- 2	2	kV	HBM ($R = 1.5 \text{ k}\Omega$, $C = 100 \text{ pF}$)
ESD-voltage	$V_{ESD7,8,9,10}$	- 6	6	kV	HBM ($R = 1.5 \text{ k}\Omega$, $C = 100 \text{ pF}$)
Junction temperature	T_j		150	°C	
Storage temperature	T_{stg}	- 40	125	°C	
Thermal resistance system ambient	$R_{th SA}$		53	K/W	

Operating Range

Supply voltage	V_6	10	13.2	V	
Ambiente temperature	T_A	0	70	°C	
Input frequency range	f_I	0.01	20	kHz	

Characteristics

$V_S = 12 \text{ V}$; $T_A = 25^\circ\text{C}$, audio reference level 0 dB–250 mVrms, if not differently defined.

I²C Bus preset: start - 84 - 01,3F - 0 2,3F - 04,00 - 0 3,1F - 0 5,88 - 0 6,10 - 07,C8 - 00,01 - stop

Chip address - $Vol_{LSI} 63$ - $Vol_{LSr} 63$ - Vol_{VLs} - $Vol_{HP} 31$ - *Sound lin Adjust 0dB* - *MUTE I, MUTE II, Mono - Bypass*

The basic setting for each point in the specification is always preset; only settings which deviate from this are given in the test conditions. Details in *italics* only provide explanation of the hexadecimal codes. If switch byte are mentioned only the bit status and activated features are indicated.

Parameter	Symbol	Limit Values			Unit	Test Condition (in accordance with test circuit 1)
		min.	typ.	max.		
Current consumption	I_{21}		58.	80	mA	

Signal Section

Max. gain	V_{16-1}	-2	0	2	dB	
Max. gain	V_{15-3}	-2	0	2	dB	
Max. gain	V_{20-1}	-2	0	2	dB	
Max. gain	V_{19-3}	-2	0	2	dB	
Max. gain	V_{16-3}	-2	0	2	dB	00,02; $V_1 = 01$ <i>Matrix: Stereo</i>
Max. gain	V_{15-3}	-2	0	2	dB	00,02; $V_1 = 01$ <i>Matrix: Stereo</i>
Max. gain	V_{20-3}	-2	0	2	dB	00,02; $V_1 = 0$ <i>Matrix: Stereo</i>
Max. gain	V_{19-3}	-2	0	2	dB	00,02; $V_1 = 0$ <i>Matrix: Stereo</i>
Max. gain	V_{16-1}	4	6	8	dB	00,02; $V_3 = 0$ <i>Matrix: Stereo</i>
Max. gain	V_{20-1}	4	6	8	dB	00,02; $V_3 = 0$ <i>Matrix: Stereo</i>
Max. gain	V_{16-7}	-2	0	2	dB	07,CC, SCART
Max. gain	V_{15-8}	-2	0	2	dB	07,CC, SCART
Max. gain	V_{20-7}	-2	0	2	dB	07,CC, SCART
Max. gain	V_{19-8}	-2	0	2	dB	07,CC, SCART
Max. gain	V_{16-6}	-2	0	2	dB	07,C9, AM
Max. gain	V_{15-6}	-2	0	2	dB	07,C9, AM
Max. gain	V_{20-6}	-2	0	2	dB	07,C9, AM
Max. gain	V_{19-6}	-2	0	2	dB	07,C9, AM

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Gain	V_{9-1}	-2	0	2	dB	
Gain	V_{10-3}	-2	0	2	dB	
Gain	V_{9-3}	-2	0	2	dB	
Gain	V_{10-3}	-2	0	2	dB	00,02; $V_1 = 0$ <i>Matrix: Stereo</i>
Gain	V_{9-1}	4	6	8	dB	00,02; $V_1 = 0$ <i>Matrix: Stereo</i>
Gain	V_{10-6}	-2	0	2	dB	00,02; $V_1 = 0$ <i>Matrix: Stereo</i>
Gain	V_{9-6}	-2	0	2	dB	07,C9, AM
Min. gain	V_{16-1}		-70	-65	dB	01,08-02,08
Main control						$Vol_{LSi\ 8} - Vol_{LSr\ 8}$
Min. gain	V_{15-3}		-70	-65	dB	01,08-02,08
Main control						$Vol_{LSi\ 8} - Vol_{LSr\ 8}$
Min. gain	V_{16-1}	-17	-15	-13	dB	04,18
1st. control						$Vol_{VLS\ 24}$
Min. gain	V_{15-3}	-17	-15	-13	dB	04,18
1st. control						$Vol_{VLS\ 24}$
Min. gain	V_{20-1}		-62	-57	dB	03,01, $Vol_{HP\ 1}$
Min. gain	V_{19-3}		-62	-57	dB	03,01, $Vol_{HP\ 1}$

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Analogous values are valid for feed in at the pins 6, 7 and 8						
Channel tracking error	ΔV_{15-16}			± 2	dB	01,3F to 01,24 02,3F to 02,24 $Vol_{LSI} 63-36 - Vol_{LSr} 63-36$
Channel tracking error	ΔV_{19-26}			± 2	dB	03,1F to 03,13 $Vol_{HP} 31-19$
Step width Vol ₁₅	ΔV_{15}	0	1.25	2.5	dB	01,X-01,(X ± 1) $Vol_{LSI} X - Vol_{LSr} (X ± 1)$
Step width Vol ₁₆	ΔV_{16}	0	1.25	2.5	dB	02,X-02,(X ± 1) $Vol_{LSr} X - Vol_{LSr} (X ± 1)$
Step width Vol ₁₅	ΔV_{15}	0	1.25	2.5	dB	04,X-04,(X ± 1) $Vol_{VLS} X - Vol_{VLS} (X ± 1)$
Step width Vol ₁₆	ΔV_{16}	0	1.25	2.5	dB	04,X-04,(X ± 1) $Vol_{VLS} X - Vol_{VLS} (X ± 1)$
Step width Vol ₁₉	ΔV_{19}	0	2	4	dB	03,X-03,(X ± 1) $Vol_{HP} X - Vol_{HP} (X ± 1)$
Step width Vol ₂₀	ΔV_{20}	0	2	4	dB	03,X-03,(X ± 1) $Vol_{HP} X - Vol_{HP} (X ± 1)$
Matrix adjustment	V_{16-1}	2.5	3	3.5	dB	06,1F, Adjust. max
Matrix adjustment	V_{20-1}	2.5	3	3.5	dB	06,1F, Adjust. max
Matrix adjustment	V_{9-1}	2.5	3	3.5	dB	06,1F, Adjust. max
Matrix adjustment	V_{16-1}	-3.5	-3	-2.5	dB	06,01, Adjust. min
Matrix adjustment	V_{20-1}	-3.5	-3	-2.5	dB	06,01, Adjust. min
Matrix adjustment	V_{9-1}	-3.5	-3	-2.5	dB	06,1F, Adjust. max
Adjust. step width	ΔV_{16}	0.1	0.2	0.3	dB	06,X-06,(X ± 1) Adjust. X - adjust. (X ± 1)

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Adjust. step width	ΔV_{20}	0.1	0.2	0.3	dB	06,X-06,(X ± 1) Adjust. X – adjust. (X ± 1)
Adjust. step width	ΔV_9	0.1	0.2	0.3	dB	06,X-06,(X ± 1) Adjust. X – adjust. (X ± 1)
Bass boost	V_{16-1}	13	15		dB	05,8 F; $f_i = 40$ Hz Bass max, treble lin.
Bass boost	V_{15-3}	13	15		dB	05,8 F; $f_i = 40$ Hz Bass max, treble lin.
Bass cut	V_{16-1}		- 12		dB	05,8 F; $f_i = 40$ Hz Bass max, treble lin.
Bass cut	V_{15-3}		- 12		dB	05,8 F; $f_i = 40$ Hz Bass max, treble lin.
Step width bass	ΔV_{15}	1	3	5	dB	05,8X-05,8 (X ± 1) Bass X – bass (X ± 1)
Step width bass	ΔV_{16}	1	3	5	dB	05,8X-05,8 (X ± 1) Bass X – bass (X ± 1)

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Treble boost	V_{16-1}	10	12		dB	05,8 F; $f_1 = 15$ Hz <i>Treble max, bass lin.</i>
Treble boost	V_{15-3}	10	12		dB	05,8 F; $f_1 = 15$ Hz <i>Treble max, bass lin.</i>
Treble cut	V_{16-1}		-12		dB	05,8 F; $f_1 = 15$ Hz <i>Treble max, bass lin.</i>
Treble cut	V_{15-3}		-12		dB	05,8 F; $f_1 = 15$ Hz <i>Treble max, bass lin.</i>
Step width bass	ΔV_{15}	1	3	5	dB	05,X8-05 (X ± 1)8 <i>Treble X – treble (X ± 1)</i>
Step width bass	ΔV_{16}	1	3	5	dB	05,X8-05 (X ± 1)8 <i>Treble X – treble (X ± 1)</i>
Linearity sound	ΔV_{15}			± 2	dB	05,88; $f_1 = 40$ Hz – 15 kHz <i>Treble, bass lin.</i>
Linearity sound	ΔV_{16}			± 2	dB	05,88; $f_1 = 40$ Hz – 15 kHz <i>Treble, bass lin.</i>
Detection level of the clipping detector	V_1		580		mVrms	05,8 F; $f_1 = 40$ Hz <i>Treble lin, bass max.</i> 01,2F - 02,2F $Vol_{LSI} 47 - Vol_{LSr} 47$

The same values are valid if the test signals are applied at pin 3, 6, 7 or 8

Channel separation	ΔV_{15-16}	50			dB	V_3 or $V_8 = 600$ mVrms
Channel separation of the clipping	ΔV_{19-20}	50			dB	V_3 or $V_8 = 600$ mVrms
Channel separation	ΔV_{9-10}	50			dB	V_3 or $V_8 = 600$ mVrms
Cross talk attenuation switch	$\alpha_{V1 \text{ interf}} / Q_{\text{rms}}$				dB	$V_{1 \text{ rms}} = 0$ $V_{1 \text{ Interf}, 3,6} = 600$ mVrms $V_{1 \text{ Interf}, 7,8} = 2$ Vrms

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Attenuation MUTE	α_{1-16}	80			dB	01,00 - 02,00 $V_{OLSI} = V_{OLSr} = 0$ $V_1 = 600 \text{ mVrms}$
Attenuation MUTE	α_{1-16}	80			dB	07,48; $V_1 = 600 \text{ mVrms}$ $MUTE I: 0$
Attenuation MUTE	α_{1-16}	80			dB	07,88; $V_1 = 600 \text{ mVrms}$ $MUTE II: 0$
Attenuation MUTE	α_{3-15}	80			dB	01,00 - 02,00 $V_{OLSI} = V_{OLSr} = 0$ $V_3 = 600 \text{ mVrms}$
Attenuation MUTE	α_{3-15}	80			dB	07,48; $V_3 = 600 \text{ mVrms}$ $MUTE I: 0$
Attenuation MUTE	α_{3-15}	80			dB	07,88; $V_3 = 600 \text{ mVrms}$ $MUTE II: 0$
Attenuation MUTE	α_{1-20}	80			dB	03,00; $V_1 = 600 \text{ mVrms}$ $V_{OLHP} = 0$
Attenuation MUTE	α_{1-20}	80			dB	07,48; $V_1 = 600 \text{ mVrms}$ $MUTE I: 0$

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Attenuation MUTE	α_{3-19}	80			dB	03,00; $V_3 = 600 \text{ mVrms}$ MUTE I: 0
Attenuation MUTE	α_{3-19}	80			dB	07,48; $V_1 = 600 \text{ mVrms}$ MUTE I: 0
Analogous values are valid for feed in at pins 6, 7, 8; $V_{7,8} = 2 \text{ Vrms}$; $V_6 = 600 \text{ mVrms}$						
Attenuation MUTE	α_{3-10}	80			dB	07,48; $V_3 = 600 \text{ mVrms}$ MUTE I: 0
Attenuation MUTE	α_{1-9}	80			dB	07,48; $V_1 = 600 \text{ mVrms}$ MUTE I: 0
Attenuation MUTE	α_{6-10}	80			dB	07,49; $V_6 = 600 \text{ mVrms}$ MUTE I: 0, AM
Attenuation MUTE	α_{6-9}	80			dB	07,49; $V_6 = 600 \text{ mVrms}$ MUTE I: 0, AM
Max. input voltage	V_6	600			mVrms	$THD_{15, 16} = 1\%$
Max. input voltage	V_3	600			mVrms	$THD_{15} = 1\%$
Max. input voltage	V_3	600			mVrms	$THD_{16} = 1\%$
Max. input voltage	V_1	300			mVrms	$THD_{16} = 1\%; 00,02$ Matrix; Stereo
Max. input voltage*)	V_7	2			Vrms	$THD_{16} = 3\%; 07,$ CC, Scart
Max. input voltage*)	V_8	2			Vrms	$THD_{15} = 1\%; 07,$ CC, Scart

*) The tone control is possible over the full functional range if 04, 18, Vol VLS 24

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Distortion	THD_{19}		0.01	0.1	%	$V_3 = 250 \text{ mVrms}$
Distortion	THD_{20}		0.01	0.1	%	$V_1 = 250 \text{ mVrms}$
Distortion	THD_{19}		0.01	0.1	%	$V_3 = 250 \text{ mVrms};$ $03,15 \text{ Vol}_{HP} 21$
Distortion	THD_{20}		0.01	0.1	%	$V_3 = 250 \text{ mVrms};$ $03,15 \text{ Vol}_{HP} 21$
Analogous values are valid for feed in at pins 6, 7, 8; $V_{7,8} = 600 \text{ Vrms}$; $V_6 = 250 \text{ mVrms}$						
Distortion	THD_{16}		0.01	0.1	%	$V_1 = 250 \text{ mVrms};$
Distortion	THD_{15}		0.01	0.1	%	$V_3 = 250 \text{ mVrms}$
Distortion	THD_{15}		0.01	0.2	%	$V_1 = 250 \text{ mVrms};$ 01,2F-02,2F $\text{Vol}_{LSI} 47 \text{ Vol}_{LSR} 47$
Distortion	THD_{15}		0.01	0.2	%	$V_3 = 250 \text{ mVrms};$ 01,2F-02,2F $\text{Vol}_{LSI} 47 \text{ Vol}_{LSR} 47$
Distortion	THD_{16}		0.1	0.4	%	$V_1 = 250 \text{ mVrms};$ 05,XX any sound
Distortion	THD_{15}		0.1	0.4	%	$V_3 = 250 \text{ mVrms};$ 05,XX any sound
Analogous values are valid for feed in at pins 6, 7, 8; $V_{7,8} = 600 \text{ mVrms}$; $V_6 = 250 \text{ mVrms}$						
Distortion	THD_{10}		0.01	0.1	%	$V_3 = 250 \text{ mVrms}$
Distortion	THD_9		0.01	0.1	%	$V_1 = 250 \text{ mVrms}$
Distortion	THD_{10}		0.01	0.1	%	$V_6 = 250 \text{ mVrms};$ 07,C9,AM
Distortion	THD_9		0.01	0.1	%	$V_6 = 250 \text{ mVrms};$ 07,C9,AM

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Anti-phase cross talk						
Base width	ΔV_{16-15}	0.5	0.55			$V_3 = 600 \text{ mVrms}$ $f_1 = 2 \text{ kHz}; 00, 11$ <i>Base width</i>
Anti-phase cross talk						
Base width	ΔV_{15-16}	0.5	0.55			$V_1 = 600 \text{ mVrms}$ $f_1 = 2 \text{ kHz}; 00, 11$ <i>Base width</i>
Base width phase	Φ_{16-15}	150	180	210	deg	$V_1 = 600 \text{ mVrms}$ $f = 2 \text{ kHz}; 00, 11$ <i>Base width</i>
Base width phase	Φ_{15-16}	150	180	210	deg	$V_3 = 600 \text{ mVrms}$ $f = 2 \text{ kHz}; 00, 11$ <i>Base width</i>
Phase rotation quasi stereo	Φ_{16-15}	0	10	40	deg	$V_{3,1} = 600 \text{ mVrms}$ $f = 40 \text{ kHz}; 00, 21$ <i>Quasi stereo</i>
Phase rotation quasi stereo	Φ_{16-15}	130	180	230	deg	$V_{3,1} = 600 \text{ mVrms}$ $f = 700 \text{ kHz}; 00, 21$ <i>Quasi stereo</i>
Phase rotation quasi stereo	Φ_{16-15}	-30	10	0	deg	$V_{3,1} = 600 \text{ mVrms}$ $f = 15 \text{ kHz}; 00, 21$ <i>Quasi stereo</i>
Signal-to-noise ratio	$\alpha_{S/N16}$	85	94		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_1 = 0.6 \text{ Vrms}$
Signal-to-noise ratio	$\alpha_{S/N15}$	85	94		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_3 = 0.6 \text{ Vrms}$
Signal-to-noise ratio	$\alpha_{S/N16}$	60	70		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_1 = 0.6 \text{ Vrms}$ 01,27-02,27 $Vol_{LSI} 39 - Vol_{LSr} 39$
Signal-to-noise ratio	$\alpha_{S/N15}$	60	70		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_3 = 0.6 \text{ Vrms}$ 01,27-02,27 $Vol_{LSI} 39 - Vol_{LSr} 39$

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
Output noise voltage	V_{N16}		12	33	μVrms	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $01,00-02,00$ $\text{Vol}_{LSI} 0-\text{Vol}_{LSr} 0$
Output noise voltage	V_{N15}		12	33	μVrms	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $01,00-02,00$ $\text{Vol}_{LSI} 0-\text{Vol}_{LSr} 0$
Signal-to-noise ratio	$\alpha_{S/N20}$	85	94		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_1 = 0.6 \text{ Vrms}$
Signal-to-noise ratio	$\alpha_{S/N19}$	85	94		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_3 = 0.6 \text{ Vrms}$
Signal-to-noise ratio	$\alpha_{S/N20}$	65	70		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_1 = 0.6 \text{ Vrms}$ 03, 10, $\text{Vol}_{HP} 16$
Signal-to-noise ratio	$\alpha_{S/N19}$	65	70		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_3 = 0.6 \text{ Vrms}$ 03, 10, $\text{Vol}_{HP} 16$
Output noise voltage	V_{N20}		12	33	μVrms	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ 03, 00, $\text{Vol}_{HP} 0$
Output noise voltage	V_{N19}		12	33	μVrms	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ 03, 00, $\text{Vol}_{HP} 0$
Signal-to-noise ratio	$\alpha_{S/N9}$	90	97		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_1 = 0.6 \text{ Vrms}$
Signal-to-noise ratio	$\alpha_{S/N10}$	90	97		dB	$V_N \text{ rms } 20 \text{ Hz-20 kHz};$ $V_1 = 0.6 \text{ Vrms}$

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
DC/pop Δ1 Bit	ΔV_{16}			± 4	mV	01, X-01, X ± 1 $Vol_{LSI} X - Vol_{LSI} (X \pm 1)$
DC/pop Δ1 Bit	ΔV_{15}			± 4	mV	02, X-02, X ± 1 $Vol_{LSr} X - Vol_{LSr} (X \pm 1)$
DC/pop Δ1 Bit	ΔV_{16}			± 4	mV	04, X-04, X ± 1 $Vol_{VLS} X - Vol_{VLS} (X \pm 1)$
DC/pop Δ1 Bit	ΔV_{15}			± 4	mV	04, X-04, X ± 1 $Vol_{VLS} X - Vol_{VLS} (X \pm 1)$
DC/pop Δ1 Bit	ΔV_{16}			± 2	mV	05, X-05, X ± 1 $ToneX - Tone (X \pm 1)$
DC/pop Δ1 Bit	ΔV_{15}			± 2	mV	05, X-05, X ± 1 $ToneX - Tone (X \pm 1)$
DC/pop Δ1 Bit	ΔV_{19}			± 4	mV	03, X-03, X ± 1 $Vol_{HP} X - Vol_{HP} (X \pm 1)$
DC/pop Δ1 Bit	ΔV_{20}			± 4	mV	03, X-03, X ± 1 $Vol_{HP} X - Vol_{HP} (X \pm 1)$

Design-Related Data

Input resistance	R_7	35		$k\Omega$		
Input resistance	R_8	35		$k\Omega$		
Input resistance	R_6	20		$k\Omega$		
Input resistance	R_3	22		$k\Omega$		
Input resistance	R_1	22		$k\Omega$		
Output resistance	R_{19}		70	Ω		
Output resistance	R_{20}		70	Ω		
Output resistance	R_{15}		70	Ω		
Output resistance	R_{16}		70	Ω		
Output resistance	R_9		70	Ω		
Output resistance	R_{10}		70	Ω		

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition	Test Circuit
		min.	typ.	max.			
ID-Signal Decoder							
Gain filter OP-amplif.	V_5	13	14	15	dB	$V_{IF} = 80 \text{ mVpp}$	1
Max. input voltage	V_5	600			mVpp	Function	2
VCO-voltage PLL	V_{27}	1.3			V	$f_{24} = 14.6 \text{ kHz}; V_{24} = 2.5 \text{ V}$	2
VCO-voltage PLL	V_{27}	2	3	4	V	$f_{24} = 15.625 \text{ kHz}; V_{24} = 2.5 \text{ V}$	2
VCO-voltage PLL	V_{27}			4.7	V	$f_{24} = 16.6 \text{ kHz}; V_{24} = 2.5 \text{ V}$	2
VCO-voltage PLL	V_{27}	1.3			V	$f_{24} = 58.4 \text{ kHz}; V_{24} = 2.5 \text{ V}$	2
VCO-voltage PLL	V_{27}			4.7	V	$f_{24} = 66.4 \text{ kHz}; V_{24} = 2.5 \text{ V}$	2
VCO-voltage PLL	V_{27}	2	3	4	V	00,08, H-pulse	4
VCO-voltage PLL	V_{27}					00,08 - 04.81 H-pulse; quartz cont. function	

$$V_{\text{Filter gain}} = \frac{\sqrt{(V_{25} - V_{25}^*)^2 + (V_{26} - V_{26}^*)^2}}{V_5} V_{25} \text{ or } V_{26} \text{ when } V_5 = 0 \\ V_{25}^* \text{ or } V_{26}^* \text{ when } V_5 = 100 \text{ mVpp}; m = 50\%$$

ID-filter gain	$V_{KT \text{ Filter}}$	3.4		6.8	V	$f_5 = \text{pilot signal dual}; I^2C\text{-talk: dual}$	2
ID-filter gain	$V_{KT \text{ Filter}}$	3.4		6.8	V	$f_5 = \text{pilot signal stereo}; I^2C\text{-talk: stereo}$	2

$$V_{5 \text{ test}} = V_{25} (V_5 = 0) \pm \Delta V_{25}; V_{26 \text{ test}} = V_{26} (V_5 = 0) \pm \Delta V_{26}$$

Characteristics (cont'd)

Parameter	Symbol	Limit Values			Unit	Test Condition	Test Circuit
		min.	typ.	max.			
Detection threshold	ΔV_{25}	900			mV	I ² C-talk: stereo or dual	3
Detection threshold	$-\Delta V_{25}$	900			mV	I ² C-talk: stereo or dual	3
Detection threshold	ΔV_{26}	900			mV	I ² C-talk: stereo or dual	3
Detection threshold	$-\Delta V_{26}$	900			mV	I ² C-talk: stereo or dual	3
Mono threshold	ΔV_{25}	0		100	mV	I ² C-talk: mono	3
Mono threshold	$-\Delta V_{25}$	0		100	mV	I ² C-talk: mono	3
Mono threshold	ΔV_{26}	0		100	mV	I ² C-talk: mono	3
Mono threshold	$-\Delta V_{26}$	0		100	mV	I ² C-talk: mono	3
Response of detection	t_{det}	1/4		1/2	t_{MPX}	I ² C-talk: stereo or dual; $\pm \Delta V_{25} = 1 \text{ V}$	3
Response of detection	t_{det}	1/4		1/2	t_{MPX}	I ² C-talk: stereo or dual; $\pm \Delta V_{26} = 1 \text{ V}$	3

Characteristics (cont'd)


Parameter	Symbol	Limit Values			Unit	Test Condition	Test Circuit
		min.	typ.	max.			
Switching threshold, f_{REF} -input	$V_H \text{ in L}$	0		1.5	V		2
Switching threshold, f_{REF} -input	$V_H \text{ in L}$	3.5		V_{21}	V		2
Amplitude crystal oscillator	V_{24}		0.3		Vpp	$f_0 = 4.00000 \text{ MHz}$ Serial resonance	4
Ext. 1- or 4 MHz-clock signal	V_{24}		2		Vpp		3
Crystal current	I_C	0.29	0.35	0.42	mArms	$R_C = 40 \Omega$	
Multiplexer clock	t_{MPX}		2.17		s	09,08, $\text{MPX} = 2 \text{ s}$	
Multiplexer clock	t_{MPX}		4.34		s	09,48, $\text{MPX} = 4 \text{ s}$	
Multiplexer clock	t_{MPX}		8.68		s	09,88, $\text{MPX} = 8 \text{ s}$	

Design-Related Data


Filter output resistance	$R_{25,26}$	110			kΩ		
f_{REF} -input resistance	R_{24}	800			Ω		
Input impedance crystal oscillator	Z_{24}	-600	-500	-400	Ω		
Crystal serial resistance	R_{C1}			100	Ω	$P_{\text{tot}} = 1 \mu\text{W}$, fundamental	
Crystal serial resistance	R_{C3}	300			Ω	$P_{\text{tot}} = 1 \mu\text{W}$ 3rd harmonic	
Spurious wave spacing (fundamental wave to harmonic and nonharmonic signals)		20			dB	$P_{\text{tot}} = 1 \mu\text{W}$ $f < 15 \text{ MHz}$	

Characteristics (cont'd)


Parameter	Symbol	Limit Values			Unit	Test Condition
		min.	typ.	max.		
I²C Bus (SCL, SDA)						
SCL, SDA edges						
Rise time	<i>t</i> _R			1	μs	
Fall time	<i>t</i> _F			300	ns	
Shift register clock pulse SCL						
Frequency	<i>f</i> _{SCL}	0		100	kHz	
H-pulse width	<i>t</i> _{HIGH}	4			μs	
L-pulse width	<i>t</i> _{LOW}	4			μs	
Start						
Set-up time	<i>t</i> _{SUSTA}	4			μs	
Hold time	<i>t</i> _{HDSTA}	4			μs	
Stop						
Set-up time	<i>t</i> _{SUDAT}	1			μs	
Bus free time	<i>t</i> _{HDDAT}	1			μs	
Data transfer						
Set-up time	<i>t</i> _{SUDAT}	1			μs	
Hold time	<i>t</i> _{HDDAT}	600			ns	
Input SCL, SDA						
Input voltage	<i>V</i> _{QH}	3		5.5	V	
	<i>V</i> _{QL}			1.5	V	
Input current	<i>V</i> _{QH}			50	μA	
	<i>V</i> _{QL}			100	μA	
Output SDA (Open collector)						
Output voltage	<i>V</i> _{QH}	5.4			V	<i>R</i> _L = 2.5 kΩ
	<i>V</i> _{QL}			0.4	V	<i>I</i> _{QL} = 3 mA





Test Circuit 1





Test Circuit 2


**Test Circuit 3**





**Application Circuit 2**




**I²C Bus Timing Diagram**

t_{SUSTA}	Setup time (start)
t_{HDSTA}	Hold time (start)
t_{HIGH}	H-pulse width (clock)
t_{LOW}	L-pulse width (clock)
t_{SUDAT}	Setup time (data transfer)
t_{HDDAT}	Hold time (data transfer)
t_{SUSTO}	Setup time (stop)
t_{BUF}	Bus free time
t_F	Fall time
t_R	Rise time


All times referred to V_{IH} and V_{IL} values.

Package Outlines

Plastic Package, P-DIP-28-1
(Plastic Dual In-Line Package)



GPDD05037

**Plastic Package, P-DSO-28.350 (SMD)
(Plastic Dual Small Outline)**

1) Does not include plastic or metal protrusions of 0.25 max per side

GPS05182

Sorts of Packing

Package outlines for tubes, trays etc. are contained in our Data Book "Package Information"

SMD = Surface Mounted Device

Dimensions in mm

Global PartnerChip for Systems on Silicon

A
Siemens AG Österreich
Postfach 326
1031 Wien
Tel (01) 717 11-56 61
Fax 1372-10
Fax (01) 717 11 5973

AUS
Siemens Ltd., Head Office
544 Church Street
Richmond (Melbourne), Vic. 3121
Tel (03) 420 7111
Fax 30425
Fax (03) 4207275

B
Siemens S.A.
chaussée de Charleroi 116
1060 Bruxelles
Tel (02) 536-2111
Fax 21347
Fax (02) 536 24 92

BR
ICOTRON S.A.
Industria de Componentes
Elettrônicos
Avenida Mutinga, 3650-6° andar
05150 São Paulo-SP
Tel (011) 8 33-22 11
Fax 11-81 001
Fax (011) 8 31-40 06

CDN
Siemens Electric Ltd.
Electronic Components Division
1180 Courtney Park Drive
Mississauga, Ontario L5T 1P2
Tel (416) 5 64 19 95
Fax (069) 68 841
Fax (416) 6 70-65 63

CH
Siemens-Albis AG
Freilagerstraße 28
8047 Zürich
Tel (01) 4 95-31 11
Fax 823781 23
Fax (01) 495 5050

D
Siemens AG
Salzufer 6-8
10587 Berlin
Tel (030) 39 93-26 26
Fax (030) 39 93-24 90

Siemens AG
Lahnweg 10
40219 Düsseldorf
Tel (0211) 39 9-29 30
Fax (0211) 3 99-14 81

Siemens AG
Rödelheimer Landstraße 5-9
60487 Frankfurt
Tel (069) 797-38 01
Fax (069) 797-25 82

Siemens AG
Lindenplatz 2
20099 Hamburg
Tel (040) 28 89-27 85
Fax (040) 28 89-30 96

Siemens AG
Werner-von-Siemens-Platz 1
30880 Laatzen (Hannover)
Tel (0511) 8 77-22 22
Fax (0511) 8 77-20 78

Siemens AG
Balanstraße 73
81541 München
Tel (089) 4144-47 21
Fax (089) 4144-49 63

Siemens AG
Halbleiter Distribution
Richard Strauss-Straße 76
81679 München
Tel (089) 92 21-31 33
Fax (089) 92 21-20 71

Siemens AG
Von-der-Tann-Straße 30
90439 Nürnberg
Tel (0911) 6 54-76 02
Fax (0911) 6 54-76 24

Siemens AG
Weissacher Straße 11
70499 Stuttgart
Tel (0711) 137 28 64
Fax (0711) 137 24 48

DK
Siemens A/S
Borupvang 3
2750 Ballerup
Tel 44 77 44 77
Fax 1258 222
Fax 44 77 40 17

E
Siemens S.A.
Dpto. Componentes
Ronda de Europa, 3
28760 Tres Cantos-Madrid
Tel (01) 8 03 00 85
Fax (01) 8 03 39 26

F
Siemens S.A.
39/47, Bd. Ornano
93527 Saint-Denis CEDEX 2
Tel (1) 49 22 31 00
Fax 234 077
Fax (1) 49 22 39 70

GB
Siemens plc
Siemens House
Oldbury
Bracknell
Berkshire RG12 8FZ
Tel (0344) 39 60 00
Fax (0344) 39 66 32

GR
Siemens AE
Paradissou & Artemidos
P.O.B. 61011
15110 Amaroussio/Athen
Tel (01) 6 86 41 11
Fax 216 292
Fax (01) 6 86 42 99

HK
Schmidt & Co. (H.K.) Ltd.
18/F., Great Eagle Centre
23 Harbour Road
Wanchai
Hong Kong
Tel 8 52/8 33 02 22
Fax 74 766 schmc hx
Fax 8 38 26 52



Siemens S.p.A.
Semiconductor Sales
Via dei Valtorta, 48
20127 Milano
✉ (02) 66 76-1
Fax (02) 66 76-4395



Siemens Nederland N.V.
Postb. 16068
2500 BB Den Haag
✉ (070) 3 33 33 33
✉ 31373
Fax (070) 3 33 2790



Siemens Components
Österögatan 1
Box 46
S-164 93 Kista
✉ (08) 7 03 35 00
✉ 11672
Fax (08) 7 03 35 01



Siemens Ltd.
Head Office
134 A, Dr. Annie Besant Road,
Worli
P.O.B. 6597
Bombay 400018
✉ (022) 4 93 87 86
✉ 1175142
Fax (022) 4 94 02 40



Siemens S.A.
Estrada Nacional 117, Km 2,6
Alfragide
2700 Amadora
✉ (01) 4 17 00 11
✉ 62 955
Fax (01) 4 17 28 70



Siemens Oy
P.O.B. 60
02801 Espoo
✉ (0) 51 051, ✆ 124 465
Fax (0) 51 052 23 98



Siemens Ltd.,
Electronic Components Division
8 Raglan Road
Dublin 4
✉ (01) 68 47 27
✉ 93744
Fax (01) 68 46 33



Fuji Electronic Components Ltd
Shinjuku Koyama Bldg. 2F
4-30-3 Yoyogi Shibuya-ku
Tokyo 151
✉ 81-3-53 88-85 25
Fax 81 3-33 76-9792



Siemens A/S
Ostre Aker vei 90
Postboks 10, Veitvet
0518 Oslo 5
✉ (02) 63 30 00
✉ 78 477
Fax (02) 63 38 05



Siemens Sp. z.o.o.
ul. Stawki 2
POB 276
00-950 Warszawa
✉ 6 35 16 19
✉ 825 554
Fax 6 35 52 38



Siemens Components Pte. Ltd.
Promotion Office
166 Kallang Way
Singapore 1334
✉ 7 417 418
Fax 7 42 62 39/742 28 03



SIMKO Ticaret ve Sanayi A.S.
Mechsi Mebusan Cad. No. 125
P.K. 1001, 80007 Karaköy
80040 Fındıklı
✉ (01) 2 51 09 00
✉ 24 233 sies tr
Fax (01) 2 52 4134



Siemens Components, Inc.
Semiconductor Division
10950 North Tantau Avenue
Cupertino, CA 95014
✉ (408) 7 77-45 00
Fax (408) 7 77-49 77



Siemens Ltd.
Siemens House,
P.O.B. 4583
Johannesburg 2000
✉ (011) 3 15 19 50
✉ 450 091
Fax (011) 3 15 19 68



Siemens Ltd.,
Asia Tower 10th Floor
726 Yeoksam-dong, Gangnam-gu
C.P.O. Box 3001
Seoul
✉ (02) 527-77 00
Fax (02) 527-77 79



Siemens AG
1. Donskoj pr., 2
Moskva 117419
✉ (095) 2 37-64 76, -6911
✉ 414 385
Fax (095) 2 37-86 14

Published by Semiconductor Group



Global PartnerChip
for
Systems on Silicon

Siemens Aktiengesellschaft

Ordering No. B111-H6807-X-X-7600
Printed in Germany
DA 08945. TD105