




**Pb-free
HEAT**



MU04 Series

Single Color / Light Bar Module

Features

Light emitting surface (Outer size)	6 x 19 mm (7 x 20 mm) (L x W)										
Product features	• Single Color (Green, Yellow Green, Orange or Red) • Lead-free soldering compatible • RoHS compliant										
Peak wavelength	<table><tr><td>Green</td><td>: 555 nm (5101,5105)</td></tr><tr><td></td><td>: 560 nm (5102)</td></tr><tr><td>Yellow Green</td><td>: 570 nm (4101,4105)</td></tr><tr><td>Orange</td><td>: 605 nm (3101,3105)</td></tr><tr><td>Red</td><td>: 660 nm (2101,2105)</td></tr></table>	Green	: 555 nm (5101,5105)		: 560 nm (5102)	Yellow Green	: 570 nm (4101,4105)	Orange	: 605 nm (3101,3105)	Red	: 660 nm (2101,2105)
Green	: 555 nm (5101,5105)										
	: 560 nm (5102)										
Yellow Green	: 570 nm (4101,4105)										
Orange	: 605 nm (3101,3105)										
Red	: 660 nm (2101,2105)										
Die materials	<table><tr><td>Green, Yellow Green</td><td>: GaP</td></tr><tr><td>Orange</td><td>: GaAsP</td></tr><tr><td>Red</td><td>: GaAlAs</td></tr></table>	Green, Yellow Green	: GaP	Orange	: GaAsP	Red	: GaAlAs				
Green, Yellow Green	: GaP										
Orange	: GaAsP										
Red	: GaAlAs										
Soldering methods	TTW (Through The Wave) soldering and manual soldering										
Soldering methods	More than 2kV(HBM)										
Packing	Plastic bag										

Recommended Applications

Electric Household Appliances, OA/FA, Other General Applications

Color and Luminous Intensity

Part No.	Material	Emitted Color	Resin Color	Intensity ^{※1} I _v (mcd)			Number of Chips
				MIN.	TYP.	I _F	
MU04-5101	GaP	Green	Green	8	16	20	3
MU04-5105	GaP		Milky White	8	16	20	3
MU04-5102	GaP		Green	10	20	20	3
MU04-4101	GaP	Yellow Green	Yellow	15	32	20	3
MU04-4105	GaP		Milky White	15	32	20	3
MU04-3101	GaAsP	Orange	Orange	8	16	20	3
MU04-3105	GaAsP		Milky White	8	16	20	3
MU04-2101	GaAlAs	Red	Red	15	32	20	3
MU04-2105	GaAlAs		Milky White	15	32	20	3

※1 Luminous Intensity : 3 chips

Absolute Maximum Ratings

(Ta=25°C)

Item	Symbol	Absolute Maximum Ratings									Unit
		5101	5105	5102	4101	4105	3101	3105	2101	2105	
Power Dissipation※ ²	P _d	190	190	225	225	225	190	190	180	180	mW
Forward Current	I _F	25	25	30	30	30	25	25	30	30	mA
Pulse Forward Current ※ ³	I _{FRM}	60	60	60	60	60	60	60	60	60	mA
Derating (Ta=25℃ or higher)	Δ I _F	0.33	0.33	0.40	0.40	0.40	0.33	0.33	0.40	0.40	mA/℃
	Δ I _{FRM}	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.80	mA/℃
Reverse Voltage	V _R	4	4	4	4	4	4	4	4	4	V
Operating Temperature	T _{opr}	-40～+85									℃
Storage Temperature	T _{std}	-40～+85									℃

※2 Power Dissipation : 3chips, The other Items : 1 chip

※3 I_{FRM} Measurement condition : Pulse Width ≤ 2ms, Duty ≤ 1/5

Electro-Optical Characteristics


(Ta=25°C)

Item		Symbol	Characteristics										Unit
	Conditions			5101	5105	5102	4101	4105	3101	3105	2101	2105	
Forward Voltage	I _F =20mA	V _F	TYP.	2.2	2.2	2.1	2.1	2.1	2.2	2.2	1.7	1.7	V
			MAX.	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.0	2.0	
Reverse Current	V _R =4V	I _R	MAX.	100	100	100	100	100	100	100	100	100	μ A
Peak Wavelength	I _F =20mA	λ _p	TYP.	555	555	560	570	570	605	605	660	660	nm
Spectral Line Half Width	I _F =20mA	Δ λ	TYP.	30	30	30	30	30	30	30	30	30	nm


※ The above Items : 1 chip

Technical Data(5101/5105)


Forward Voltage vs. Forward Current
Condition : $T_a = 25^\circ\text{C}$




Ambient Temperature vs. Forward Voltage



Forward Current vs. Relative Intensity
Condition : $T_a = 25^\circ\text{C}$




Ambient Temperature vs. Relative Intensity
Condition : $I_F = 20\text{mA}$




Technical Data(5101/5105)


Derating
Ambient Temperature vs. Maximum Forward Current
Repetition Frequency : $f \geq 100\text{Hz}$




Power Dissipation vs. Ambient Temperature



Pulse Width vs. Maximum Tolerable Peak Current
Condition : $T_a = 25^\circ\text{C}$




Dynamic Drive Rating
Duty cycle vs. Maximum Forward Current
Condition : $T_a = 25^\circ\text{C}$




Technical Data(5102)


Forward Voltage vs. Forward Current
Condition : $T_a = 25^\circ\text{C}$




Ambient Temperature vs. Forward Voltage







Forward Current vs. Relative Intensity
Condition : $T_a = 25^\circ\text{C}$



Ambient Temperature vs. Relative Intensity
Condition : $I_F = 20\text{mA}$




Technical Data(5102)




Technical Data(4101/4105)


Forward Voltage vs. Forward Current
Condition : $T_a = 25^\circ\text{C}$




Ambient Temperature vs. Forward Voltage







Forward Current vs. Relative Intensity
Condition : $T_a = 25^\circ\text{C}$



Ambient Temperature vs. Relative Intensity
Condition : $I_F = 20\text{mA}$




Technical Data(4101/4105)




Technical Data(3101/3105)


Forward Voltage vs. Forward Current
Condition : $T_a = 25^\circ\text{C}$




Ambient Temperature vs. Forward Voltage



Forward Current vs. Relative Intensity
Condition : $T_a = 25^\circ\text{C}$




Ambient Temperature vs. Relative Intensity
Condition : $I_F = 20\text{mA}$




Technical Data(3101/3105)


Derating
Ambient Temperature vs. Maximum Forward Current
Repetition Frequency : $f \geq 100\text{Hz}$




Power Dissipation vs. Ambient Temperature



Pulse Width vs. Maximum Tolerable Peak Current
Condition : $T_a = 25^\circ\text{C}$




Dynamic Drive Rating
Duty cycle vs. Maximum Forward Current
Condition : $T_a = 25^\circ\text{C}$




Technical Data(2101/2105)


Forward Voltage vs. Forward Current
Condition : $T_a = 25^\circ\text{C}$




Ambient Temperature vs. Forward Voltage







Forward Current vs. Relative Intensity
Condition : $T_a = 25^\circ\text{C}$



Ambient Temperature vs. Relative Intensity
Condition : $I_F = 20\text{mA}$




Technical Data(2101/2105)



Package Dimensions

(Unit: mm)

(Tolerance : ± 0.25 mm)



● ※ mark : The measure of lead root

TTW (Through The Wave) soldering Conditions

Pre-heating	100 °C 60 s	(MAX.) Resin surface temperature (MAX.)
Solder Bath Temp.	265 °C	(MAX.)
Dipping Time	5 s	(MAX.)
Position	At least 2.0 mm away from the root of lead	

- 1) The dip soldering process shall be 2 times maximum.
- 2) The product shall be cooled to normal temperature before the second dipping process.

Manual Soldering Conditions

Iron tip temp.	400 °C	(MAX.) (30 W Max.)
Soldering time and frequency	3 s 2 times	(MAX.) (MAX.)
Position	At least 2.0 mm away from the root of lead	

Reliability Testing Result

Reliability Testing Result	Applicable Standard	Testing Conditions	Duration	Failure
Room Temp. Operating Life	BAJED-4701/100(101)	Ta = 25°C, If = Maximum Rated Current	1,000 h	0/10
Resistance to Soldering Heat	BAJED-4701/300(302)	260±5°C, 3mm from package base	10s	0/10
Temperature Cycling	BAJED-4701/100(105)	Minimum Rated Storage Temperature(30min) ~ Normal Temperature(15min) ~ Maximum Rated Storage Temperature(30min) ~ Normal Temperature(15min)	5 cycles	0/10
Wet High Temp. Storage Life	BAJED-4701/100(103)	Ta = 60±2°C, RH = 90±5%	1,000 h	0/10
High Temp. Storage Life	BAJED-4701/200(201)	Ta = Maximum Rated Storage Temperature	1,000 h	0/10
Low Temp. Storage Life	BAJED-4701/200(202)	Ta = Minimum Rated Storage Temperature	1,000 h	0/10
Lead Tension	BAJED-4701/400(401)	5N, 1time	10s	0/10
Vibration, Variable Frequency	BAJED-4701/400(403)	98.1m/s ² (10G), 100 ~ 2KHz sweep for 20min., XYZ each direction	2 h	0/10
Lead Bend	BAJED-4701/400(401)	2.5N, 0°↔90°	Twice	0/10
Shock	JSC 7201 A-8	It falls on wood engraving from height of 75cm.	3 times	0/10

Failure Criteria

Items	Symbols	Conditions	Failure criteria
Luminous Intensity	Iv	If=20mA	Testing Min. Value < Spec. Min. Value x 0.5
Forward Voltage	V _F	If=20mA	Testing Max. Value ≥ Spec. Max. Value x 1.2
Reverse Current	I _R	V _R =4V	Testing Max. Value ≥ Spec. Max. Value x 2.5
Cosmetic Appearance	-	-	Occurrence of notable decoloration, deformation and cracking

Special Notice to Customers Using the Products and Technical Information Shown in This Data Sheet

- 1) The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products. It does not constitute the warranting of industrial property nor the granting of any license.
- 2) For the purpose of product improvement, the specifications, characteristics and technical data described in the data sheets are subject to change without prior notice. Therefore it is recommended that the most updated specifications be used in your design.
- 3) When using the products described in the data sheets, please adhere to the maximum ratings for operating voltage, heat dissipation characteristics, and other precautions for use. We are not responsible for any damage which may occur if these specifications are exceeded.
- 4) The products that have been described to this catalog are manufactured so that they will be used for the electrical instrument of the benchmark (OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument).
The application of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. needs a high reliability and safety, and the breakdown and the operation might influence the life or the human body. Please consult us beforehand if you plan to use our product for the usages of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. except OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument.
- 5) In order to export the products or technologies described in this data sheet which are under the "Foreign Exchange and Foreign Trade Control Law," it is necessary to first obtain an export permit from the Japanese government.
- 6) No part of this data sheet may be reprinted or reproduced without prior written permission from Stanley Electric Co., Ltd.
- 7) The most updated edition of this data sheet can be obtained from the address below:
<http://www.stanley-components.com>