

Standard System Cable Assemblies

- System or Test Bench Patch Cord Assemblies
- Standard RG 58C/U Cable
- N, BNC, TNC, and SMA Connectors
- Quick Delivery

Midwest Microwave offers these standard cable assemblies for use in a system or on the laboratory test bench. These low cost, quick delivery assemblies provide a simple approach to meeting the immediate need for standard test bench or system cable assemblies. Normally standard MIL-C-17 RG58C/U cable (**see note for XX designation) is used with standard off the shelf connectors however other types of cable can be provided upon request.



BNC Male to BNC Male		
XX = Select Cable Type		
Model No.	Length*	
CSY-BMBM-XX-012-CS	12	
CSY-BMBM-XX-024-CS	24	
CSY-BMBM-XX-036-CS	36	
CSY-BMBM-XX-048-CS	48	
CSY-BMBM-XX-060-CS	60	
CSY-BMBM-XX-072-CS	72	
CSY-BMBM-XX-084-CS	84	
CSY-BMBM-XX-096-CS	96	

BNC Male to SMA Male		
XX = Select Cable Type		
Model No.	Length*	
CSY-BMSM-XX-012-CS	12	
CSY-BMSM-XX-024-CS	24	
CSY-BMSM-XX-036-CS	36	
CSY-BMSM-XX-048-CS	48	
CSY-BMSM-XX-060-CS	60	
CSY-BMSM-XX-072-CS	72	
CSY-BMSM-XX-084-CS	84	
CSY-BMSM-XX-096-CS	96	

SMA Male to SMA Male		
XX = Select Cable Type		
Model No.	Length*	
CSY-SMSM-XX-012-CS	12	
CSY-SMSM-XX-024-CS	24	
CSY-SMSM-XX-036-CS	36	
CSY-SMSM-XX-048-CS	48	
CSY-SMSM-XX-060-CS	60	
CSY-SMSM-XX-072-CS	72	
CSY-SMSM-XX-084-CS	84	
CSY-SMSM-XX-096-CS	96	

BNC Male to BNC Bkhd Female		
XX = Select Cable Type		
Model No.	Length*	
CSY-BMBB-XX-012-CS	12	
CSY-BMBB-XX-024-CS	24	
CSY-BMBB-XX-036-CS	36	
CSY-BMBB-XX-048-CS	48	
CSY-BMBB-XX-060-CS	60	
CSY-BMBB-XX-072-CS	72	
CSY-BMBB-XX-084-CS	84	
CSY-BMBB-XX-096-CS	96	

N Male to N Male		
XX = Select Cable Type		
Model No.	Length*	
CSY-NMNM-XX-012-CS	12	
CSY-NMNM-XX-024-CS	24	
CSY-NMNM-XX-036-CS	36	
CSY-NMNM-XX-048-CS	48	
CSY-NMNM-XX-060-CS	60	
CSY-NMNM-XX-072-CS	72	
CSY-NMNM-XX-084-CS	84	
CSY-NMNM-XX-096-CS	96	

N Male to N Bkhd Female		
XX = Select Cable Type		
Model No.	Length*	
CSY-NMNB-XX-012-CS	12	
CSY-NMNB-XX-024-CS	24	
CSY-NMNB-XX-036-CS	36	
CSY-NMNB-XX-048-CS	48	
CSY-NMNB-XX-060-CS	60	
CSY-NMNB-XX-072-CS	72	
CSY-NMNB-XX-084-CS	84	
CSY-NMNB-XX-096-CS	96	

BNC Male to N Male		
XX = Select Cable Type		
Model No.	Length*	
CSY-BMNM-XX-012-CS	12	
CSY-BMNM-XX-024-CS	24	
CSY-BMNM-XX-036-CS	36	
CSY-BMNM-XX-048-CS	48	
CSY-BMNM-XX-060-CS	60	
CSY-BMNM-XX-072-CS	72	
CSY-BMNM-XX-084-CS	84	
CSY-BMNM-XX-096-CS	96	

N Male to SMA Male		
XX = Select Cable Type		
Model No.	Length*	
CSY-NMSM-XX-012-CS	12	
CSY-NMSM-XX-024-CS	24	
CSY-NMSM-XX-036-CS	36	
CSY-NMSM-XX-048-CS	48	
CSY-NMSM-XX-060-CS	60	
CSY-NMSM-XX-072-CS	72	
CSY-NMSM-XX-084-CS	84	
CSY-NMSM-XX-096-CS	96	

TNC Male to TNC BkhdFemale		
XX = Select Cable Type		
Model No.	Length*	
CSY-TMTB-XX-012-CS	12	
CSY-TMTB-XX-024-CS	24	
CSY-TMTB-XX-036-CS	36	
CSY-TMTB-XX-048-CS	48	
CSY-TMTB-XX-060-CS	60	
CSY-TMTB-XX-072-CS	72	
CSY-TMTB-XX-084-CS	84	
CSY-TMTB-XX-096-CS	96	

Notes: * All lengths shown are in inches.

** To designate RG58C/U Cable, substitute "58" for "XX" in the Model No. Alternately "42" or "52" may be used to designate M42 or M52 higher performance cable (see page 78 for cable specifications). For use of other cable types, please contact the factory for Model Numbers.