



600 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS

KVA	CATALOG NO.	APPROX. DIMENSIONS ② Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W – Wall F – Floor	WEATHER SHIELD P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH				
15.0	NS10-0279333-3S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	345 (157.0)	F ①	WS-A-1	29-E
30.0	NS10-0213102-3S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	345 (157.0)	F ①	WS-A-1	29-E
45.0	NS10-0213103-3S	35.40 (89.9)	31.90 (81.0)	26.90 (68.3)	575 (261.0)	F	WS-A-3	29-E
75.0	NS10-0213104-3S	35.40 (89.9)	31.90 (81.0)	26.90 (68.3)	575 (261.0)	F	WS-A-3	29-E
112.5	NS10-0213105-3S	41.50 (105.4)	32.90 (83.6)	29.90 (75.9)	1000 (454.0)	F	WS-A-4	29-E
150.0	NS10-0213106-3S	45.60 (115.8)	39.50 (100.3)	35.50 (90.2)	1500 (680.0)	F	WS-A-5	29-E
225.0	NS10-213107-3S	52.00 (132.1)	52.00 (132.1)	40.00 (101.6)	2225 (1009.0)	F	WS-B-60	30-G
300.0	NS10-213099-3S	62.00 (157.5)	54.00 (137.2)	42.00 (106.7)	2675 (1213.0)	F	WS-B-3	30-G
500.0	NS10-0213112-4S	62.80 (159.5)	54.00 (137.2)	49.50 (125.7)	4000 (1814.0)	F	WS-A-6	③

600 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS

KVA	CATALOG NO.	APPROX. DIMENSIONS ③ Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W – Wall F – Floor	WEATHER SHIELD P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH				
15.0	NS75-017933-3S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	325 (147.0)	F ①	WS-A-1	29-E
30.0	NS75-0113102-3S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	400 (181.0)	F ①	WS-A-1	29-E
45.0	NS75-0113103-3S	29.90 (75.9)	28.20 (71.6)	22.40 (56.9)	600 (272.0)	F ①	WS-A-2	29-E
75.0	NS75-0113104-3S	35.90 (91.2)	31.90 (81.0)	26.90 (68.3)	790 (358.0)	F	WS-A-3	29-E
112.5	NS75-0113105-3S	41.50 (105.4)	32.90 (83.6)	29.90 (75.9)	1000 (454.0)	F	WS-A-4	29-E
150.0	NS75-0113106-3S	41.50 (105.4)	32.90 (83.6)	29.90 (75.9)	1250 (567.0)	F	WS-A-4	29-E
225.0	NS75-0113107-3S	45.60 (115.8)	39.50 (100.3)	35.50 (90.2)	1550 (703.0)	F	WS-A-5	29-E
300.0	NS75-113099-3S	62.00 (157.5)	54.00 (137.2)	42.00 (106.7)	2675 (1213.0)	F	WS-B-3	30-G
450.0	NS75-0113111-3S	63.00 (160.0)	54.00 (137.2)	49.50 (125.7)	4000 (1814.0)	F	WS-A-6	49-G
500.0	NS75-0113112-3S	63.00 (160.0)	54.00 (137.2)	49.50 (125.7)	4000 (1814.0)	F	WS-A-6	49-G
600.0	NS75-0113113-3S	63.00 (160.0)	54.00 (137.2)	49.50 (125.7)	4000 (1814.0)	F	WS-A-6	49-G

600 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS

KVA	CATALOG NO.	APPROX. DIMENSIONS ② Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W – Wall F – Floor	WEATHER SHIELD P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH				
15.0	NS25-0079333-3S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	325 (147.0)	F ①	WS-A-1	29-E
30.0	NS25-0013102-3S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	325 (147.0)	F ①	WS-A-1	29-E
45.0	NS25-0013103-3S	29.40 (74.7)	28.20 (71.6)	22.40 (56.9)	425 (193.0)	F ①	WS-A-2	29-E
75.0	NS25-0013104-3S	35.40 (89.9)	31.90 (81.0)	26.90 (68.3)	575 (261.0)	F	WS-A-3	29-E
112.5	NS25-0013105-3S	41.50 (105.4)	32.90 (83.6)	29.90 (75.9)	970 (440.0)	F	WS-A-4	29-E
150.0	NS25-0013106-3S	41.50 (105.4)	32.90 (83.6)	29.90 (75.9)	1140 (517.0)	F	WS-A-4	29-E
225.0	NS25-0013107-3S	45.60 (115.8)	39.50 (100.3)	35.50 (90.2)	1550 (703.0)	F	WS-A-5	29-E
300.0	NS25-013099-3S	52.00 (132.1)	52.00 (132.1)	40.00 (101.6)	2225 (1009.0)	F	WS-A-60	30-G
450.0	NS25-013111-3S	64.00 (162.6)	60.00 (152.4)	42.00 (106.7)	3500 (1588.0)	F	WS-B-4	30-G
500.0	NS25-013112-3S	64.00 (162.6)	60.00 (152.4)	42.00 (106.7)	3500 (1588.0)	F	WS-B-4	30-G
600.0	NS25-0013113-3S	63.00 (160.0)	54.00 (137.2)	49.50 (125.7)	4000 (1814.0)	F	WS-A-6	③

① Wall mounting brackets are available for these sizes, refer to page 50.

② Dimensions in this section may change and are not to be used for detailed construction purposes. Please contact the factory for certified dimensional drawings.

③ Consult factory for wiring diagrams.