



PWR13XX SERIES
1.5 WATTS
UNREGULATED

DC/DC CONVERTERS

4000V HIGH ISOLATION VOLTAGE RATING

FEATURES

- HIGH ISOLATION - 4000V RATING
- 8000V ISOLATION TEST VOLTAGE
- BARRIER 100% PRODUCTION TESTED
- LOW BARRIER CAPACITANCE - 10pF
- LOW LEAKAGE CURRENT - 2 μ A MAX
- 24-PIN DIP PACKAGE
- INTERNAL FILTERING

DESCRIPTION

The PWR13XX Series offers a broad line of low-cost, high-isolation voltage, unregulated, single and dual output DC/DC converters in a 24-pin DIP package. These small converters offer a 4000V isolation rating in a 1.25" x 0.8" package area.

The dielectric withstand characteristics of each converter is tested in production to ensure barrier integrity. During the development of the PWR13XX Series extensive testing was done to verify that subjecting the barrier to as many as ten barrier tests will not destroy the barrier.

The PWR13XX Series uses advanced circuit design and packaging technology to realize superior reliability and performance. A 220kHz driven push-pull oscillator is used to ensure stable frequency and non-saturating operation of the input stage. This means there are no high peak voltages or currents like other design topologies, which can reduce unit reliability.

APPLICATIONS

- BIOMEDICAL DATA ACQUISITION
- INDUSTRIAL PROCESS CONTROL
- ANALYTICAL MEASUREMENTS
- GROUND LOOP ELIMINATION
- INTRINSIC SAFETY SYSTEMS

Reliability is further enhanced by the use of MOSPOWER transistors. These rugged devices permit higher frequency operation with less complicated drive circuitry than is possible with bipolar power transistors. Reduced parts count adds to the reliability of the PWR13XX Series.

The high efficiency of the PWR13XX Series means less internal power dissipation. With less heat to dissipate, the PWR13XX Series can operate over a wider ambient temperature range with no degradation of reliable operation.

The PWR13XX Series offers the user low cost without sacrificing reliability. The use of surface mounted devices and manufacturing technologies make it possible to offer premium performance and low cost. Testing of the PWR13XX isolation barrier is performed per the methods set forth by UL544, VDE750, CSA 22.2 and IEC 601-1.

ELECTRICAL SPECIFICATIONS

Specifications typical at $T_A = +25^\circ\text{C}$, nominal input voltage, rated output current unless otherwise noted.

MODEL	NOMINAL INPUT VOLTAGE (VDC)	RATED OUTPUT VOLTAGE (VDC)	RATED OUTPUT CURRENT (mA)	INPUT CURRENT		REFLECTED RIPPLE CURRENT (mA _{p-p})
				NO LOAD (mA)	RATED LOAD (mA)	
PWR1300	5	5	300	50	400	30
PWR1301	5	12	125	50	400	30
PWR1302	5	15	100	50	400	30
PWR1303	5	±5	±150	50	400	30
PWR1304	5	±12	±63	50	400	30
PWR1305	5	±15	±50	50	400	30
PWR1306	12	5	300	30	167	25
PWR1307	12	12	125	30	167	25
PWR1308	12	15	100	30	167	25
PWR1309	12	±5	±150	30	167	25
PWR1310	12	±12	±63	30	167	25
PWR1311	12	±15	±50	30	167	25
PWR1312	15	5	300	30	133	20
PWR1313	15	12	125	30	133	20
PWR1314	15	15	100	30	133	20
PWR1315	15	±5	±150	30	133	20
PWR1316	15	±12	±63	30	133	20
PWR1317	15	±15	±50	30	133	20

NOTE: Other input to output voltage options may be available. Please consult factory.

COMMON SPECIFICATIONS


Specifications typical at $T_A = +25^\circ\text{C}$, nominal input voltage, rated output current unless otherwise noted.

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
INPUT Voltage Range		4.5 13.5	5 15	5.5 16.5	VDC VDC
ISOLATION Rated Voltage Test Voltage Resistance Capacitance Leakage Current	60 Hz, 60 Seconds $V_{iso} = 240\text{VAC}, 60\text{Hz}$	4,000 8,000	10 10 1	2	VDC Vpk GΩ pF μArms
OUTPUT Rated Power Voltage Setpoint Accuracy Ripple & Noise	Rated Load, Nominal V_n BW = DC to 10MHz BW = 10Hz to 2MHz		1.5 40 10	±5	Watts % mVp-p mVrms
REGULATION Line Regulation Load Regulation	High Line to Low Line See Performance Curves		1.5		%/%
GENERAL Efficiency Switching Frequency Package Weight MTTF per MIL-HDBK-217, Rev. E* Ground Benign Fixed Ground Naval Sheltered Airborne Uninhabited Fighter	Circuit Stress Method $T_A = +25^\circ\text{C}$ $T_A = +85^\circ\text{C}$ $T_A = +35^\circ\text{C}$ $T_A = +35^\circ\text{C}$ $T_A = +35^\circ\text{C}$		75 220 12 2,000,000 90,000 540,000 300,000 55,000		% kHz g Hr Hr Hr Hr Hr
TEMPERATURE Specification Operation Storage		-40 -55 -55	+25	+85 +100 +110	°C °C °C


* For demonstrated MTTF results reference Power Convertibles' Reliability Report PWR1304A

MECHANICAL


TOPVIEW - "A" Package Option




TOPVIEW - "B" Package Option




SIDEVIEW - "A" Package Option




SIDEVIEW - "B" Package Option



BOTTOMVIEW - "A" Package Option



BOTTOMVIEW - "B" Package Option



PIN CONNECTIONS

"A" Package Option Only

PIN	SINGLE MODELS	DUAL MODELS
1	+V _{IN}	+V _{IN}
2	+V _{IN}	+V _{IN}
11	+V _{OUT}	+V _{OUT}
12	+V _{OUT}	+V _{OUT}
13	-V _{OUT}	Common *
14	-V _{OUT}	Common *
15	No Pin	-V _{OUT}
23	-V _{IN}	-V _{IN}
24	-V _{IN}	-V _{IN}

Notes:

All dimensions are in inches (millimeters).

GRID: 0.100 inches (2.54 millimeters)

* Common pins not present on single output models.

PIN PLACEMENT TOLERANCE: ±0.015"

Marked with: specific model ordered, date code, job code.

MATERIAL: Units are encapsulated in Iso-ThermoFlex™, a low thermal resistance molding compound which has excellent chemical resistance, wide operating temperature range, and good electrical properties under high humidity environments. The encapsulant and outer shell of the unit have UL94V-0 ratings. Lead material is brass with a solder plated surface to allow ease of solderability.

ABSOLUTE MAXIMUM RATINGS

Output Short-Circuit Duration.....	5 seconds
Internal Power Dissipation.....	750mW
Lead Temperature (soldering, 10 seconds max).....	+300°C

ORDERING INFORMATION

Device Family _____	PWR	13XX	A	H
PWR Indicates DC/DC Converter				
Model Number _____	Selected from Electrical Specifications Table			
Package Option _____	Choose From A or B			
Screening Option _____				

TYPICAL PERFORMANCE CURVES

Specifications at $T_a = +25^\circ\text{C}$, nominal input voltage, rated output current

