

Electrical Characteristics (At Ta=25°C, Unless Otherwise Specified)											
Type No.	V _{ZT} at I _{ZT}			r _{ZT} at I _{ZT} max (Ohm)	I _{ZT} (mA)	Temp. Coeff. of Zener Voltage typ (%/°C)	I _R at V _R Ta 25°C max (µA)	V _R (V)	P _D (W)	V _F @ I _F max (V) (mA)	
	min	nom	max (V)								
1CZ5V1	4.8	5.4	20	20	20	-0.01	10	1	1	1.2	200
1CZ5V6	5.2	6	15	20	20	+0.008	10	2	1	1.2	200
1CZ6V2	5.8	6.6	10	20	20	+0.025	10	3	1	1.2	200
1CZ6V8	6.4	7.2	8	20	20	+0.035	10	4	1	1.2	200
1CZ7V5	7	7.9	8	10	10	+0.045	10	5	1	1.2	200
1CZ8V2	7.7	8.7	8	10	10	+0.055	10	6	1	1.2	200
1CZ9V1	8.5	9.6	10	10	10	+0.06	10	7	1	1.2	200
1CZ10	9.4	10.6	15	10	10	+0.08	10	8	1	1.2	200
1CZ11	10.4	11.6	20	10	10	+0.065	10	8.5	1	1.2	200
1CZ12	11.4	12.7	20	10	10	+0.07	10	9	1	1.2	200
1CZ13	12.4	14.1	25	5	5	+0.075	10	10	1	1.2	200
1CZ15	13.8	15.6	30	5	5	+0.08	10	11	1	1.2	200
1CZ16	15.3	17.1	40	5	5	+0.085	10	12	1	1.2	200
1CZ18	16.8	19.1	50	5	5	+0.09	10	13.5	1	1.2	200
1CZ20	18.8	21.2	55	5	5	+0.1	10	15	1	1.2	200
1CZ22	20.8	23.3	58	5	5		10	16	1	1.2	200
1CZ24	22.8	25.6	80	5	5		10	18	1	1.2	200