

FLK 14/EZ-DR/ 60/KONFEK/S

Order No.: 2299068

The illustration shows a 50-pos. version

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2299068>Round shielded cable set, with two 14-pos. female connectors, cable
length: 0.6 m**Commercial data**

EAN	4017918828196
Pack	1 pcs.
Customs tariff	85444993
Weight/Piece	0.058 KG

Product notesWEEE/RoHS-compliant since:
12/11/2006

[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data**General**

Nominal voltage U_N	< 50 V AC
	60 V DC
Max. conductor resistance	0.16 Ω /m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Shielding	Tinned copper-braided shield, approx. 85% covering
Width	29.6 mm
Length	40 mm

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2009 Phoenix Contact
Technical modifications reserved;