


EB71F62 Series

- Oven Controlled Crystal Oscillators (OCXO)
- HCMOS Output
- +5.0V Supply Voltage
- SC-Cut Crystal Used
- External Voltage Control Function
- 5 pin DIP Metal Package



ELECTRICAL SPECIFICATIONS

Frequency Range	10.000MHz, 12.288MHz, 12.800MHz, 16.000MHz, 19.440MHz, or 20.000MHz	
Operating Temperature Range (OTR)	0°C to 50°C, 0°C to 70°C, or -20°C to 70°C	
Storage Temperature Range	-55°C to 125°C	
Supply Voltage (V_{DD})	5.0V _{DC} ±5%	
Frequency Tolerance / Stability		
vs. Initial Tolerance	at Nominal V _{DD} and V _C , at 25°C	±500ppb or ±300ppb Maximum
vs. Temperature Stability	at Nominal V _{DD} and V _C	±20ppb, ±30ppb, ±50ppb, ±80ppb, ±100ppb, ±200ppb, or ±280ppb Maximum
vs. V _{DD}	V _{DD} ±5%	±20ppb Maximum
vs. Load	V _{load} ±5%	±20ppb Maximum
vs. Aging (1 Day)	after 72 Hours of Operation	±2.0ppb Maximum
vs. Aging (1 Year)	after 72 Hours of Operation	±100ppb Maximum
vs. Aging (10 Years)	after 72 Hours of Operation	±500ppb Maximum
Crystal Cut	SC-Cut	
Warm Up Time	to ±100ppb of Final Frequency at 1 Hour at 25°C	3 Minute Maximum
Power Consumption	at Steady State, at 25°C	1.2 Watts Maximum
	During Warm Up, at 25°C	3.6 Watts Maximum
Output Voltage Logic High (V_{OH})	I _{OH} = -8mA	V _{DD} -0.5V _{DC} Minimum
Output Voltage Logic Low (V_{OL})	I _{OL} = +8mA	0.5V _{DC} Maximum
Rise Time / Fall Time	Measured at 20% to 80% of Waveform	6nSec Maximum
Duty Cycle	Measured at 50% of Waveform	50 ±5(%)
Load Drive Capability		15pF Maximum
Frequency Deviation	Referenced to F ₀ at V _C = 2.5V _{DC} ; V _{DD} =5.0V _{DC} over OTR	±1.0ppm Minimum
Control Voltage Range		0.0V _{DC} to V _{DD}
Control Voltage (V_C)		2.5V _{DC} ±2.5V _{DC}
Transfer Function		Positive Transfer Characteristic
Reference Voltage Output		4.5V _{DC} ±0.3V _{DC} (Pin 5)
Linearity		±10% Maximum
Input Impedance		10kOhms Typical
Typical Phase Noise (at 12.800MHz)	1Hz Offset	-85dBc/Hz
	10Hz Offset	-100dBc/Hz
	100Hz Offset	-130dBc/Hz
	1kHz Offset	-145dBc/Hz
	10kHz Offset	-150dBc/Hz

MANUFACTURER ECLIPTEK CORP.	CATEGORY OSCILLATOR	SERIES EB71F62	PACKAGE 5 pin DIP	VOLTAGE 5.0V	CLASS OS2J	REV. DATE 06/09
--------------------------------	------------------------	-------------------	----------------------	-----------------	---------------	--------------------

PART NUMBERING GUIDE

EB71F62 D 10 B V 2 - 20.000M

INITIAL TOLERANCE

D=±500ppb
E=±300ppb

FREQUENCY STABILITY

2 Digit Code Per Table 1

OPERATING TEMPERATURE RANGE

1 Letter Code Per Table 1

FREQUENCY

DUTY CYCLE

2=50% ±5%

VOLTAGE CONTROL OPTION


V=Voltage Control on Pin 4 and Reference Voltage Output on Pin 5

TABLE 1: PART NUMBERING CODES



Operating Temperature Range	FREQUENCY STABILITY X Denotes availability							
		±20ppb	±30ppb	±50ppb	±80ppb	±100ppb	±200ppb	±280ppb
	Code	02	03	05	08	10	20	28
0°C to +50°C	A	X	X	X	X	X	X	X
0°C to +70°C	B		X	X	X	X	X	X
-20°C to +70°C	C			X	X	X	X	X

MECHANICAL DIMENSIONS

ALL DIMENSIONS IN MILLIMETERS



- Pin 1: Supply Voltage
- Pin 2: Output
- Pin 3: Case/Ground
- Pin 4: Voltage Control
- Pin 5: Reference Voltage Output



ENVIRONMENTAL/MECHANICAL SPECIFICATIONS

Characteristic

Specification

Gross Leak Test	MIL-STD-883, Method 1014, Condition C
Mechanical Shock	MIL-STD-202, Method 213, Condition C
Vibration	MIL-STD-883, Method 2007, Condition A
Lead Integrity	MIL-STD-883, Method 2004
Solderability	MIL-STD-883, Method 2002
Temperature Cycling	MIL-STD-883, Method 1010
Resistance to Soldering Heat	MIL-STD-883, Method 210
Resistance to Solvents	MIL-STD-883, Method 215

MARKING SPECIFICATIONS

Line 1: ECLIPTEK

Line 2: XX.XXX M

Frequency in MHz
(5 Digits Maximum + Decimal)

Line 3: XX Y ZZ

Week of Year
Last Digit of Year
Ecliptek Manufacturing Identifier

Note: Pin 1 shall be designated with a dot

MANUFACTURER ECLIPTEK CORP.	CATEGORY OSCILLATOR	SERIES EB71F62	PACKAGE 5 pin DIP	VOLTAGE 5.0V	CLASS OS2J	REV. DATE 06/09
--------------------------------	------------------------	-------------------	----------------------	-----------------	---------------	--------------------