

KM2520xxx03



KM2520xxx08



KM2520xxx09



Part No.	Material	λ D (nm)	Lens Type	Iv (mcd) @20mA		Viewing Angle	Dimension
				Min.	Typ.		
KM2520SURC03	InGaAlP	628	water clear	650	1600	20°	Subminiature Solid State Lamps Gull Wing Lead
KM2520SURCK03	InGaAlP	635	water clear	480	1400	20°	
KM2520SEC03	InGaAlP	601	water clear	1200	2000	20°	
KM2520SECK03	InGaAlP	601	water clear	900	1800	20°	
KM2520SYC03	InGaAlP	588	water clear	900	1500	20°	
KM2520SYCK03	InGaAlP	590	water clear	650	1300	20°	
KM2520MGC03	InGaAlP	568	water clear	280	600	20°	
KM2520CGCK03	InGaAlP	570	water clear	110	400	20°	
KM2520ZGC03	AlInGaN	525	water clear	1800	3300	20°	
KM2520VGC-A03	InGaN	525	water clear	380	800	20°	
KM2520VGC-Z03	InGaN	535	water clear	3300	6400	20°	
KM2520QBC-D03	AlInGaN	470	water clear	180	500	20°	
KM2520PBC-A03	InGaN	470	water clear	110	250	20°	
KM2520PBC-J03	InGaN	470	water clear	380	1000	20°	
KM2520SURC08	InGaAlP	628	water clear	650	1600	20°	Subminiature Solid State Lamps Yoke Lead
KM2520SURCK08	InGaAlP	635	water clear	480	1400	20°	
KM2520SEC08	InGaAlP	601	water clear	1200	2000	20°	
KM2520SECK08	InGaAlP	601	water clear	900	1800	20°	
KM2520SYC08	InGaAlP	588	water clear	900	1500	20°	
KM2520SYCK08	InGaAlP	590	water clear	650	1300	20°	
KM2520MGC08	InGaAlP	568	water clear	280	600	20°	
KM2520CGCK08	InGaAlP	570	water clear	110	400	20°	
KM2520ZGC08	AlInGaN	525	water clear	1800	3300	20°	
KM2520VGC-A08	InGaN	525	water clear	380	800	20°	
KM2520VGC-Z08	InGaN	535	water clear	3300	6400	20°	
KM2520QBC-D08	AlInGaN	470	water clear	180	500	20°	
KM2520PBC-A08	InGaN	470	water clear	110	250	20°	
KM2520PBC-J08	InGaN	470	water clear	380	1000	20°	
KM2520SURC09	InGaAlP	628	water clear	650	1600	20°	Subminiature Solid State Lamps Z-Bend Lead
KM2520SURCK09	InGaAlP	635	water clear	480	1400	20°	
KM2520SEC09	InGaAlP	601	water clear	1200	2000	20°	
KM2520SECK09	InGaAlP	601	water clear	900	1800	20°	
KM2520SYC09	InGaAlP	588	water clear	900	1500	20°	
KM2520SYCK09	InGaAlP	590	water clear	650	1300	20°	
KM2520MGC09	InGaAlP	568	water clear	280	600	20°	
KM2520CGCK09	InGaAlP	570	water clear	110	400	20°	
KM2520ZGC09	AlInGaN	525	water clear	1800	3300	20°	
KM2520VGC-A09	InGaN	525	water clear	380	800	20°	
KM2520VGC-Z09	InGaN	535	water clear	3300	6400	20°	
KM2520QBC-D09	AlInGaN	470	water clear	180	500	20°	
KM2520PBC-A09	InGaN	470	water clear	110	250	20°	
KM2520PBC-J09	InGaN	470	water clear	380	1000	20°	

NOTES:

1. All dimensions are in millimeters(inches).
2. Tolerance is $\pm 0.25\text{mm}(0.01")$ unless otherwise noted.