

SC10331KT Product Details

 [Live Product Chat](#)



SC10331KT
(1623953-2)

TE Internal Number: 1623953-2

 [Active](#)

Inductors

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Inductor
- Inductor Type = RF
- Lead Type = Axial Leaded
- Wirewound
- Inductance = 330 ?H

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [Axial Leaded Power Inductors - Type SC10, SC15, SC30...](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Inductor
- Inductor Type = RF
- [Element](#) = Wirewound
- [Shielded](#) = No

Electrical Characteristics:

- [Inductance \(?H\)](#) = 330
- [DC Resistance \(?\)](#) = 22
- [Current, Maximum \(mA\)](#) = 103
- [Quality Factor](#) = 45
- [Package Type](#) = Ammo Packed
- Tolerance (%) = 10

Body Related Features:

- [Lead Type](#) = Axial Leaded
- [Series](#) = SC10
- [Package, Component Size](#) = 10.0 x 4.2
- [Mount Style](#) = Through-Hole

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Operation/Application:

- [Application](#) = Radio Frequency

Other:

- Brand = Sigma Inductors