

HIGH FREQUENCY PATCH CORDS



BNC Male to Standard Alligator Clips with Boots

PART NO.	LENGTH INCHES	WIRE	INSULATION
1587-12	12	RG 58/U Coaxial Cable Impedance 50 Ohms CTR	Polyethylene Insulation Black PVC Jacket
1587-24	24		
1587-36	36		
1587-48	48		
1587-60	60		



BNC Male to Miniature Alligator Clips with Boots

PART NO.	LENGTH INCHES	WIRE	INSULATION
1791-12	12	RG 58/U Coaxial Cable Impedance 50 Ohms CTR	Polyethylene Insulation Black PVC Jacket
1791-24	24		
1791-36	36		
1791-48	48		
1791-60	60		



BNC Male to BNC Male

PART NO.	LENGTH INCHES	WIRE	INSULATION
1589-12	12	RG 58/U Coaxial Cable Impedance 50 Ohms CTR	Polyethylene Insulation Black PVC Jacket
1589-24	24		
1589-36	36		
1589-48	48		
1589-60	60		



BNC Male to Dual Banana Plug

PART NO.	LENGTH INCHES	WIRE	INSULATION
1584-12	12	RG 58/U Coaxial Cable Impedance 50 Ohms CTR	Polyethylene Insulation Black PVC Jacket
1584-24	24		
1584-36	36		
1584-48	48		
1584-60	60		

◆ Please note that, except for types with coaxial connectors at both ends, impedance mismatches will exist when using these cables for temporary connections.

◆ Please refer to the Test Lead Specifications table on page 9 for rating information.

