

REV. X0



<http://www.stewartconnector.com>

Stewart Connector Systems, Inc.
Insilco Technologies Group
11118 Susquehanna Trail South
Glen Rock, PA 17327-9199
(717) 235-7512 Fax: (717) 235-7954

REV.	REVISION CHANGES	ECN
X0	AS DRAWN	-


PART NO. SS-748804-GY-NF

LED SPECIFICATIONS

STANDARD LED	* FORWARD VOLTAGE (MAX)	* FORWARD VOLTAGE (TYP)	POWER DISSIPATION	WAVELENGTH	LUMINOUS INTENSITY @ 10mA	
					MIN	MAX
YELLOW DIFFUSED	2.5 V	2.1 V	105 mW	590 nm	2 MCD	8 MCD
GREEN DIFFUSED	2.6 V	2.25 V	105 mW	555 nm	2 MCD	8 MCD

* WITH A FORWARD CURRENT OF 20 mA

LED POLARITY (ENLARGED VIEW)




SINGLE COLOR LED

FOR REFERENCE ONLY

SHEET 2 OF 2

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF STEWART CONNECTOR SYSTEMS ("SCS") AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONSENT OF "SCS". THE SUBJECT MATTER MAY BE PATENTED OR A PATENT MAY BE PENDING. © SCS

THIRD ANGLE PROJECTION



DRN BY: T. R. MECKLEY

DATE 12-19-00

ORIGINAL PROPOSAL DRAWING

CKD BY: DAVE GUTTER

DATE 12-19-00

ENR NUMBER 9214

APPD BY: BOB COLANTUONO

DATE 12-20-00

PROJECT NO. -

UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE ± 0.05 [± 0.13]

DWG NO. CT740062

REV. X0