

361 Product Details

[Live Product Chat](#) Product View

NEMA Terminal Blocks

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- 300 Series Block Series
- Terminal Block
- Block Type = Fuse
- In-Line Circuit Protection Application
- Contact Type = Strap Screw

[View all Features](#)

Quick Links

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

361

(3-1437397-2)

TE Internal Number: 3-1437397-2

[Active](#)[Add to My Part List](#)[Request Sample](#)[Find Similar Products](#)[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [BUCHANAN TERMINAL BLOCKS CATALOG - NEMA TERMINAL BLOCKS](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Line Drawing](#)
- [Typical Mounting Configuration](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Terminal Block
- Screw Size = 10-32 Binding Head

Electrical Characteristics:

- Voltage Rating (VAC) = 600
- Amperes (Amps.) = 25.0

Body Related Features:

- [Block Series](#) = 300 Series
- [Block Type](#) = Fuse
- Mount Style = Direct Mount (Flat Base)
- [Wire Range \(Solid and Stranded\)\[MCM\] \(AWG\)](#) = 22-8
- [Blown Fuse Indicator](#) = Without
- [Blown Fuse Indicator Type](#) = None
- Flammability Rating = UL 94V-1

Contact Related Features:

- Contact Type = Strap Screw
- Pitch (mm [in]) = 19.05 [0.750]

Housing Related Features:

- [Housing Material](#) = Phenolic

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Temperature, Max. (?C) = 150

Operation/Application:

- Application = In-Line Circuit Protection

Packaging Related Features:

- Terminals Per Foot = 16

Other:

- [Fuse Puller](#) = Without
- Brand = Buchanan