

Programmable Attenuators...dc-26.5 GHz

Model Number	Connector Type	Frequency Range (GHz)	Incremental Attenuation Range (dB)	Insertion Loss (dB)	Average Power (Watts)	Peak Power (Watts)	Maximum SWR	
3200-1 3200-2	SMA	dc-2.0	0-127/1 0-63.75/0.25	3.00-4.75*	1	50	1.25-1.35*	
3201-1 3201-2 3201-4 3205-1 3205-2 3205-3 3206-1	SMA	dc-2.0	0-31/1 0-120/10 0-1.2/0.1 0-70/10 0-55/5 0-1.5/0.1 0-63/1	2.25-3.75*	1	50	1.25-1.35*	
3200T-1 3200T-2 3201T-1 3201T-2 3206T-1	SMA SMA	dc-2.0 dc-2.0	0-127/1 0-63.75/0.25 0-31/1 0-120/10 0-63/1	3.00-4.75* 2.25-3.75*	1 1	50 50	1.25-1.35* 1.25-1.35*	
3202-1	SMA	dc-2.0	0.5/0.5 (Single Cell)	0.5-0.75*	1	50	1.25-1.35*	
3203-1 3204-1	SMA	dc-1.5	0-103/1 0-55/1	2.50-3.75* 2.00-3.25*	1	50	1.25-1.35*	
3220-1 3221-1 3221-2	SMA	dc-2.0	0-127/1 0-31/1 0-120/10	2.25-4.75*	1	50	1.25-1.35*	
3230-63 3230-90 3231-95.5 3231-63.75	SMA	dc-1.2	0-63/1 0-90/10 0-95.5/0.5 0-63.75/0.25	1.75-4.25* 1.75-4.25* 1.75-4.90* 1.75-4.90*	1	50	1.30-1.45*	
3250-63 (75 Ω)	BNC	dc-1.0	0-63/1	2.25-4.25*	1	50	1.20-1.30*	
150-11 150-15 150-62 150-70 150-75 150-110 151-11 151-15 151-62 151-70 151-75 151-110 152-11 152-15 152-55 152-70 152-90	3.5mm 3.5mm 3.5mm	dc-18.0 dc-4.0 dc-26.5	0-11/1 0-15/1 0-62/2 0-70/10 0-75/5 0-110/10 0-11/1 0-15/1 0-62/2 0-70/10 0-75/5 0-110/10 0-11/1 0-15/1 0-55/5 0-70/10 0-90/10	0.9-2.2* 0.9-2.2* 1.1-1.6* 0.7-1.6* 0.9-2.2* 0.9-2.2* 0.9 0.9 1.1 0.7 0.9 0.9 0.9 0.9-2.98* 	1 1 1	100 100 100	1.50-1.90* 1.50-1.90* 1.50-1.90* 1.35-1.70* 1.50-1.90* 1.50-1.90* 1.50 1.50 1.50 1.35 1.50 1.50 1.50 1.40-1.80 	
150T-11 150T-15 150-T62 150T-70 150T-75 150T-110 151T-11 151T-15 151T-62 151T-70 151T-75 151T-110 152T-11 152T-15 152T-55 152T-70 152T-90 155T-11 155T-70 155T-90	3.5mm 3.5mm 3.5mm SMA	dc-18.0 dc-4.0 dc-26.5 dc-8.0	0-11/1 0-15/1 0-62/2 0-70/10 0-75/5 0-110/10 0-11/1 0-15/1 0-62/2 0-70/10 0-75/5 0-110/10 0-11/1 0-15/1 0-55/5 0-70/10 0-90/10 0-11/1 0-70/10 0-90/10	0.9-2.2* 0.9-2.2* 1.1-1.6* 0.7-1.6* 0.9-2.2* 0.9-2.2* 0.9 0.9 1.1 0.7 0.9 0.9 0.9-2.98* 0.9-1.5* 0.7-1.5* 0.9-1.5*	1 1 1	100 100 100	1.50-1.90* 1.50-1.90* 1.50-1.90* 1.35-1.70* 1.50-1.90* 1.50-1.90* 1.50 1.50 1.50 1.35 1.50 1.50 1.40-1.80 1.50-1.80* 1.35-1.50* 1.50-1.80*	
8300-1 8300-2 8300-3	PLANAR CONN SYSTEM	dc-2.0 dc-18.0 dc-26.5	127/1 121/1 110/5	3.0-5.25* 8.0-12.0* 8.0-14.0*	1 1 1	50 100 100	1.25-1.35* 1.25-1.85* 1.20-1.80*	

* VARIES WITH FREQUENCY.