



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1 BRASS PER QQ-B-626
- 2 NICKEL PL 80 MIN. THICK OVER COPPER STRIKE
- 3 BRIGHT TIN PL. 80 MIN. THICK OVER COPPER PL. 100 MIN.
- 4 GASKET N.B.R. , BLACK (SUPPLIED BY CUSTOMER)

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

PART NO.	F7310-NPPT	
APPROVED	DATE	10-11-01'
CHECKED	DATE	10-11-01'
DRAWN	DATE	10-11-01'
FILE NO.		

<b>Amphenol</b>	
TITLE	F CONNECTOR
DRAWING NO.	KJ-F7310-NPPT
ITEM NO.	

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
5	GASKET	NOTE 4	NOTE 4	1	GS-95/75XD1
4	INSULATOR	DELRIIN	NATURAL	1	F7310-4
3	CONTACT PIN	NOTE 1	NOTE 3	1	F7310-3
2	INSULATOR	P.P.	WHITE	1	835-0500-010-2
1	BODY	NOTE 1	NOTE 2	1	F7310-1

1 2 3 4 5 6 7 8