



## AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type



Dimensions in mm

- (1) Hole  $\varnothing$  1.3 for  $d_t = 0.8$  mm
- (2)  $0 \leq \alpha < 50^\circ$
- (3)  $|F - F'| < 0.3$  mm  
 $F = 7.5 + 0.6/-0.1$  mm
- (4)  $A = 2.0 + 1.0/-0.5$  mm for 10 mm pitch  
 $A = 2.5 + 1.5/-0.5$  mm for 15 mm pitch  
 $A = 2.5 + 1.4/-0.5$  mm for pitch  $> 22.5$  mm



Dimensions in mm

### APPLICATIONS

Where high currents and steep pulses occur. For deflection circuits in television sets.

### REFERENCE SPECIFICATIONS

IEC 60384-17

### MARKING

C-value; tolerance; rated voltage; manufacturer's type; manufacturer's location

### DIELECTRIC

Polypropylene film

### ELECTRODES

Metallized and aluminum

### CONSTRUCTION

Internal serial construction

### RATED (DC) VOLTAGE

630 V, 1000 V, 1600 V, 2000 V

### RATED (AC) VOLTAGE

300 V, 400 V, 500 V, 600 V

### RATED PEAK-TO-PEAK VOLTAGE

850 V, 1100 V, 1400 V, 1700 V

### FEATURES

- 10 mm to 27.5 mm pitch
- Supplied loose in box (including lock lead versions) and taped
- Bent back version for automatic insertion available
- Compliant to RoHS directive 2002/95/EC



**RoHS**  
COMPLIANT

### ENCAPSULATION

Flame retardant epoxy material  
(Class UL 94 V-0)

### CLIMATIC TESTING CLASS ACC. TO IEC 60068-1

55/105/56

### CAPACITANCE RANGE (E24 SERIES)

0.1 nF to 270 nF

### CAPACITANCE TOLERANCE

$\pm 5\%$ ;  $\pm 3.5\%$

### LEADS

Tinned wire

### RATED TEMPERATURE

85 °C

### MAXIMUM APPLICATION TEMPERATURE

105 °C

### PERFORMANCE GRADE

for  $C > 5.6$  nF: grade 1 (long life)  
for  $C \leq 5.6$  nF: grade 2

### STABILITY GRADE


Grade 2

### DETAIL SPECIFICATION

For more detailed data and test requirements contact:

[dc-film@vishay.com](mailto:dc-film@vishay.com)

### COMPOSITION OF CATALOG NUMBER



TYPE	PACKAGING	LEAD CONFIGURATION	PREFERRED TYPES				
			C-TOL.	630 V	1000 V	1600 V	2000 V
375	Loose in box	Lead length 5.0 mm ± 1.0 mm	± 5 %	14	24	34	44
		Lock lead 4.0 mm + 1.0/- 0.5 mm	± 5 %	90	90	90	90
	Taped on reel <sup>(2)</sup> (bent back)	H = 16.0 mm; P <sub>0</sub> = 15.0 mm; Reel diameter 500 mm	± 5 %	16	26	36	46
Dimensions of this code numbers stays between brackets							
<b>ON REQUEST</b>							
375	Loose in box	Lead length 5.0 ± 1.0 mm	± 3.5 %	15	25	35	45
		Lead length 3.5 ± 0.5 mm	± 5 %	10	20	30	40
			± 3.5 %	11	21	31	41
	Taped on reel <sup>(2)</sup> (bent back)	H = 16.0 mm; P <sub>0</sub> = 12.7 mm; Reel diameter = 500 mm	± 5 %	12	22	32	42
		H = 16.0 mm; P <sub>0</sub> = 15.0 mm; Reel diameter = 500 mm	± 3.5 %	13	23	33	43
			± 3.5 %	17	27	37	47
Dimensions of this code numbers stays between brackets							
		H = 16.0 mm; P <sub>0</sub> = 15.0 mm; Reel diameter = 356 mm	± 5 %	18	28	38	48

**Note**

<sup>(1)</sup> For detailed tape specifications refer to "Packaging Information" [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139) or end of catalog

### SPECIFIC REFERENCE DATA (630 V<sub>DC</sub>)

DESCRIPTION	VALUE	
	10 kHz	100 kHz
Tangent of loss angle at (x 10 <sup>-4</sup> ) Pitch = 10 mm, 15 mm and 7.5 mm (bent back) Pitch = 22.5 mm Pitch = 27.5 mm	≤ 6 ≤ 8 ≤ 8	≤ 10 ≤ 15 ≤ 20
Rated voltage pulse slope (dU/dt) <sub>R</sub> : Pitch = 10 mm Pitch = 15 mm and 7.5 mm (bent back) Pitch = 22.5 mm Pitch = 27.5 mm	15 000 V/μs 8000 V/μs 2800 V/μs 1900 V/μs	
R between leads at 500 V, 1 min	> 100 000 MΩ	
R between interconnected leads and case, 500 V, 1 min	> 100 000 MΩ	
Ionisation (AC) voltage (typical value) at 50 pC peak discharge at 50 pC peak discharge at 20 pC peak discharge	> 400 V	
Withstanding (DC) voltage (cut off current 10 mA), rise time 1000 V/s For C ≤ 47 nF For C > 47 nF	1008 V, 1 min	
Withstanding (DC) voltage between leads and case	2840 V, 1 min	
Maximum application temperature	105 °C	



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

$U_{RDC} = 630\text{ V}$ ;  $U_{RAC} = 300\text{ V}$ ;  $U_{pp} = 850\text{ V}$  (kinked); C-tol. =  $\pm 5\%$

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING				
			LOOSE IN BOX	REEL			C VALUE
			Leads 5 mm $\pm$ 1.0 mm	Original pitch	Pitch = 7.5 mm (bent back)		..YYY
				$\varnothing$ 500 mm	$\varnothing$ 500 mm	$\varnothing$ 356 mm	
XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)				
C (pF)	Pitch = 10.0 mm $\pm$ 0.4 mm; $d_t = 0.60\text{ mm} \pm 0.06\text{ mm}$		Pitch = 10.0 mm	Pitch = 7.5 mm (bent back)			
680	5.0 x 13.0 x 14.5	0.65	14... (2000)	12... (1200)		681	
750						751	
820	5.5 x 13.5 x 14.5	0.70	14... (2000)	12... (1100)		821	
910						911	
1000		102					
1100		112					
1200		122					
1300		132					
1500		152					
1600	0.85	162					
1800	6.0 x 14.0 x 14.5	0.80	14... (1750)	12... (1000)		182	
2000		0.85				202	
2200		0.90				222	
2400		1.0				242	
2700	6.5 x 14.5 x 14.5	1.1	14... (1500)	12... (900)		272	

**Note**

<sup>(1)</sup> Net weight for short lead product only

- SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 630 \text{ V}$ ;  $U_{RAC} = 300 \text{ V}$ ;  $U_{pp} = 850 \text{ (kinked)}$ ;  $C\text{-tol.} = \pm 5 \%$

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING				C VALUE
			LOOSE IN BOX	REEL			
			Leads 5 mm ± 1.0 mm	Original pitch	Pitch = 7.5 mm (bent back)		..YYY
				Ø 500 mm	Ø 500 mm	Ø 356 mm	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	
<b>C (pF)</b>	<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>				<b>Pitch = 7.5 mm (bent back)</b>		
3000 3300	5.0 x 14.0 (16.0) x 18.5	1.0	14... (2000)	12... (1200)	16 ... (1000)	18 ... (550)	302 332
3600 3900 4300 4700 5100 5600	5.5 x 14.5 (16.0) x 18.5	1.1	14... (2000)	12... (1100)	16 ... (900)	18 ... (500)	362 392 432 472 512 562
6200 6800 7500 8200 9100 10 000 11 000 12 000 13 000 15 000 16 000	6.0 x 15.0 (16.0) x 18.5	1.2	14... (2000)	12... (1000)	16 ... (800)	18 ... (450)	622 682 752 822 912 103 113 123 133 153 163
18 000 20 000	6.5 x 15.5 (17.0) x 18.5	1.3	14... (1500)	12... (900)	16... (750)	18... (400)	183 203
22 000	7.0 x 16.0 (17.5) x 18.5	1.5	14... (1500)	12... (800)	16... (700)	18... (400)	223
24 000	7.5 x 16.5 (18.0) x 18.5	1.6	14... (1250)	12... (800)	16... (650)	18... (350)	243
27 000 30 000	8.0 x 17.0 (18.5) x 18.5	1.9	14... (1250)	12... (750)	16... (600)	18... (350)	273 303
33 000	8.5 x 17.5 (19.0) x 18.5	2	14... (1000)	12... (700)	16... (550)	18... (300)	333
36 000 39 000	9.0 x 18.5 (20.0) x 18.5	2.3	14... (900)	12... (600)	16... (500)	18... (300)	ON REQUEST
<b>C (µF)</b>	<b>Pitch = 22.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			<b>Pitch = 22.5 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>		
0.036 0.039 0.043 0.047 0.051 0.056 0.062	7.0 x 20.0 x 26.0	2.7	14... (650)	-	-		363 393 433 473 513 563 623
0.068	7.5 x 20.5 x 26.0	3	14... (600)	-	-	-	683
0.075 0.082	8.0 x 21.0 x 26.0	3.3	14... (550)	-	-	-	753 823
0.091	8.5 x 21.5 x 26.0	3.8	14... (500)	-	-	-	913
0.1	9.0 x 22.0 x 26.0	4	14... (450)	-	-	-	104

### Note

<sup>(1)</sup> Net weight for short lead product only

- SPQ = Standard Packing Quantity



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

U<sub>RDC</sub> = 630 V; U<sub>RAC</sub> = 300 V; U<sub>pp</sub> = 850 (kinked); C-tol. = ± 5 %

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING				
			LOOSE IN BOX	REEL			C VALUE
			Leads 5 mm ± 1.0 mm	Original pitch	Pitch = 7.5 mm (bent back)		
				XX (SPQ)	Ø 500 mm	Ø 500 mm	Ø 356 mm
<b>C (µF)</b>	<b>Pitch = 22.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 22.5 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
0.11	9.5 x 22.5 x 26.0	4.3	14... (400)			114	
0.12	10.0 x 23.0 x 26.0	4.7	14... (400)			124	
<b>C (µF)</b>	<b>Pitch = 27.5 mm ± 0.5 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 27.5mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
0.13	9.5 x 22.5 x 30.0	4.7	14... (500)			134	
0.15	10.0 x 23.0 x 30.0	5.2	14... (500)			154	
0.16	10.5 x 23.5 x 30.0	5.5	14... (450)			164	
0.18	11.0 x 24.0 x 30.0	6	14... (400)			184	
0.2	11.5 x 24.5 x 30.0	6.6	14... (400)			204	
0.22	12.5 x 25.5 x 30.0	7.1	14... (350)			224	
0.24	13.0 x 26.0 x 30.0	7.7	14... (300)			244	
0.27	13.5 x 26.5 x 30.0	8.5	14... (300)			274	

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
- SPQ = Standard Packing Quantity

U<sub>RDC</sub> = 630 V; U<sub>RAC</sub> = 300 V; U<sub>pp</sub> = 850 V (lock lead); C-tol. = ± 5 %

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING	
			LOOSE IN BOX	
			l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm	
			(SPQ)	
<b>C (pF)</b>	<b>Pitch = 10.0 mm ± 1.0 mm; d<sub>t</sub> = 0.60 mm ± 0.06 mm</b>			
680	5.5 x 16.5 x 14.5	0.65	90308	(2000)
750			90309	
820			90311	
910			90312	
1000			90313	
1100			90314	
1300			90316	
1500			90317	
1600	90318			
1800	6.0 x 17.0 x 14.5	0.80	90319	(1750)
2000			90321	
2200			90322	
2400			90323	
2700	6.5 x 17.5 x 14.5	1.1	90324	(1500)

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 630 \text{ V}$ ;  $U_{RAC} = 300 \text{ V}$ ;  $U_{pp} = 850 \text{ V}$  (lock lead); C-tol. =  $\pm 5 \%$

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING	
			LOOSE IN BOX	
			$l_t = 4.0 \text{ mm} + 1.0 \text{ mm}/- 0.5 \text{ mm}$	
			(SPQ)	
<b>C (pF)</b>	<b>Pitch = 15.0 mm <math>\pm</math> 1.0 mm; <math>d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}</math></b>			
3000	5.0 x 17.0 x 18.5	1	90325	(2000)
3300			90326	
3600	5.5 x 17.5 x 18.5	1.1	90327	(2000)
3900			90328	
4300			90329	
4700			90331	
5100			90332	
5600			90333	
6200			6.0 x 18.0 x 18.5	
6800	90335			
7500	90336			
8200	90337			
9100	90338			
10 000	90339			
11 000	90236			
12 000	90341			
13 000	90342			
15 000	90343			
16 000	90344			
18 000	6.5 x 18.5 x 18.5	1.4	90218	(1750)
20 000			90345	
22 000	7.0 x 19.0 x 18.5	1.5	90219	(1500)
24 000	7.5 x 19.5 x 18.5	1.6	90221	(1400)
27 000	8.0 x 20.0 x 18.5	1.9	90223	(1250)
30 000			90346	
33 000	8.5 x 20.5 x 18.5	2	90347	(1200)
36 000	9.0 x 21.5 x 18.5	2.3	ON REQUEST	
39 000			(1000)	
<b>C (<math>\mu</math>F)</b>	<b>Pitch = 22.5 mm <math>\pm</math> 1.0 mm; <math>d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}</math></b>			
0.036	7.0 x 23.0 x 26.0	2.7	90348	(600)
0.039			90349	
0.043			90351	
0.047			90352	
0.051			90353	
0.056			90354	
0.062			90355	
0.068	7.5 x 23.5 x 26.0	3	90356	(550)
0.075	8.0 x 24.0 x 26.0	3.3	90357	(500)
0.082			90358	
0.091	8.5 x 24.5 x 26.0	3.8	90359	(450)

### Notes

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING	
			LOOSE IN BOX	
			l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm	
			(SPQ)	
<b>C (μF)</b>	<b>Pitch = 22.5 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
0.1	9.0 x 25.0 x 26.0	4.0	90361	(450)
0.11	9.5 x 25.5 x 26.0	4.3	90362	(400)
0.12	10.0 x 26.0 x 26.0	4.7	90363	(350)
<b>C (μF)</b>	<b>Pitch = 27.5 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
0.13	9.5 x 25.5 x 30.0	4.7	90364	(450)
0.15	10.0 x 26.0 x 30.0	5.2	90365	(400)
0.16	10.5 x 26.5 x 30.0	5.5	90366	(350)
0.18	11.0 x 27.0 x 30.0	6.0	90367	(350)
0.2	11.5 x 27.5 x 30.0	6.6	90368	(350)
0.22	12.5 x 28.5 x 30.0	7.1	90369	(300)
0.24	13.0 x 29.0 x 30.0	7.7	90371	(250)
0.27	13.5 x 29.5 x 30.0	8.5	90372	(250)

**Notes**

<sup>(1)</sup> Net weight for short lead product only

- SPQ = Standard Packing Quantity

**SPECIFIC REFERENCE DATA (1000 V<sub>DC</sub>)**

DESCRIPTION	VALUE	
	10 kHz	100 kHz
Tangent of loss angle at (x 10 <sup>-4</sup> ) Pitch = 10 mm, 15 mm and 7.5 mm (bent back)	≤ 6	≤ 10
Pitch = 22.5 mm	≤ 8	≤ 15
Pitch = 27.5 mm	≤ 8	≤ 20
Rated voltage pulse slope (dU/d <sub>t</sub> ): Pitch = 10 mm	27 000 V/μs	
Pitch = 15 mm and 7.5 mm (bent back)	15 000 V/μs	
Pitch = 22.5 mm	5000 V/μs	
Pitch = 27.5 mm	3300 V/μs	
R between leads at 500 V, 1 min	> 100 000 MΩ	
R between interconnected leads and case, 500 V, 1 min	> 100 000 MΩ	
Ionisation (AC) voltage (typical value) at 50 pC peak discharge at 20 pC peak discharge	> 500 V	
Withstanding (DC) voltage (cut off current 10 mA), rise time 1000 V/s For C ≤ 47 nF For C > 47 nF	1600 V, 1 min [1.6 - (0.0364 x (C - 47))] x 1000 V, 1 min	
Withstanding (DC) voltage between leads and case	2840 V, 1 min	
Maximum application temperature	105 °C	

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 1000 \text{ V}$ ;  $U_{RAC} = 400 \text{ V}$ ;  $U_{pp} = 1100 \text{ V}$  (kinked);  $C\text{-tol.} = \pm 5 \%$

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING				C VALUE
			LOOSE IN BOX	REEL			
			Leads 5 mm ± 1.0 mm	Original pitch	Pitch = 7.5 mm (bent back)		..YYY
				Ø 500 mm	Ø 500 mm	Ø 356 mm	
		XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)		
<b>C (pF)</b>	<b>Pitch = 10.0 mm ± 0.4 mm; d<sub>t</sub> = 0.60 mm ± 0.06 mm</b>		<b>Pitch = 10.0 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
100	5.0 x 13.0 x 14.5	0.5	<b>24...</b> (2000)	<b>22...</b> (1200)	-	<b>101</b>	
110						<b>111</b>	
120						<b>121</b>	
130						<b>131</b>	
150						<b>151</b>	
160	5.5 x 13.5 x 14.5	0.55	<b>24...</b> (2000)	<b>22...</b> (1100)	-	<b>161</b>	
180		0.55				<b>181</b>	
200		0.55				<b>201</b>	
220		0.60				<b>221</b>	
240		0.60				<b>241</b>	
270		0.60				<b>271</b>	
300		0.60				<b>301</b>	
330		0.60				<b>331</b>	
360		0.60				<b>361</b>	
390		0.65				<b>391</b>	
430		0.70				<b>431</b>	
470		0.75				<b>471</b>	
510		0.75				<b>511</b>	
560		0.80				<b>561</b>	
620		0.80				<b>621</b>	
680	0.80	<b>681</b>					
750	0.70	<b>751</b>					
820	0.70	<b>821</b>					
910	0.70	<b>911</b>					
1000	6.0 x 14.0 x 14.5	0.75	<b>24...</b> (1750)	<b>22...</b> (1000)	-	<b>102</b>	
1100		0.85				<b>112</b>	
1200		0.90				<b>122</b>	
1300		0.85				<b>132</b>	
1500		0.90				<b>152</b>	
<b>C (pF)</b>	<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 15.0 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
1600	5.5 x 14.5 (16.0) x 18.5	1.1	<b>24...</b> 2000)	<b>22...</b> (1100)	<b>26...</b> (900)	<b>28...</b> (500)	<b>162</b>
1800							<b>182</b>
2000							<b>202</b>
2200							<b>222</b>
2400							<b>242</b>
2700	6.0 x 15.0 (16.5) x 18.5	1.2	<b>24...</b> (2000)	<b>22...</b> (1000)	<b>26...</b> (800)	<b>28...</b> (450)	<b>272</b>
3000							<b>302</b>
3300							<b>332</b>
3600							<b>362</b>
3900							<b>392</b>
4300							<b>432</b>
4700							<b>472</b>
5100							<b>512</b>
5600	<b>562</b>						

### Notes

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
- SPQ = Standard Packing Quantity





AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

U<sub>RDC</sub> = 1000 V; U<sub>RAC</sub> = 400 V; U<sub>pp</sub> = 1100 V (kinked); C-tol. = ± 5 %

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING				C VALUE  ..YYY
			LOOSE IN BOX	REEL			
			Leads 5 mm ± 1.0 mm	Original pitch	Pitch = 7.5 mm (bent back)		
				Ø 500 mm	Ø 500 mm	Ø 356 mm	
XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)				
<b>C (pF)</b>	<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 15.0 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
6200 6800	6.0 x 15.0 (16.5) x 18.5	1.2	24... (2000)	22... (1000)	26... (800)	28... (450)	622 682
7500 8200 9100	7.0 x 16.0 (17.5) x 18.5	1.4	24... (1500)	22... (800)	26... (700)	28... (400)	752 822 912
10 000	7.5 x 16.5 (18.0) x 18.5	1.6	24... (1250)	22... (800)	26... (650)	28... (350)	103
11 000 12 000	8.0 x 17.0 (18.5) x 18.5	1.8	24... (1250)	22... (750)	26... (600)	28... (350)	113 123
13 000	8.5 x 17.5 (19.0) x 18.5	1.9	24... (1000)	22... (700)	26... (550)	28... (300)	133
15 000	9.0 x 18.5 (19.5) x 18.5	2.1	24... (1000)	22... (650)	26... (550)	28... (300)	153
<b>C (µF)</b>	<b>Pitch = 22.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 22.5 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
0.016 0.018	6.0 x 19.0 x 26.0	2.2	24... (800)				163 183
0.02 0.022	6.5 x 19.5 x 26.0	2.5	24... (750)				203 223
0.024	7.0 x 20.0 x 26.0	2.7	24...				243
0.027 0.03	7.5 x 20.5 x 26.0	3.1	24... (600)				273 303
0.033	8.0 x 21.0 x 26.0	3.4	24... (550)				333
0.036 0.039	8.5 x 21.5 x 26.0	3.7	24... (500)				363 393
0.043	9.0 x 22.0 x 26.0	4.1	24... (450)				433
<b>C (µF)</b>	<b>Pitch = 27.5 mm ± 0.5 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 27.5 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
0.047	7.0 x 20.0 x 30.0	3.1	24... (1000)				473
0.051 0.056	7.5 x 20.5 x 30.0	3.4	24... (750)				513 563
0.062	8.0 x 21.0 x 30.0	3.8	24... (650)				623
0.068	8.5 x 21.5 x 30.0	4.0	24... (550)				683
0.075	9.0 x 22.0 x 30.0	4.4	24... (550)				753
0.082	9.5 x 22.5 x 30.0	4.7	24... (500)				823
0.091	10.0 x 23.0 x 30.0	5.1	24... (500)				913
0.10	10.5 x 23.5 x 30.0	5.5	24... (450)				104
0.11	11.0 x 24.0 x 30.0	5.9	24... (400)				114
0.12	11.5 x 24.5 x 30.0	6.3	24... (400)				124
0.13	12.0 x 25.0 x 30.0	6.8	24... (350)				134
0.15	12.5 x 25.5 x 30.0	7.6	24... (350)				154

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
- SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 1000\text{ V}$ ;  $U_{RAC} = 400\text{ V}$ ;  $U_{pp} = 1100\text{ V}$  (lock lead); C-tol =  $\pm 5\%$

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING	
			LOOSE IN BOX	
			$l_t = 4.0\text{ mm} + 1.0\text{ mm} / - 0.5\text{ mm}$	
			(SPQ)	
<b>C (pF)</b>	<b>Pitch = 10.0 mm <math>\pm</math> 1.0 mm; <math>d_t = 0.60\text{ mm} \pm 0.06\text{ mm}</math></b>			
100	5.0 x 16.0 x 14.5	0.5	90373	(2000)
110			90374	
120			90375	
130			90376	
150	5.5 x 16.5 x 14.5	0.55	90377	(2000)
160		0.55	90378	
180		0.55	90379	
200		0.55	90281	
220		0.60	90382	
240		0.60	90383	
270		0.60	90384	
300		0.60	90385	
330		0.60	90386	
360		0.60	90387	
390		0.65	90388	
430		0.70	90389	
470		0.75	90391	
510		0.75	90392	
560		0.80	90393	
620		0.80	90394	
680	0.80	90395		
750	0.70	90396		
820	0.70	90397		
910	0.70	90398		
1000	6.0 x 17.0 x 14.5	0.75	90399	(1750)
1100		0.85	90401	
1200		0.90	90402	
1300		0.85	90403	
1500		0.90	90404	
<b>C (pF)</b>	<b>Pitch = 15.0 mm <math>\pm</math> 1.0 mm; <math>d_t = 0.80\text{ mm} \pm 0.08\text{ mm}</math></b>			
1600	5.5 x 17.5 x 18.5	1.1	90405	(2000)
1800			90406	
2000			90407	
2200			90408	
2400			90409	
2700	6.0 x 18.0 x 18.5	1.2	90411	(2000)
3000			90412	
3300			90413	
3600			90414	
3900			90415	
4300			90416	
4700			90417	
5100			90418	
5600			90419	
6200			90421	
6800	90422			

### Notes

<sup>(1)</sup> Net weight for short lead product only

- SPQ = Standard Packing Quantity



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING	
			LOOSE IN BOX	
			l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm	
			(SPQ)	
<b>C (pF)</b>	<b>Pitch = 15.0 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
7500	7.0 x 19.0 x 18.5	1.5	90232	(1500)
8200			90423	
9100			90424	
10 000	7.5 x 19.5 x 18.5	1.6	90425	(1400)
11 000	8.0 x 20.0 x 18.5	1.8	90426	(1250)
12 000			90427	
13000	8.5 x 20.5 x 18.5	1.9	90428	(1200)
15000	9.0 x 21.0 x 18.5	2.1	90429	(1100)
<b>C (μF)</b>	<b>Pitch = 22.5 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
0.016	6.0 x 22.0 x 26.0	2.2	90431	(750)
0.018			90432	
0.02	6.5 x 22.5 x 26.0	2.5	90433	(700)
0.022			90434	
0.024	7.0 x 23.0 x 26.0	2.7	90435	(600)
0.027	7.5 x 23.5 x 26.0	3.1	90436	(550)
0.03			90437	
0.033	8.0 x 24.0 x 26.0	3.4	90438	(500)
0.036	8.5 x 24.5 x 26.0	3.8	90439	(450)
0.039			90224	
0.043	9.0 x 25.0 x 26.0	4.1	90441	(450)
<b>C (μF)</b>	<b>Pitch = 27.5 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
0.047	7.0 x 23.0 x 30.0	3.1	90442	(800)
0.051	7.5 x 23.5 x 30.0	3.4	90443	(600)
0.056			90444	
0.062	8.0 x 24.0 x 30.0	3.8	90445	(550)
0.068	8.5 x 24.5 x 30.0	4.0	90446	(550)
0.075	9.0 x 25.0 x 30.0	4.4	90447	(450)
0.082	9.5 x 25.5 x 30.0	4.7	90448	(450)
0.091	10.0 x 26.0 x 30.0	5.1	90449	(400)
0.1	10.5 x 26.5 x 30.0	5.5	90451	(350)
0.11	11.0 x 27.0 x 30.0	5.9	90452	(350)
0.12	11.5 x 27.5 x 30.0	6.3	90453	(350)
0.13	12.0 x 28.0x 30.0	6.8	90454	(350)
0.15	12.0 x 28.5x 30.0	7.6	90455	(300)

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity

Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors  
 KP/MKP Radial Lacquered Type

**SPECIFIC REFERENCE DATA (1600 V<sub>DC</sub>)**

DESCRIPTION	VALUE	
	10 kHz	100 kHz
Tangent of loss angle at (x 10 <sup>-4</sup> ): Pitch = 10 mm, 15 mm and 7.5 mm (bent back) Pitch = 22.5 mm Pitch = 27.5 mm	≤ 6 ≤ 6 ≤ 6	≤ 10 ≤ 15 ≤ 20
Rated voltage pulse slope (dU/dt): Pitch = 10 mm Pitch = 15 mm and 7.5 mm (bent back) Pitch = 22.5 mm Pitch = 27.5 mm	21 000 V/μs 7000 V/μs 4700 V/μs	
R between leads at 500 V, 1 min	> 100 000 MΩ	
R between interconnected leads and case, 500 V, 1 min	> 100 000 MΩ	
Ionisation (AC) voltage (typical value) at 50 pC peak discharge at 10 pC peak discharge	> 550 V	
Withstanding (DC) voltage (cut off current 10 mA), rise time 1000 V/s For C ≤ 47 nF For C > 47 nF	2560 V, 1 min	
Withstanding (DC) voltage between leads and case	2840 V, 1 min	
Maximum application temperature	105 °C	

**U<sub>RDC</sub> = 1600 V; U<sub>RAC</sub> = 500 V; U<sub>pp</sub> = 1400 V (kinked); C-tol. = ± 5 %**

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING				C VALUE  ..YYY
			LOOSE IN BOX  Leads 5 mm ± 1.0 mm  XX (SPQ)	REEL			
				Original pitch Ø 500 mm XX (SPQ)	Pitch = 7.5 mm (bent back)		
					Ø 500 mm XX (SPQ)	Ø 356 mm XX (SPQ)	
<b>C (pF)</b>	<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 15.0 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
680	5.5 x 14.5 (15.0) x 18.5	0.75	34... (2000)	32... (1100)	36... (900)	38... (500)	681
750							751
820							821
910							911
1000	6.0 x 15.0 (15.5) x 18.5	0.85	34...(2000)	32... (1000)	36... (800)	38... (450)	102
1100							112
1200							122
1300							132
1500	5.5 x 14.5 (16.0) x 18.5	1.1	34... (2000)	32... (1100)	36... (900)	38... (500)	152
1600							162
1800	6.0 x 15.0 (16.5) x 18.5	1.2	34... (2000)	32... (1000)	36... (800)	38... (450)	182
2000	6.5 x 15.5 (17.0) x 18.5	1.3	34... (1500)	32... (900)	36... (750)	38... (400)	202
2200							222
2400	7.0 x 16.0 (17.5) x 18.5	1.4	34... (1500)	32... (800)	36... (700)	38... (400)	242
2700	7.5 x 16.5 (18.0) x 18.5	1.6	34... (1250)	32... (800)	36... (650)	38... (350)	272
3000							302
3300	8.0 x 17.0 (18.5) x 18.5	1.7	34... (1250)	32... (750)	36... (600)	38... (350)	332
3600	8.5 x 17.5 (19.0) x 18.5	1.8	34... (1000)	32... (700)	36... (550)	38... (300)	362
3900	9.0 x 18.5 (19.5) x 18.5	2.0	34... (1000)	32... (650)	36... (550)	38... (300)	392
4300							432

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
- SPQ = Standard Packing Quantity



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XYYYY AND PACKAGING				C VALUE  ..YYY
			LOOSE IN BOX	REEL			
				Original pitch	Pitch = 7.5 mm (bent back)		
			Leads 5 mm ± 1.0 mm	Ø 500 mm	Ø 500 mm	Ø 356 mm	
XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)				
<b>C (µF)</b>	<b>Pitch = 22.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 22.5 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
0.0047 0.0051 0.0056	6.0 x 19.0 x 26.0	2.0	34... (800)			472 512 562	
0.0062 0.0068	6.5 x 19.5 x 26.0	2.1	34... (750)			622 682	
0.0075 0.0082	7.0 x 20.0 x 26.0	2.3	34... (650)			752 822	
0.0091	7.5 x 20.5 x 26.0	2.5	34... (600)			912	
0.01	8.0 x 21.0 x 26.0	2.6	34... (550)	-	-	103	
0.011 0.012	8.5 x 21.5 x 26.0	2.9	34... (500)			113 123	
0.013	9.0 x 22.0 x 26.0	3.1	34... (450)			133	
0.015	9.5 x 22.5 x 26.0	3.5	34... (400)			153	
0.016	10.0 x 23.0 x 26.0	3.6	34... (400)			163	
0.018	10.5 x 23.5 x 26.0	4.0	34... (350)			183	
<b>C (µF)</b>	<b>Pitch = 27.5 mm ± 0.5 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 27.5 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
0.02	9.0 x 22.0 x 30.0	4.2	34... (550)			203	
0.022	9.5 x 22.5 x 30.0	4.4	34... (500)			223	
0.024	10.0 x 23.0 x 30.0	4.7	34... (500)			243	
0.027	10.5 x 23.5 x 30.0	5.2	34... (450)			273	
0.03	11.0 x 24.0 x 30.0	5.6	34... (400)			303	
0.033	11.5 x 24.5 x 30.0	6.0	34... (400)			333	
0.036	12.0 x 25.0 x 30.0	6.5	34... (350)			363	
0.039	12.5 x 25.5 x 30.0	6.9	34... (350)			393	

**Notes**

- (1) Net weight for short lead product only
- Loose in box, all lengths have same SPQ
- SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

$U_{RDC} = 1600\text{ V}$ ;  $U_{RAC} = 500\text{ V}$ ;  $U_{pp} = 1400\text{ V}$  (lock lead); C-tol. =  $\pm 5\%$

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING	
			LOOSE IN BOX	
			$l_t = 4.0\text{ mm} + 1.0\text{ mm}/- 0.5\text{ mm}$	
			(SPQ)	
<b>C (pF)</b>	<b>Pitch = 15.0 mm <math>\pm</math> 1.0 mm; <math>d_t = 0.80\text{ mm} \pm 0.08\text{ mm}</math></b>			
680	5.5 x 17.5 x 18.5	0.75	90456	(2000)
750			90457	
820			90458	
910	6.0 x 18.0 x 18.5	0.80	90459	(2000)
1000		0.85	90461	
1100		0.85	90462	
1200		0.90	90463	
1300		0.95	90464	
1500	5.5 x 17.5 x 18.5	1.1	90465	(2000)
1600			90466	
1800	6.0 x 18.0 x 18.5	1.2	90467	(2000)
2000	6.5 x 18.5 x 18.5	1.3	90468	(1750)
2200			90469	
2400	7.0 x 19.0 x 18.5	1.4	90471	(1500)
2700	7.5 x 19.5 x 18.5	1.6	90472	(1400)
3000			90473	
3300	8.0 x 20.0 x 18.5	1.9	90141	(1250)
3600	8.5 x 20.5 x 18.5	2.3	90142	(1200)
3900	9.0 x 21.5 x 18.5	2.5	90143	(1100)
4300			90144	
<b>C (<math>\mu</math>F)</b>	<b>Pitch = 22.5 mm <math>\pm</math> 1.0 mm; <math>d_t = 0.80\text{ mm} \pm 0.08\text{ mm}</math></b>			
0.0047	6.0 x 22.0 x 26.0	2.4	90145	(750)
0.0051			90146	
0.0056			90147	
0.0062	6.5 x 22.5 x 26.0	2.6	90148	(700)
0.0068			90149	
0.0075	7.0 x 23.0 x 26.0	2.8	90151	(600)
0.0082			90152	
0.0083			90202	
0.0091	7.5 x 23.5 x 26.0	2.9	90153	(550)
0.01	8.0 x 24.0 x 26.0	3.2	90154	(500)
0.011	8.5 x 24.5 x 26.0	3.4	90155	(450)
0.012			90156	
0.013	9.0 x 25.0 x 26.0	3.6	90157	(450)
0.015	9.5 x 25.5 x 26.0	4.0	90158	(400)
0.016	10.0 x 26.0 x 26.0	4.3	90159	(350)
0.018	10.5 x 26.5 x 26.0	4.7	90161	(350)
<b>C (<math>\mu</math>F)</b>	<b>Pitch = 27.5 mm <math>\pm</math> 1.0 mm; <math>d_t = 0.80\text{ mm} \pm 0.08\text{ mm}</math></b>			
0.02	9.0 x 25.0 x 30.0	4.2	90474	(450)
0.022	9.5 x 25.5 x 30.0	4.4	90475	(450)
0.024	10.0 x 26.0 x 30.0	4.7	90476	(400)
0.027	10.5 x 26.5 x 30.0	5.2	90477	(350)
0.03	11.0 x 27.0 x 30.0	5.6	90478	(350)
0.033	11.5 x 27.5 x 30.0	6.0	90479	(350)
0.036	12.0 x 28.0 x 30.0	6.5	90481	(300)
0.039	12.5 x 28.5 x 30.0	6.9	90482	(300)

### Notes

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

**SPECIFIC REFERENCE DATA (2000 V<sub>DC</sub>)**

DESCRIPTION	VALUE	
	10 kHz	100 kHz
Tangent of loss angle at ( $\times 10^{-4}$ ): Pitch = 10 mm, 15 mm and 7.5 mm (bent back)	$\leq 6$	$\leq 10$
Pitch = 22.5 mm	$\leq 6$	$\leq 10$
Pitch = 27.5 mm	$\leq 6$	$\leq 15$
Rated voltage pulse slope (dU/dt): Pitch = 10 mm	30 000 V/ $\mu$ s	
Pitch = 15 mm and 7.5 mm (bent back)	10 000 V/ $\mu$ s	
Pitch = 22.5 mm	6700 V/ $\mu$ s	
Pitch = 27.5 mm		
R between leads at 500 V, 1 min	> 100 000 M $\Omega$	
R between interconnected leads and case, 500 V, 1 min	> 100 000 M $\Omega$	
Ionisation (AC) voltage (typical value) at 50 pC peak discharge at 20 pC peak discharge	> 600 V	
Withstanding (DC) voltage (cut off current 10 mA), rise time 1000 V/s For C $\leq$ 47 nF For C > 47 nF	3200 V, 1 min	
Withstanding (DC) voltage between leads and case	2840 V, 1 min	
Maximum application temperature	105 °C	

**U<sub>RDC</sub> = 2000 V; U<sub>RAC</sub> = 600 V; U<sub>pp</sub> = 1700 (kinked); C-tol. =  $\pm$  5 %**

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING				
			LOOSE IN BOX	REEL		C VALUE	
			Leads 5 mm $\pm$ 1.0 mm	Original pitch	Pitch = 7.5 mm (bent back)		..YYY
				$\varnothing$ 500 mm	$\varnothing$ 500 mm	$\varnothing$ 356 mm	
XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)				
<b>C (pF)</b>	<b>Pitch = 15.0 mm <math>\pm</math> 0.4 mm; d<sub>t</sub> = 0.80 mm <math>\pm</math> 0.08 mm</b>		<b>Pitch = 15.0 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
100	5.5 x 14.5 (15.0) x 18.5	0.75	44... (2000)	42... (1100)	46... (900)	48... (500)	101
110		0.75					111
120		0.75					121
130		0.75					131
150		0.75					151
160		0.75					161
180		0.75					181
200		0.75					201
220		0.75					221
240		0.75					241
270		0.75					271
300		0.75					301
330		0.75					331
360		0.75					361
390		0.75					391
430		0.75					431
470		0.80					471
510		0.80					511
560		0.80					561

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING				
			LOOSE IN BOX	REEL			C VALUE
			Leads 5 mm ± 1.0 mm	Original pitch	Pitch = 7.5 mm (bent back)		..YYY
				Ø 500 mm	Ø 500 mm	Ø 356 mm	
			XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)	
<b>C (pF)</b>	<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 15.0 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
620	6.0 x 15.0 (15.5) x 18.5	0.85	44... (2000)	42... (1000)	46... (800)	48... (450)	621
680		0.85					681
750		0.90					751
820	6.5 x 15.5 (16.0) x 18.5	0.95	44... (1500)	42... (900)	46... (750)	48... (400)	821
910	5.5 x 14.5 (16.0) x 18.5	1.1	44... (2000)	42... (420)	46... (900)	48... (500)	911
1000	6.0 x 15.0 (16.5) x 18.5	1.2	44... (2000)	42... (1000)	46... (800)	48... (450)	102
1100							112
1200							122
1300	6.5 x 15.5 (17.0) x 18.5	1.3	44... (1500)	42... (900)	46... (750)	48... (400)	132
1500	7.0 x 16.0 (17.5) x 18.5	1.4	44... (1500)	42... (800)	46... (700)	48... (400)	152
1600	7.5 x 16.5 (18.0) x 18.5	1.5	44... (1250)	42... (800)	46... (650)	48... (350)	162
1800							182
2000	8.0 x 17.0 (18.5) x 18.5	1.6	44... (1250)	42... (750)	46... (600)	48... (350)	202
2200	8.5 x 17.5 (19.0) x 18.5	1.7	44... (1000)	42... (700)	46... (550)	48... (300)	222
2400	9.0 x 18.0 (19.5) x 18.5	1.8	44... (1000)	42... (650)	46... (550)	48... (300)	242
2700	9.5 x 18.5 (20.0) x 18.5	2.0	44... (900)	42... (600)	46... (500)	48... (300)	272
<b>C (µF)</b>	<b>Pitch = 22.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 22.5 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
0.003	6.0 x 19.0 x 26.0	2.1	44... (800)				302
0.0033							332
0.0036							362
0.0039							392
0.0043	6.5 x 19.5 x 26.0	2.3	44... (750)				432
0.0047							472
0.0051	7.0 x 20.0 x 26.0	2.6	44... (650)				512
0.0056							562
0.0062	7.5 x 20.5 x 26.0	2.8	44... (600)				622
0.0068	8.0 x 21.0 x 26.0	3.0	44... (550)				682
0.0075							752
0.0082	8.5 x 21.5 x 26.0	3.3	44... (500)				822
0.0091	9.0 x 22.0 x 26.0	3.6	44... (450)				912
0.01	9.5 x 22.5 x 26.0	3.8	44... (400)				103

### Notes

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity





AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING				
			LOOSE IN BOX	REEL			C VALUE
			Leads 5 mm ± 1.0 mm	Original pitch	Pitch = 7.5 mm (bent back)		..YYY
				Ø 500 mm	Ø 500 mm	Ø 356 mm	
XX (SPQ)	XX (SPQ)	XX (SPQ)	XX (SPQ)				
<b>C (µF)</b>	<b>Pitch = 27.5 mm ± 0.5 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>		<b>Pitch = 27.5 mm</b>	<b>Pitch = 7.5 mm (bent back)</b>			
0.011	9.0 x 22.0 x 30.0	3.8	44... (550)			113	
0.012	9.5 x 22.5 x 30.0	4.1	44... (500)			123	
0.013	10.0 x 23.0 x 30.0	4.4	44... (500)			133	
0.015	10.5 x 23.5 x 30.0	4.9	44... (450)			153	
0.016	11.0 x 24.0 x 30.0	5.1	44... (400)			163	
0.018	11.5 x 24.5 x 30.0	5.6	44... (400)			183	
0.02	12.5 x 25.5 x 30.0	6.1	44... (350)			203	
0.022	13.0 x 26.0 x 30.0	6.5	44... (300)			223	

**Notes**

- <sup>(1)</sup> Net weight for short lead product only
- Loose in box, all lengths have same SPQ
- SPQ = Standard Packing Quantity

**U<sub>RDC</sub> = 2000 V; U<sub>RAC</sub> = 600 V; U<sub>pp</sub> = 1700 V (lock lead)**

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING	
			LOOSE IN BOX	
			l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm	
			(SPQ)	
<b>C (pF)</b>	<b>Pitch = 15.0 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
100	5.5 x 17.5 x 18.5	0.75	90483	(2000)
110		0.75	90484	
120		0.75	90485	
130		0.75	90486	
150		0.75	90487	
160		0.75	90488	
180		0.75	90489	
200		0.75	90491	
220		0.75	90276	
240		0.75	90492	
270		0.75	90493	
300		0.75	90494	
330		0.75	90495	
360		0.75	90496	
390		0.75	90188	
430		0.75	90497	
470		0.80	90498	
510		0.80	90499	
560	0.80	90501		

**Note**

- SPQ = Standard Packing Quantity

# KP/MKP 375



## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type

C	DIMENSIONS w x h (h') x l (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 375 XXYYY AND PACKAGING	
			LOOSE IN BOX	
			l <sub>t</sub> = 4.0 mm + 1.0 mm/- 0.5 mm	
			(SPQ)	
<b>C (pF)</b>	<b>Pitch = 15.0 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
620		0.85	<b>90502</b>	
680	6.0 x 18.0 x 18.5	0.85	<b>90229</b>	(2000)
750		0.90	<b>90503</b>	
820	6.5 x 18.5 x 18.5	0.95	<b>90504</b>	(1750)
910	5.5 x 17.5 x 18.5	1.1	<b>90505</b>	(2000)
1000			<b>90225</b>	
1100	6.0 x 18.0 x 18.5	1.3	<b>90506</b>	(2000)
1200			<b>90226</b>	
1300	6.5 x 18.5 x 18.5	1.3	<b>90507</b>	(1750)
1500	7.0 x 19.0 x 18.5	1.5	<b>90266</b>	(1500)
1600			<b>90508</b>	
1800	7.5 x 19.5 x 18.5	1.7	<b>90237</b>	(1400)
2000	8.0 x 20.0 x 18.5	1.7	<b>90509</b>	(1250)
2200	8.5 x 20.5 x 18.5	2.3	<b>90227</b>	(1200)
2400	9.0 x 21.0 x 18.5	1.8	<b>90511</b>	(1100)
2700	9.5 x 21.5 x 18.5	2.7	<b>90228</b>	(1000)
<b>C (μF)</b>	<b>Pitch = 22.5 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
0.003			<b>90512</b>	
0.0033	6.0 x 22.0 x 26.0	2.2	<b>90162</b>	(750)
0.0036			<b>90163</b>	
0.0039			<b>90164</b>	
0.0043	6.5 x 22.5 x 26.0	2.4	<b>90165</b>	(700)
0.0047			<b>90166</b>	
0.0051	7.0 x 23.0 x 26.0	2.6	<b>90167</b>	(600)
0.0056			<b>90168</b>	
0.0062	7.5 x 23.5 x 26.0	2.8	<b>90169</b>	(550)
0.0068	8.0 x 24.0 x 26.0	3.0	<b>90171</b>	(500)
0.0075			<b>90172</b>	
0.0082	8.5 x 24.5 x 26.0	3.2	<b>90173</b>	(450)
0.0091	9.0 x 25.0 x 26.0	3.5	<b>90174</b>	(450)
0.01	9.5 x 25.5 x 26.0	3.8	<b>90175</b>	(400)
<b>C (μF)</b>	<b>Pitch = 27.5 mm ± 1.0 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>			
0.011	9.0 x 25.0 x 30.0	4.4	<b>90176</b>	(450)
0.012	9.5 x 25.5 x 30.0	4.6	<b>90177</b>	(450)
0.013	10.0 x 26.0 x 30.0	5.0	<b>90178</b>	(400)
0.015	10.5 x 26.5 x 30.0	5.4	<b>90179</b>	(350)
0.016	11.0 x 27.0 x 30.0	5.8	<b>90181</b>	(350)
0.018	11.5 x 27.5 x 30.0	6.2	<b>90182</b>	(350)
0.02	12.5 x 28.5 x 30.0	6.1	<b>90513</b>	(300)
0.022	13.0 x 29.0 x 30.0	6.5	<b>90514</b>	(250)

### Notes

- <sup>(1)</sup> Net weight for short lead product only
- SPQ = Standard Packing Quantity

**MOUNTING****Normal Use**

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to "Packaging information" [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139) or end of catalog

**Specific Method of Mounting to Withstand Vibration and Shock**

- For pitches  $\leq 15$  mm capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

**Storage Temperature**

- Storage temperature:  $T_{stg} = -25\text{ }^{\circ}\text{C}$  to  $+40\text{ }^{\circ}\text{C}$  with RH maximum 80 % without condensation


**Ratings and Characteristics Reference Conditions**

Unless otherwise specified, all electrical values apply to an ambient temperature of  $23\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$ , an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of  $50\% \pm 2\%$ .


For reference testing, a conditioning period shall be applied over  $96\text{ h} \pm 4\text{ h}$  by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.

### CHARACTERISTICS


Capacitance as a function of ambient temperature  
(typical curve)




Impedance as a function of frequency  
(typical curve)



Max. DC voltage as a function of temperature




Max. allowed component temperature rise  
as a function of ambient temperature






## Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors KP/MKP Radial Lacquered Type


Max. RMS voltage (sinewave) as a function of frequency



Max. RMS voltage (sinewave) as a function of frequency




Tangent of loss angle (typical curve)




1. KP/MPK 10.0 mm and 15 mm pitch all versions  
22.5 mm pitch, 1000 V, 1600 V, 2000 V and 2500 V versions
2. KP/MPK 22.5 mm pitch, 630 V versions  
27.5 mm pitch, 1000 V, 1600 V and 2000 V versions
3. KP/MPK 27.5 mm pitch, 630 V versions

Maximum curves



1. KP/MPK 10.0 mm and 15 mm pitch all versions  
22.5 mm pitch, 1000 V, 1600 V, 2000 V and 2500 V versions
2. KP/MPK 22.5 mm pitch, 630 V versions  
27.5 mm pitch, 1000 V, 1600 V and 2000 V versions
3. KP/MPK 27.5 mm pitch, 630 V versions

Insulation resistance as a function of ambient temperature



**HEAT CONDUCTIVITY (G) AS A FUNCTION OF (ORIGINAL) PITCH AND CAPACITOR BODY THICKNESS IN mW/°C**

W <sub>max.</sub> (mm)	HEAT CONDUCTIVITY (mW/°C)			
	PITCH 10 mm	PITCH 15 mm	PITCH 22.5 mm	PITCH 27.5 mm
4.0	4.0	5.0	-	-
4.5	4.5	6.0	-	-
5.0	5.0	6.0	12.0	13.0
5.5	6.0	6.5	13.0	15.0
6.0	6.0	6.5	13.0	15.0
6.5	6.5	8.0	15.0	17.0
7.0	-	8.0	15.0	17.0
7.5	-	9.0	17.0	18.0
8.0	-	9.0	17.0	20.0
8.5	-	11.0	18.0	20.0
9.0	-	11.0	18.0	22.0
9.5	-	12.0	20.0	22.0
10.0	-	12.0	20.0	23.0
10.5	-	-	22.0	25.0
11.0	-	-	22.0	25.0
11.5	-	-	23.0	27.0
12.0	-	-	-	27.0
12.5	-	-	-	30.0
13.0	-	-	-	30.0
13.5	-	-	-	30.0
14.0	-	-	-	30.0
14.5	-	-	-	33.0
15.0	-	-	-	33.0
15.5	-	-	-	37.0
16.0	-	-	-	37.0

**POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE**

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free ambient temperature.

The power dissipation can be calculated according Type detail specification "HQN-384-01/101: Technical Information Film Capacitors


The component temperature rise ( $\Delta T$ ) can be measured (see section "Measuring the component temperature" for more details) or calculated by

$$\Delta T = P/G:$$

- $\Delta T$  = Component temperature rise (°C)
- P = Power dissipation of the component (mW)
- G = Heat conductivity of the component (mW/°C)

## MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:



The temperature is measured in unloaded ( $T_{amb}$ ) and maximum loaded condition ( $T_C$ ).

The temperature rise is given by  $\Delta T = T_C - T_{amb}$ .

To avoid radiation or convection, the capacitor should be tested in a wind-free box.

## APPLICATION NOTE AND LIMITING CONDITIONS

To select the capacitor for a certain application, the following conditions must be checked:

1. The peak voltage ( $U_P$ ) shall not be greater than the rated DC voltage ( $U_{RDC}$ )
2. The peak-to-peak voltage ( $U_{P-P}$ ) shall not be greater than the maximum ( $U_{P-P}$ ) to avoid the ionisation inception level
3. The voltage pulse slope ( $dU/dt$ ) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by  $U_{Rdc}$  and divided by the applied voltage.

For all other pulses following equation must be fulfilled:

$$2 \times \int_0^T \left( \frac{dU}{dt} \right)^2 \times dt < U_{Rdc} \times \left( \frac{dU}{dt} \right)_{rated}$$

T is the pulse duration.

4. The maximum component surface temperature rise must be lower than the limits

## EXAMPLE

$C = 10 \text{ nF}$  1600 V, KP/MPK

This is a signal as in the drawing below


$U_{P-P} = 1200 \text{ V}$ ;  $U_P = 1100 \text{ V}$ ;  $T_1 = 12 \text{ } \mu\text{s}$ ;  $T_2 = 64 \text{ } \mu\text{s}$

The ambient temperature is  $50 \text{ } ^\circ\text{C}$

Checking conditions:

1. The peak voltage  $U_P = 1100 \text{ V}$  is lower than  $1600 \text{ V}_{DC}$
2. The peak-to-peak voltage  $1200 \text{ V}$  is lower than  $2\sqrt{2} \times 550 \text{ Vac} = 1414 \text{ } U_{P-P}$
3. The voltage pulse slope ( $dU/dt$ ) =  $320 \text{ V}$  is much lower than  $7000 \text{ V}/\mu\text{s}$
4. The dissipated power is  $170 \text{ mW}$  as calculated with fourier terms

This gives a temperature rise of  $170 \text{ mW}/(17 \text{ mW}/^\circ\text{C}) = 10 \text{ } ^\circ\text{C}$  which is allowed acc. fig. "max. allowed temperature rise as a function of ambient temperature" for an ambient temperature of  $50 \text{ } ^\circ\text{C}$







AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

**INSPECTION REQUIREMENTS**

**General Notes:**

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-17 and Specific Reference Data”.

**Group C Inspection Requirements**

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b>		
4.1 Dimensions (detail)		As specified in chapters “General Data” of this specification
4.3.1 Initial measurements	Capacitance Tangent of loss angle at 100 kHz	
4.3 Robustness of terminations	Tensile: Load 10 N; 10 s Bending: Load 5 N; 4 x 90°	No visible damage
4.4 Resistance to soldering heat	Method: 1A Solder bath: 280 °C ± 5 °C Duration: 10 s	
4.14 Component solvent resistance	Isopropylalcohol at room temperature Method: 2 Immersion time: 5 min ± 0.5 min Recovery time: Min. 1 h, max. 2 h	
4.4.2 Final measurements	Visual examination  Capacitance  Tangent of loss angle	No visible damage Legible marking   ΔC/C  ≤ 1 % + 5 pF of the value measured initially  Increase of tan δ: ≤ 0.0005 Compared to values measured in 4.3.1
<b>SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1</b>		
4.6.1 Initial measurements	Capacitance Tangent of loss angle at 100 kHz	
4.15 Solvent resistance of the marking	Isopropylalcohol at room temperature Method: 1 Rubbing material: cotton wool Immersion time: 5 min ± 0.5 min	No visible damage Legible marking
4.6 Rapid change of temperature	θA = - 55 °C θB = + 105 °C 5 cycles Duration t = 30 min	
4.7 Vibration	Visual examination Mounting: See section “Mounting” of this specification Procedure B4 Frequency range: 10 Hz to 55 Hz Amplitude: 0.75 mm or Acceleration 98 m/s <sup>2</sup> (whichever is less severe) Total duration 6 h	No visible damage

Vishay BCcomponents AC and Pulse Metallized Polypropylene Film Capacitors  
 KP/MKP Radial Lacquered Type

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
4.7.2 Final inspection  4.9 Shock  4.9.3 Final measurements	Visual examination  Mounting: See section "Mounting" of this specification Pulse shape: Half sine Acceleration: 490 m/s <sup>2</sup> Duration of pulse: 11 ms Visual examination  Capacitance  Tangent of loss angle  Insulation resistance	No visible damage  No visible damage  For C > 0.027μF:  ΔC/C  ≤ 2 % or for C ≤ 0.027μF:  ΔC/C  ≤ 3 % + 5 pF of the value measured in 4.6.1. Increase of tan δ: ≤ 0.0005 Compared to values measured in 4.6.1 As specified in chapter "General data" of this specification
<b>SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B</b>		
4.10 Climatic sequence  4.10.2 Dry heat  4.10.3 Damp heat cyclic Test Db, first cycle 4.10.4 Cold  4.10.6 Damp heat cyclic Test Db, remaining cycles 4.10.6.2 Final measurements	Temperature: + 105 °C Duration: 16 h  Temperature: - 55 °C Duration: 2 h  Voltage proof = U <sub>RDC</sub> for 1 min within 15 min after removal from testchamber Visual examination  Capacitance  Tangent of loss angle  Insulation resistance	No breakdown of flash-over  No visible damage Legible marking  ΔC/C  ≤ 3 % of the value measured in 4.4.2 or 4.9.3 Increase of tan δ: ≤ 0.001 Compared to values measured in 4.3.1 or 4.6.1 ≥ 50 % of values specified in chapters "General data" of this specification
<b>SUB-GROUP C2</b>		
4.11 Damp heat steady state  4.11.1 Initial measurements  4.11.3 Final measurements	56 days, 40 °C, 90 % to 95 % RH  Capacitance Tangent of loss angle at 1 kHz Voltage proof = U <sub>RDC</sub> for 1 min within 15 min after removal from testchamber Visual examination  Capacitance  Tangent of loss angle  Insulation resistance	No breakdown of flash-over  No visible damage Legible marking  ΔC/C  ≤ 1 % + 5 pF of the value measured in 4.11.1. Increase of tan δ ≤ 0.0005 Compared to values measured in 4.11.1 ≥ 50 % of values specified in section "Insulation Resistance" of this specification



AC and Pulse Metallized Polypropylene Film Capacitors Vishay BCcomponents  
 KP/MKP Radial Lacquered Type

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB GROUP C3</b>		
4.12.1 Endurance	Duration: 2000 h Temperature: 85 °C Voltage: 1.25 x max. $U_{RDC} V_{rms}$ , 50 Hz Duration: 2000 h Temperature: 105 °C	
4.12.1.1 Initial measurements  4.12.1.3 Final measurements	Voltage: 0.875 x max. $U_{RDC} V_{rms}$ , 50 Hz Capacitance Tangent of loss angle at 100 kHz  Visual examination  Capacitance  Tangent of loss angle  Insulation resistance	No visible damage Legible marking Temperature: 85 °C  For $C > 0.056 \mu F$ : $ \Delta C/C  \leq 2\% + 5 \text{ pF}$ or for $C > 0.056 \mu F$ : $ \Delta C/C  \leq 3\% + 5 \text{ pF}$ of the value measured in 4.12.1.1 Temperature: 105 °C $ \Delta C/C  \leq 5\% + 5 \text{ pF}$ Increase of $\tan \delta$ : $\leq 0.001$ Compared to values measured in 4.12.1 $\geq 50\%$ of values specified in chapters "General data" of this specification
<b>SUB-GROUP C4</b>		
4.2.6 Temperature characteristics	Capacitance  Insulation resistance	As specified in section "Capacitance" of this specification As specified in chapters "General data" of this specification



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**