Ultra High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#: ATS-52325G-C1-R0

Description: maxiFLOW™ Heat Sink, T412, BLUE-ANODIZED

Heat Sink Type: maxiFLOW
Heat Sink Attachment: THERMAL TAPE
Equivalent Part Number: ATS-52325G-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- · Comes pre-assembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	3.51 °C/W	2.80 °C/W	2.42 °C/W	2.17 °C/W	1.98 °C/W	1.84 °C/W	1.73 °C/W
	Ducted Flow	2.76	n/a	n/a	n/a	n/a	n/a	n/a

Product Detail





