

REVISION BJ

LEAD STYLE	PIN A	PIN B	"C"
-01-SH	ASP-70937-02-S-X	N/A	.126 [3.20]
-01-DH	T-1S13-09-X-2	T-1S13-09-X-2	.126 [3.20]
-01-MT	T-1S13-09-X-2	T-1S13-09-X-2	.126 [3.20]
-02-MT	T-1S13-09-X-2	T-1S13-09-X-2	.175 [4.45]
-02-SH	ASP-70937-01-S-X	N/A	.175 [4.45]
-02-DH	T-1S13-09-X-2	T-1S13-09-X-2	.175 [4.45]

- NOTES:
1. PUSH OUT FORCE SHALL BE 2 LB. MIN.
 2. Ⓢ REPRESENTS A CRITICAL DIMENSION.
 3. ALL DIMENSIONS IN BRACKETS [] TO BE IN MILLIMETERS.
 4. NOTE 4 DELETED.
 5. NOTE 5 DELETED.
 6. NOTE 6 DELETED.
 7. FOR NON -LC & -A, USE 2TS-XX-D.
 8. COPLANARITY TO INCLUDE INSULATOR.
 9. .002 MAX BURR ALLOWED.
 10. .015 MAX OPT CUT FLASH ALLOWED. (NO FLASH TO BE ON BOTTOM OF BODY)
 11. -TT OPTION: PIN B TO BE FLUSH TO $\pm .003$ A LINE MADE BY THE BODY.
 12. -HD OPTION: PIN A TO BE FLUSH TO $\pm .003$ ABOVE A LINE MADE BY THE BODY.
 13. -SH OPTION: PIN A TO BE FLUSH TO $\pm .003$ ABOVE A LINE MADE BY THE BODY.
 14. -SH OPTION: PIN A TO BE FLUSH TO $\pm .003$ A LINE MADE BY THE BODY.

UNLESS OTHERWISE NOTED		TOLERANCES ARE:	TITLE:	DWG NO:
DIMENSIONS ARE IN INCHES			2mm HORIZONTAL TERMINAL SURFACE MOUNT STRIP ASSEM	MMT-1XX-XX-X-XX-XX-XX-Y-XX
ONE PLACE DECIMALS: $\pm .1$	THREE PLACE DECIMALS: $\pm .005$	ANGLES $\pm 5^\circ$		SHEET 1 of 2
TWO PLACE DECIMALS: $\pm .01$	FOUR PLACE DECIMALS: $\pm .0020$			

MMT-1XX-XX-X-XX-XX-XX-X-XX

NO. OF POSITIONS PER ROW

(02 THRU -50, -DH AND -MT)
(02 THRU -36, -SH)

LEAD STYL
84 188

-01: .126 [3.20] POST
-02: .175 [4.45] POST
(SEE TABLE 2)

PLATING SPECIFICATION

- T: TIN (SPECIFY -T IN TERMINAL SUFFIX -X)
- S: SELECTIVE (SPECIFY -S IN TERMINAL SUFFIX -X)
- L: LIGHT SELECTIVE (SPECIFY -L IN TERMINAL SUFFIX -X)
- F: GOLD FLASH SELECTIVE (SPECIFY -F IN TERMINAL SUFFIX -XX)
- P: GOLD/PdNi SELECTIVE (SPECIFY -P IN TERMINAL SUFFIX -XX)

ROW OPTION

- SH: SINGLE (2TS-XX-SH-X)
- DH: DOUBLE (2TS-XX-DH-XX-XX) (SEE NOTE 7)
FOR 2 POSITION WITH -A OPTION, USE ASP-80676-01-S.
- MT: MIXED TECHNOLOGY (2TS-XX-DH-XX-XX)
(NOT AVAILABLE WITH -LC, OR -A OPTIONS)

(SEE TABLE 2, ON SHT. 1)

NOTE:
TAIL DIMENSION IS REF FOR -SH OPTIONS.
DO NOT SHEAR. THE TAIL, BEFORE SHEAR,
IS .118 [3.00] (-01-SH) AND .123 [3.12].
BEING A SINGLE ROW OPTION, THE TAIL CAN
BE LONG. FOOT PRINT ACCEPTS.

'c'

⌋ (SEE TABLE 2, ON SHT. 1)

A horizontal beam is shown with a vertical downward arrow (point load) labeled '2.01' and a vertical upward arrow (reaction) labeled '0.79'.

[illegible][illegible]

TABLE 1

POS.	"E"
ODD	.150 [.572]
EVEN	.111 [2.82]

EXISPROD\ASSEMBLY\2MM
UNITAS-H

EXISPRO
santec

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
PHONE (812) 944-6733 P.O. BOX 1147
CODE 55322

MADE BY: G.REIDINGER 6-22-92	MMT-1XX-XX-X-XX-XX-XX-X-X SHEET 1 OF
------------------------------	---

PROBATIONARY NAME

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAWTEC INC. AND SHALL NOT BE
REPRODUCED OR TRANSFERRED TO
OTHER DOCUMENTS OR DISCLOSED TO
OTHERS OR USED FOR ANY PURPOSE
OTHER THAN THAT FOR WHICH IT WAS
OBTAINED WITHOUT THE APPROVED.

-LC: LOCKING CLIP

-A: ALIGNMENT PIN

-P: PICK & PLACE PAD OPTION

-MT: MIXED TECHNOLOGY

DIFFERENT AS SHOWN, OTHERWISE SAME AS ABOVE