# High Performance ASIC Cooling Solutions w/Thermal Tape Attachment





ATS Part#:

#### ATS-56003-C1-R0

Description:

maxiFLOW™ Heat Sink, T412, BLACK-ANODIZED

Heat Sink Type:maxiFLOWHeat Sink Attachment:THERMAL TAPEEquivalent Part Number:ATS-56003-C3-R0

\*Image above is for illustration purpose only.

### **Features & Benefits**

- maxiFLOW<sup>™</sup> design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Designed specifically for ASIC package and their unique cooling requirements
- · Comes pre-assembled with high performance thermal interface material

## **Thermal Performance**

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	12.00 °C/W	10.00 °C/W	7.80 °C/W	6.90 °C/W	6.00 °C/W	5.70 °C/W	5.10 °C/W
	Ducted Flow	9.00	n/a	n/a	n/a	n/a	n/a	n/a

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
	15.0 mm	15.0 mm	9.0 mm	18.0 mm	T412	BLACK-ANODIZED
Image above is for illustration purpose only.	<ul> <li>Dimensio</li> <li>ATS-5600</li> <li>(Saint Go</li> <li>Thermal papplicatio</li> <li>ATS resepret/performant</li> <li>ATS certi</li> </ul>	n <b>C</b> is the heat sink 03-C3-R0 is the exa bain C675). performance data ar n. rves the right to upd nce. fies that this heat sir	eat sink length and theight from the botto of heat sink assemb e provided for refere late or change its pro- nk assembly is RoHS ustom options availa	om of the base to the ly with an equivalent ence only. Actual per oducts without notice S-6 and REACH cor	t thermal	interface material e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

