



## Shorting Dust Cap for SMA Female

## **TECHNICAL DATA SHEET**

**PE6007** 

## **Shorting Dust Cap for SMA Female**

Configuration

Connector SMA Female Shorting
Connector Specification MIL-C-39012

Chain Option No Chain

**Mechanical Specifications** 

Size

Length, in [mm] 0.53 [13.46] Width, in [mm] 0.25 [6]

Connector

Type SMA Female Shorting
Contact Material and Plating Beryllium Copper, Gold
Contact Plating Specification 3μ-5μ in. minimum
Body Material and Plating Brass, Nickel
Body Plating Specification 70μ in. minimum

Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

**Plotted and Other Data** 

**RoHS Compliant** 

Notes: Values at 25 °C, sea level

Shorting Dust Cap for SMA Female from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Shorting Dust Cap for SMA Female PE6007

URL: http://www.pasternack.com/50-ohm-sma-female-short-cap-pe6007-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



## PE6007 CAD Drawing

Shorting Dust Cap for SMA Female

