



## 75 Ohm SMC Plug Right Angle Connector Clamp/ Solder Attachment For RG180, RG195

### TECHNICAL DATA SHEET

**PE4267**

#### 75 Ohm SMC Plug Right Angle Connector Clamp/Solder Attachment For RG180, RG195

##### Configuration

|                                          |              |
|------------------------------------------|--------------|
| Connector                                | SMC Plug     |
| Connector Interface Type                 | RG180, RG195 |
| Cable Attachment Method (Shield/Contact) | Clamp/Solder |
| Body Style                               | Right Angle  |

##### Electrical Specifications

|                 |    |
|-----------------|----|
| Impedance, Ohms | 75 |
|-----------------|----|

##### Mechanical Specifications

###### Size

|                     |               |
|---------------------|---------------|
| Length, in [mm]     | 0.725 [18.42] |
| Width/Dia., in [mm] | 0.345 [8.76]  |
| Height, in [mm]     | 0.685 [17.4]  |
| Weight, lbs [g]     | 0.027 [12.25] |

###### Connector

|                                   |               |
|-----------------------------------|---------------|
| Type                              | SMC Plug      |
| Contact Material and Plating      | Gold          |
| Coupling Nut Material and Plating | Brass, Nickel |
| Hex Size, in.                     | 11/32         |
| Torque, in-lbs [Nm]               | 5 [0.57]      |
| Body Material and Plating         | Brass, Nickel |
| Dielectric Type                   | PTFE          |

##### Compliance Certifications (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

##### Plotted and Other Data

|        |                            |
|--------|----------------------------|
| Notes: | Values at 25 °C, sea level |
|--------|----------------------------|



75 Ohm SMC Plug Right Angle Connector Clamp/Solder Attachment For RG180, RG195 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm SMC Plug Right Angle Connector Clamp/Solder Attachment For RG180, RG195 PE4267](http://www.pasternack.com/smc-plug-standard-rg180-rg195-connector-pe4267-p.aspx)

URL: <http://www.pasternack.com/smc-plug-standard-rg180-rg195-connector-pe4267-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.






### STRIPPING DIMENSIONS

### ASSEMBLY PROCEDURES

1. SLIDE CLAMP NUT (1) OVER CABLE AS SHOWN IN A. SLIDE COMPRESSION WASHER (2) OVER BRAID & SEAT AGAINST JACKET. FLAIR BRAID OVER COMPRESSION WASHER (2).
2. SLIDE BRAID CLAMP (3) OVER DIELECTRIC & UNDER BRAID. PUSH INTO WASHER UNTIL IT STOPS. STRIP CABLE AS SHOWN IN B. TRIM EXCESS BRAID FLUSH WITH SURFACE OF COMPRESSION WASHER (2). INSERT CABLE ASSEMBLY INTO BODY & TIGHTEN. SOLDER CENTER CONDUCTOR IN PLACE.
3. INSERT PTFE (4) INTO CONNECTOR. PRESS DOWN CAP.



DWG TITLE

PE4267

NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].  
4. FITS MIL-C-17 AND EQUIVALENT CABLES.