

# ROITHNER LASERTECHNIK

A-1040 WIEN, FLEISCHMANNGASSE 9

TEL: +43 -1- 586 52 43 FAX: +43 -1- 586 41 43

e-mail: office@roithner-laser.com http://www.roithner-laser.com

## RLT80805MG TECHNICAL DATA



### Infrared Laserdiode

Structure: **GaAlAs double heterostructure**

Lasing wavelength: **808 nm typ.**

Max. optical power: **5 mW**


Package: **5.6 mm**

**NOTE!**


LASERDIODE  
MUST BE COOLED!



### PIN CONNECTION:



- 1) Laser diode cathode
- 2) Laser diode anode and photodiode cathode
- 3) Photodiode anode



### Maximum Ratings (Tc=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Optical Output Power	P <sub>o</sub>	5	mW
LD Reverse Voltage	V <sub>R(LD)</sub>	2	V
PD Reverse Voltage	V <sub>R(PD)</sub>	30	V
Operating Temperature	T <sub>C</sub>	-10 .. +45	°C
Storage Temperature	T <sub>STG</sub>	-40 .. +85	°C

### Optical-Electrical Characteristics (Tc = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Optical Output Power	P <sub>o</sub>	kink free			5	mW
Threshold Current	I <sub>th</sub>		20	25	40	mA
Operation Current	I <sub>op</sub>	P <sub>o</sub> = 5 mW		40	50	mA
Operation Voltage	V <sub>op</sub>	P <sub>o</sub> = 5 mW			2.5	V
Lasing Wavelength	λ <sub>p</sub>	P <sub>o</sub> = 5 mW	790	808	810	nm
Beam Divergence	θ <sub>∥</sub>	P <sub>o</sub> = 5 mW	5	8	11	°
Beam Divergence	θ <sub>⊥</sub>	P <sub>o</sub> = 5 mW	25	31	37	°
Astigmatism	A <sub>s</sub>	P <sub>o</sub> = 5 mW, NA=0.4		5		μm
Monitor Current	I <sub>m</sub>	P <sub>o</sub> = 5mW, V <sub>r</sub> =5V		10		μA