


AC POWER CORDS

NORTH AMERICA, JAPAN



STANDARD LENGTH: 6 FT

Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			



Hospital Grade Cord

Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
UL SP	ZHG1	125V 10A	18	43/34	SVT	6.3	60°C, 75°C or 105°C
	ZHG2	125V 10A	18	43/34	SJT	7.8	
	ZHG3	125V 13A	16	68/34	SJT	8.5	
	ZHG4	125V 15A	14	41/30	SJT	9.3	




Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
UL SP	ZV03	125V 10A	18	41/0.16	SVT	6.4	60°C, 75°C or 105°C
	ZJ03	125V 10A	18	41/0.16	SJT	8.3	60°C, 75°C or 105°C



Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
UL SP	ZV05	125V 10A	18	41/0.16	SVT	6.4	60°C, 75°C or 105°C
	ZJ05	125V 10A	18	41/0.16	SJT	8.3	60°C, 75°C or 105°C




Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
			ZV01	125V 10A			
UL SP	ZJ01	125V 10A	18	41/0.16	SJT	8.3	60°C, 75°C or 105°C
	ZP01	125V 10A	1.25mm ²	50/0.18	VCTE	8.7	60°C, 75°C



Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
UL SP	ZV02	125V 10A	18	41/0.16	SVT	6.4	60°C, 75°C or 105°C
	ZJ02	125V 10A	18	41/0.16	SJT	8.3	60°C, 75°C or 105°C



Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
UL SP	ZV07	125V 10A	18	41/0.16	SVT	6.4	60°C, 75°C or 105°C
	ZJ07	125V 10A	18	41/0.16	SJT	8.3	60°C, 75°C or 105°C



For Polarized plug add -P after model no.

Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
			Z1	125V 10A			
UL SP	Z2	125V 13A	16	66/0.16	SPT-2, (HPN)	3.7x7.4	(HPN-90°C, 105°C)
	ZP1	125V 12A	1.25mm ²	50/0.18	HVFF	3.1x6.2	HVFF 75°C

INTERNATIONAL



STANDARD LENGTH: 2 METERS (6.7 FT)

Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			



Continental Europe Cord Set

Approval	Model No.	Rating	Size of Conductor	Cord	Nominal O.D. (mm)	Temperature Rating
DVE	Z510	250V 10A	(1.0mm ²)	32/0.2	H05VV-F	7.5 mm 60°C, 75°C




United Kingdom Cord Set, With 13A Fuse

Approval	Model No.	Rating	Size of Conductor	Cord	Nominal O.D. (mm)	Temperature Rating
DVE	Z610	250V 10A	(1.0mm ²)	32/0.2	H05VV-F	7.5 mm 60°C, 75°C



Australia Plug, Optional 2 Prong

Approval	Model No.	Rating	Size of Conductor	Cord	Nominal O.D. (mm)	Temperature Rating
ETA S/86	Z410	250V 10A	(1.0mm ²)	32/0.2	GFC-3R	7.5 mm 75°C



Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
DVE	Z505	250V 6A	(0.75mm ²)	42/0.15	H05VV-F	7.5 mm 60°C	
	Z506	250V 10A	(1.0mm ²)	32/0.2	H05VV-F	7.5 mm 60°C	



Continental Europe

Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
DVE	Z508	250V 6A	(0.75mm ²)	42/0.15	H05VV-F	7.5 mm 60°C	
	Z509	250V 10A	(1.0mm ²)	32/0.2	H05VV-F	7.5 mm 60°C	



Approval	Model No.	Rating	Size of Conductor		Cord	Nominal O.D. (mm)	Temperature Rating
			AWG	Composition			
DVE	Z502	250V 6A	(0.75mm ²)	42/0.15	H05VV-F	7.5 mm 60°C	
	Z503	250V 10A	(1.0mm ²)	32/0.2	H05VV-F	7.5 mm 60°C	



Approval	Model No.	Rating	Size of Conductor	Cord	Nominal O.D. (mm)	Temperature Rating
DVE	Z3	250V 2.5A	(0.75mm ²)	42/0.15	H03VVH2-F H05VVH2-F	3.7x5.8 60°C

Notes:

- The mark S next to the cord assembly denotes that shielded cord is available when requested.
- Shielded power supply cords are 100% aluminum-mylar tape shielded.
- All cords except Z1, Z2, ZP1 are available in 14 or 16 AWG wire for higher power ratings.

SPECIAL LENGTHS, CUSTOM MADE CORDS, STRAIN RELIEF, ETC. ARE AVAILABLE PER CUSTOMER SPECIFICATIONS.

"SEE PAGE 2 FOR 10 WATT VULCAN POWER CORDS"