

2 Mbit (128K x16) 1.8V Asynchronous SRAM

FEATURES SUMMARY

- SUPPLY VOLTAGE: 1.65 to 1.95V
- 128K x 16 bits SRAM with OUTPUT ENABLE
- EQUAL CYCLE and ACCESS TIME: 55ns
- SINGLE BYTE READ/WRITE
- LOW STANDBY CURRENT
- LOW V_{CC} DATA RETENTION: 1.0V
- TRI-STATE COMMON I/O
- AUTOMATIC POWER DOWN

Figure 1. Packages




TABLE OF CONTENTS

FEATURES SUMMARY	1
Figure 1. Packages	1
SUMMARY DESCRIPTION	3
Figure 2. Logic Diagram	3
Table 1. Signal Names	3
Figure 3. TFBGA Connections (Top view through package)	4
Figure 4. Block Diagram	5
OPERATION	6
Read Mode	6
Write Mode	6
Table 2. Operating Modes	6
MAXIMUM RATING	7
Table 3. Absolute Maximum Ratings	7
DC and AC PARAMETERS	8
Table 4. Operating and AC Measurement Conditions	8
Figure 5. AC Measurement I/O Waveform	8
Figure 6. AC Measurement Load Circuit	8
Table 5. Capacitance	9
Table 6. DC Characteristics	9
Figure 7. Address Controlled, Read Mode AC Waveforms	10
Figure 8. Chip Enable or Output Enable Controlled, Read Mode AC Waveforms	10
Figure 9. Chip Enable or $\overline{UB}/\overline{LB}$ Controlled, Standby Mode AC Waveforms	10
Table 7. Read and Standby Mode AC Characteristics	11
Figure 10. Write Enable Controlled, Write AC Waveforms	12
Figure 11. Chip Enable Controlled, Write AC Waveforms	13
Figure 12. $\overline{UB}/\overline{LB}$ Controlled, Write AC Waveforms	13
Table 8. Write Mode AC Characteristics	14
Figure 13. Low V_{CC} Data Retention AC Waveforms	15
Table 9. Low V_{CC} Data Retention Characteristics	15
PACKAGE MECHANICAL	16
Figure 14. TFBGA48 6x8mm - 6x8 ball array, 0.75 mm pitch, Bottom View Package Outline	16
Table 10. TFBGA48 6x8mm - 6x8 ball array, 0.75 mm pitch, Package Mechanical Data	16
PART NUMBERING	17
Table 11. Ordering Information Scheme	17
REVISION HISTORY	18
Table 12. Document Revision History	18

SUMMARY DESCRIPTION

The M68AR128M is a 2 Mbit (2,097,152 bit) CMOS SRAM, organized as 131,072 words by 16 bits. The device features fully static operation requiring no external clocks or timing strobes, with equal address access and cycle times. It requires a single 1.8V (±150mV) supply. This device has an

automatic power-down feature, reducing the power consumption by over 99% when deselected. The M68AR128M is available in TFBGA48 (0.75 mm pitch) package.

Figure 2. Logic Diagram




Table 1. Signal Names

A0-A16	Address Inputs
DQ0-DQ15	Data Input/Output
$\overline{E}$	Chip Enable
$\overline{G}$	Output Enable
$\overline{W}$	Write Enable
$\overline{UB}$	Upper Byte Enable Input
$\overline{LB}$	Lower Byte Enable Input
VCC	Supply Voltage
VSS	Ground
NC	Not Connected Internally
DU	Don't Use as Internally Connected

Figure 3. TFBGA Connections (Top view through package)





Figure 4. Block Diagram



OPERATION

The M68AR128M has a Chip Enable power down feature which invokes an automatic standby mode whenever either Chip Enable is de-asserted ($\overline{E}$ = High) or LB and UB are de-asserted (LB and UB = High). An Output Enable ($\overline{G}$) signal provides a high speed tri-state control, allowing fast read/write cycles to be achieved with the common I/O data bus. Operational modes are determined by device control inputs W, E, LB and UB as summarized in the Operating Modes table (see Table 6).

Read Mode

The M68AR128M is in the Read mode whenever Write Enable (W) is High with Output Enable ($\overline{G}$) Low, and Chip Enables ($\overline{E}$) is asserted. This provides access to data from eight or sixteen, depending on the status of the signal UB and LB, of the 2,097,152 locations in the static memory array, specified by the 17 address inputs. Valid data will be available at the eight or sixteen output pins within t_{AVQV} after the last stable address, providing $\overline{G}$ is Low and $\overline{E}$ is Low. If Chip Enable or Output Enable access times are not met, data access will be measured from the limiting parameter (t_{ELQV} , t_{GLQV} or t_{BLQV}) rather than the address. Data out may be indeterminate at t_{ELQX} , t_{BLQX} and t_{GLQX} , but data lines will always be valid at t_{AVQV} .

Write Mode

The M68AR128M is in the Write mode whenever the W and E are Low. Either the Chip Enable input ($\overline{E}$) or the Write Enable input (W) must be de-asserted during Address transitions for subsequent write cycles. When $\overline{E}$ (W) is Low, and UB or LB is Low, write cycle begins on the $\overline{W}$ ($\overline{E}$)'s falling edge. When $\overline{E}$ and W are Low, and UB = LB = High, write cycle begins on the first falling edge of UB or LB. Therefore, address setup time is referenced to Write Enable, Chip Enable or UB/LB as t_{AVWL} , t_{AVEL} and t_{AVBL} respectively, and is determined by the latter occurring edge.

The Write cycle can be terminated by the earlier rising edge of E, W or UB/LB.

If the Output is enabled ($\overline{E}$ = Low, $\overline{G}$ = Low, $\overline{LB}$ or UB = Low), then W will return the outputs to high impedance within t_{WLQZ} of its falling edge. Care must be taken to avoid bus contention in this type of operation. Data input must be valid for t_{DVWH} before the rising edge of Write Enable, or for t_{DVEH} before the rising edge of $\overline{E}$, or for t_{DVBH} before the rising edge of UB/LB whichever occurs first, and remain valid for t_{WHDX} , t_{EHDX} and t_{BHDX} respectively.

Table 2. Operating Modes

Operation	$\overline{E}$	$\overline{W}$	$\overline{G}$	$\overline{LB}$	$\overline{UB}$	DQ0-DQ7	DQ8-DQ15	Power
Deselected	V_{IH}	X	X	X	X	Hi-Z	Hi-Z	Standby (I_{SB})
Deselected	X	X	X	V_{IH}	V_{IH}	Hi-Z	Hi-Z	Standby (I_{SB})
Lower Byte Read	V_{IL}	V_{IH}	V_{IL}	V_{IL}	V_{IH}	Data Output	Hi-Z	Active (I_{CC})
Lower Byte Write	V_{IL}	V_{IL}	X	V_{IL}	V_{IH}	Data Input	Hi-Z	Active (I_{CC})
Output Disabled	V_{IL}	V_{IH}	V_{IH}	X	X	Hi-Z	Hi-Z	Active (I_{CC})
Upper Byte Read	V_{IL}	V_{IH}	V_{IL}	V_{IH}	V_{IL}	Hi-Z	Data Output	Active (I_{CC})
Upper Byte Write	V_{IL}	V_{IL}	X	V_{IH}	V_{IL}	Hi-Z	Data Input	Active (I_{CC})
Word Read	V_{IL}	V_{IH}	V_{IL}	V_{IL}	V_{IL}	Data Output	Data Output	Active (I_{CC})
Word Write	V_{IL}	V_{IL}	X	V_{IL}	V_{IL}	Data Input	Data Input	Active (I_{CC})

Note: 1. X = V_{IH} or V_{IL} .

MAXIMUM RATING

Stressing the device above the rating listed in the "Absolute Maximum Ratings" table may cause permanent damage to the device. These are stress ratings only and operation of the device at these or any other conditions above those indicated in the Operating sections of this specification is not im-

plied. Exposure to Absolute Maximum Rating conditions for extended periods may affect device reliability. Refer also to the STMicroelectronics SURE Program and other relevant quality documents.

Table 3. Absolute Maximum Ratings

Symbol	Parameter	Value	Unit
$I_O^{(1)}$	Output Current	20	mA
T_A	Ambient Operating Temperature	-55 to 125	°C
T_{STG}	Storage Temperature	-65 to 150	°C
V_{CC}	Supply Voltage	-0.5 to 2.5	V
$V_{IO}^{(2)}$	Input or Output Voltage	-0.5 to $V_{CC} + 0.5$	V
P_D	Power Dissipation	1	W

Note: 1. One output at a time, not to exceed 1 second duration.

2. Up to a maximum operating V_{CC} of 1.95V only.

DC AND AC PARAMETERS

This section summarizes the operating and measurement conditions, as well as the DC and AC characteristics of the device. The parameters in the following DC and AC Characteristic tables are derived from tests performed under the Measure-

ment Conditions listed in the relevant tables. Designers should check that the operating conditions in their projects match the measurement conditions when using the quoted parameters.

Table 4. Operating and AC Measurement Conditions

Parameter		M68AR128M
V _{CC} Supply Voltage		1.65 to 1.95V
Ambient Operating Temperature	Range 1	0 to 70°C
	Range 6	−40 to 85°C
Load Capacitance (C _L)		30pF
Output Circuit Protection Resistance (R ₁)		15.3kΩ
Load Resistance (R ₂)		11.3kΩ
Input Rise and Fall Times		1ns/V
Input Pulse Voltages		0 to V _{CC}
Input and Output Timing Ref. Voltages		V _{CC} /2
Output Transition Timing Ref. Voltages		V _{RL} = 0.3V _{CC} ; V _{RH} = 0.7V _{CC}

Figure 5. AC Measurement I/O Waveform




Figure 6. AC Measurement Load Circuit




Table 5. Capacitance

Symbol	Parameter ^(1,2)	Test Condition	Min	Max	Unit
C _{IN}	Input Capacitance on all pins (except DQ)	V _{IN} = 0V		6	pF
C _{OUT}	Output Capacitance	V _{OUT} = 0V		8	pF

Note: 1. Sampled only, not 100% tested.

2. At T_A = 25°C, f = 1 MHz, V_{CC} = 1.8V.

Table 6. DC Characteristics

Symbol	Parameter	Test Condition	Min	Typ	Max	Unit
I _{CC1} ^(1,2)	Operating Supply Current	V _{CC} = 1.95V, f = 1/t _{AVAV} , I _{OUT} = 0mA		2	6	mA
I _{CC2} ⁽³⁾	Operating Supply Current	V _{CC} = 1.95V, f = 1MHz, I _{OUT} = 0mA		1	2	mA
I _{LI}	Input Leakage Current	0V ≤ V _{IN} ≤ V _{CC}	-1		1	μA
I _{LO} ⁽⁴⁾	Output Leakage Current	0V ≤ V _{OUT} ≤ V _{CC} ⁽³⁾	-1		1	μA
I _{SB}	Standby Supply Current CMOS	V _{CC} = 1.95V, $\overline{E} \geq V_{CC} - 0.2V$ or $\overline{LB} = \overline{UB} \geq V_{CC} - 0.2V$, f = 0		0.5	4	μA
V _{IH}	Input High Voltage		1.4		V _{CC} + 0.4	V
V _{IL}	Input Low Voltage		-0.5		0.4	V
V _{OH}	Output High Voltage	I _{OH} = -100μA	1.5			V
V _{OL}	Output Low Voltage	I _{OL} = 100μA			0.2	V


Note: 1. Average AC current, cycling at t_{AVAV} minimum.

2. $\overline{E}$ = V_{IL}, $\overline{LB}$ or/and $\overline{UB}$ = V_{IL}, V_{IN} = V_{IL} or V_{IH}.

3. E ≤ 0.2V, $\overline{LB}$ or/and $\overline{UB}$ ≤ 0.2V, V_{IN} ≤ 0.2V or V_{IN} ≥ V_{CC} - 0.2V.


4. Output disabled.

Figure 7. Address Controlled, Read Mode AC Waveforms



Note: $\overline{E}$ = Low, $\overline{G}$ = Low, $\overline{W}$ = High, $\overline{UB}$ = Low and/or $\overline{LB}$ = Low.

Figure 8. Chip Enable or Output Enable Controlled, Read Mode AC Waveforms



Note: Write Enable ($\overline{W}$) = High.


Figure 9. Chip Enable or $\overline{UB}/\overline{LB}$ Controlled, Standby Mode AC Waveforms

Table 7. Read and Standby Mode AC Characteristics

Symbol	Parameter		M68AR128M		Unit
			55	70	
t_{AVAV}	Read Cycle Time	Min	55	70	ns
t_{AVQV}	Address Valid to Output Valid	Max	55	70	ns
$t_{AXQX}^{(1)}$	Data hold from address change	Min	5	5	ns
$t_{BHQZ}^{(2,3)}$	Upper/Lower Byte Enable High to Output Hi-Z	Max	20	25	ns
t_{BLQV}	Upper/Lower Byte Enable Low to Output Valid	Max	55	70	ns
$t_{BLQX}^{(1)}$	Upper/Lower Byte Enable Low to Output Transition	Min	5	5	ns
$t_{EHQZ}^{(2,3)}$	Chip Enable High to Output Hi-Z	Max	20	25	ns
t_{ELQV}	Chip Enable Low to Output Valid	Max	55	70	ns
$t_{ELQX}^{(1)}$	Chip Enable Low to Output Transition	Min	5	5	ns
$t_{GHQZ}^{(2,3)}$	Output Enable High to Output Hi-Z	Max	20	25	ns
t_{GLQV}	Output Enable Low to Output Valid	Max	25	35	ns
$t_{GLQX}^{(2)}$	Output Enable Low to Output Transition	Min	5	5	ns
$t_{PD}^{(4)}$	Chip Enable or $\overline{UB}/\overline{LB}$ High to Power Down	Max	55	70	ns
$t_{PU}^{(4)}$	Chip Enable or $\overline{UB}/\overline{LB}$ Low to Power Up	Min	0	0	ns


Note: 1. Test conditions assume transition timing reference level = $0.3V_{CC}$ or $0.7V_{CC}$.

2. At any given temperature and voltage condition, t_{GHQZ} is less than t_{GLQX} , t_{BHQZ} is less than t_{BLQX} and t_{EHQZ} is less than t_{ELQX} for any given device.

3. These parameters are defined as the time at which the outputs achieve the open circuit conditions and are not referenced to output voltage levels.


4. Tested initially and after any design or process changes that may affect these parameters.

Figure 10. Write Enable Controlled, Write AC Waveforms




Note: 1. During this period DQ0-DQ15 are in output state and input signals should not be applied.

Figure 11. Chip Enable Controlled, Write AC Waveforms



AI04842

Figure 12. $\overline{UB}/\overline{LB}$ Controlled, Write AC Waveforms

AI04843


Note: 1. During this period DQ0-DQ15 are in output state and input signals should not be applied.

Table 8. Write Mode AC Characteristics

Symbol	Parameter		M68AR128M		Unit
			55	70	
t_{AVAV}	Write Cycle Time	Min	55	70	ns
t_{AVBH}	Address Valid to $\overline{LB}$, $\overline{UB}$ High	Min	45	60	ns
t_{AVBL}	Address Valid to $\overline{LB}$, $\overline{UB}$ Low	Min	0	0	ns
t_{AVEH}	Address Valid to Chip Enable High	Min	45	60	ns
t_{AVEL}	Address valid to Chip Enable Low	Min	0	0	ns
t_{AVWH}	Address Valid to Write Enable High	Min	45	60	ns
t_{AVWL}	Address Valid to Write Enable Low	Min	0	0	ns
t_{BHAX}	$\overline{LB}$, $\overline{UB}$ High to Address Transition	Min	0	0	ns
t_{BHDX}	$\overline{LB}$, $\overline{UB}$ High to Input Transition	Min	0	0	ns
t_{BLBH}	$\overline{LB}$, $\overline{UB}$ Low to $\overline{LB}$, $\overline{UB}$ High	Min	45	60	ns
t_{BLEH}	$\overline{LB}$, $\overline{UB}$ Low to Chip Enable High	Min	45	60	ns
t_{BLWH}	$\overline{LB}$, $\overline{UB}$ Low to Write Enable High	Min	45	60	ns
t_{DVBH}	Input Valid to $\overline{LB}$, $\overline{UB}$ High	Min	25	30	ns
t_{DVEH}	Input Valid to Chip Enable High	Min	25	30	ns
t_{DVWH}	Input Valid to Write Enable High	Min	25	30	ns
t_{EHAX}	Chip Enable High to Address Transition	Min	0	0	ns
t_{EHDX}	Chip enable High to Input Transition	Min	0	0	ns
t_{ELBH}	Chip Enable Low to $\overline{LB}$, $\overline{UB}$ High	Min	45	60	ns
t_{ELEH}	Chip Enable Low to Chip Enable High	Min	45	60	ns
t_{ELWH}	Chip Enable Low to Write Enable High	Min	45	60	ns
t_{WHAX}	Write Enable High to Address Transition	Min	0	0	ns
t_{WHDX}	Write Enable High to Input Transition	Min	0	0	ns
$t_{WHQX}^{(1)}$	Write Enable High to Output Transition	Min	5	5	ns
t_{WLBH}	Write Enable Low to $\overline{LB}$, $\overline{UB}$ High	Min	45	60	ns
t_{WLEH}	Write Enable Low to Chip Enable High	Min	45	60	ns
$t_{WLQZ}^{(1,2)}$	Write Enable Low to Output Hi-Z	Max	20	20	ns
t_{WLWH}	Write Enable Low to Write Enable High	Min	45	60	ns

Note: 1. At any given temperature and voltage condition, t_{WLQZ} is less than t_{WHQX} for any given device.

2. These parameters are defined as the time at which the outputs achieve the open circuit conditions and are not referenced to output voltage levels.

Figure 13. Low V_{CC} Data Retention AC WaveformsTable 9. Low V_{CC} Data Retention Characteristics

Symbol	Parameter	Test Condition	Min	Typ	Max	Unit
$I_{CCDR}^{(1)}$	Supply Current (Data Retention)	$V_{CC} = 1.0V, \bar{E} \geq V_{CC} - 0.2V$ or $\bar{UB} = \bar{LB} \geq V_{CC} - 0.2V, f = 0^{(3)}$		0.5	2	μA
$t_{CDR}^{(1,2)}$	Chip Deselected to Data Retention Time		0			ns
$t_R^{(2)}$	Operation Recovery Time		t_{AVAV}			ns
$V_{DR}^{(1)}$	Supply Voltage (Data Retention)	$\bar{E} \geq V_{CC} - 0.2V$ or $\bar{UB} = \bar{LB} \geq V_{CC} - 0.2V, f = 0$	1.0			V


Note: 1. All other Inputs at $V_{IH} \geq V_{CC} - 0.2V$ or $V_{IL} \leq 0.2V$.

2. Tested initially and after any design or process changes that may affect these parameters. t_{AVAV} is Read cycle time.

3. No input may exceed $V_{CC} + 0.2V$.

PACKAGE MECHANICAL

Figure 14. TFBGA48 6x8mm - 6x8 ball array, 0.75 mm pitch, Bottom View Package Outline



Note: Drawing is not to scale.

Table 10. TFBGA48 6x8mm - 6x8 ball array, 0.75 mm pitch, Package Mechanical Data

Symbol	millimeters			inches		
	Typ	Min	Max	Typ	Min	Max
A			1.200			0.0472
A1		0.260			0.0102	
A2			0.900			0.0354
b		0.350	0.450		0.0138	0.0177
D	6.000	5.900	6.100	0.2362	0.2323	0.2402
D1	3.750	—	—	0.1476	—	—
ddd			0.100			0.0039
E	8.000	7.900	8.100	0.3150	0.3110	0.3189
E1	5.250	—	—	0.2067	—	—
e	0.750	—	—	0.0295	—	—
FD	1.125	—	—	0.0443	—	—
FE	1.375	—	—	0.0541	—	—
SD	0.375	—	—	0.0148	—	—
SE	0.375	—	—	0.0148	—	—

PART NUMBERING

Table 11. Ordering Information Scheme

Example:	M68AR128	M	L	55	ZB	6	T
Device Type							
M68							
Mode							
A = Asynchronous							
Operating Voltage							
R = 1.65 to 1.95V							
Array Organization							
128 = 2 Mbit (128K x16)							
Option 1							
M = 1 Chip Enable; Write and Standby from UB and LB							
Option 2							
L = Low Leakage							
Speed Class							
55 = 55 ns 70 = 70 ns							
Package							
ZB = TFBGA48: 0.75 mm pitch							
Operative Temperature							
1 = 0 to 70 °C 6 = -40 to 85 °C							
Shipping							
T = Tape & Reel Packing							

Note: 1. Package option available on request. Please contact STMicroelectronics local Sales Office.

For a list of available options (e.g., Speed, Package) or for further information on any aspect of this device, please contact the ST Sales Office nearest to you.

REVISION HISTORY

Table 12. Document Revision History

Date	Version	Revision Details
July 2001	-01	First Issue
05-Mar-2002	-02	tAXQX, tBLQX, tELQX clarified in Read and Standby Mode AC Characteristics table (Table 7)
14-May-2002	-03	Document globally revised
09-Oct-2002	3.1	Revision numbering modified: a minor revision will be indicated by incrementing the digit after the dot, and a major revision, by incrementing the digit before the dot (revision version 03 equals 3.0). Part number changed
27-Sep-2004	4.0	t _{PD} and t _{PU} modified in Table 7., Read and Standby Mode AC Characteristics . Document structure updated without modifications of the content.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.

All other names are the property of their respective owners

© 2004 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com