



TY Variable Capacitance Diode

- For Hyperband TV / VTR tuners, Bd I



BB640



Type	Package	Configuration	L_S (nH)	Marking
BB640	SOD323	single	1.8	red S

Maximum Ratings at $T_A = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value	Unit
Diode reverse voltage	V_R	30	V
Peak reverse voltage ($R \geq 5\text{k}\Omega$)	V_{RM}	35	
Forward current	I_F	20	mA
Operating temperature range	T_{op}	-55 ... 150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 ... 150	

Electrical Characteristics at $T_A = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Reverse current $V_R = 30 \text{ V}$ $V_R = 30 \text{ V}, T_A = 85^\circ\text{C}$	I_R	- -	- -	10 200	nA
AC Characteristics					
Diode capacitance $V_R = 1 \text{ V}, f = 1 \text{ MHz}$ $V_R = 2 \text{ V}, f = 1 \text{ MHz}$ $V_R = 25 \text{ V}, f = 1 \text{ MHz}$ $V_R = 28 \text{ V}, f = 1 \text{ MHz}$	C_T	62 47.5 2.85 2.8	69 54.5 3.28 3.05	76 61.5 3.7 3.3	pF
Capacitance ratio $V_R = 1 \text{ V}, V_R = 28 \text{ V}, f = 1 \text{ MHz}$	C_{T1}/C_{T28}	19.5	-	25	
Capacitance ratio $V_R = 2 \text{ V}, V_R = 25 \text{ V}, f = 1 \text{ MHz}$	C_{T2}/C_{T25}	15	16.6	-	
Capacitance matching ¹⁾ $V_R = 1 \text{ V}, V_R = 28 \text{ V}, f = 1 \text{ MHz}$	$\Delta C_T/C_T$	-	-	2.5	%
Series resistance $C_T = 12 \text{ pF}, f = 100 \text{ MHz}$	r_S	-	1.15	-	Ω

¹For details please refer to Application Note 047.