Between-Series Adapters

N to SMA

N Male Plug to SMA Male Plug

Model Number


ADT-2580-NM-SMM-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.04 @ DC-4.0 GHz 1.07 @ 4.0-8.0 GHz 1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel





Model Number

ADT-2581-NM-SMF-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz **VSWR:** 1.04 @ DC-4.0 GHz 1.07 @ 4.0-8.0 GHz 1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel

N Male Plug to SMA Female Jack





Model Number

ADT-2582-NF-SMM-02


SPECIFICATIONS

Frequency: DC - 18.0 GHz **VSWR:** 1.04 @ DC-4.0 GHz 1.07 @ 4.0-8.0 GHz 1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel

N Female Jack to SMA Male Plug





N Female Jack to SMA Female Jack

Model Number

ADT-2583-NF-SMF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.04 @ DC-4.0 GHz 1.07 @ 4.0-8.0 GHz 1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel

