


## Features

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

## DO - 27



Dimensions in millimeters

## Mechanical Data

- ◇ Case: JEDEC DO-27, molded plastic
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.041 ounces, 1.15 grams
- ◇ Mounting position: Any

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		ERD29-02	ERD29-04	ERD29-06	UNITS
Maximum recurrent peak reverse voltage	$V_{RRM}$	200	400	600	V
Maximum RMS voltage	$V_{RMS}$	140	280	420	V
Maximum DC blocking voltage	$V_{DC}$	200	400	600	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ\text{C}$	$I_{F(AV)}$	2.5			A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ\text{C}$	$I_{FSM}$	150.0			A
Maximum instantaneous forward voltage @ 2.5 A	$V_F$	1.1			V
Maximum reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	$I_R$	5.0 100.0			$\mu\text{A}$
Maximum reverse recovery time (Note1)	$t_{rr}$	100			ns
Typical junction capacitance (Note2)	$C_J$	22			pF
Typical thermal resistance (Note3)	$R_{\theta JA}$	35			$^\circ\text{C/W}$
Operating junction temperature range	$T_J$	-55----+150			$^\circ\text{C}$
Storage temperature range	$T_{STG}$	-55----+150			$^\circ\text{C}$


NOTE:1. Measured with  $I_F=0.5\text{A}$ ,  $I_R=1\text{A}$ ,  $I_{rr}=0.25\text{A}$ .

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


3. Thermal resistance from junction to ambient.

## Ratings AND Characteristic Curves


**FIG.1 – REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM**



NOTES:  
1.RISE TIME=7ns MAX. INPUT IMPEDANCE=1MΩ 22pF  
2.RISE TIME=10ns MAX. SOURCE IMPEDANCE=50Ω




**FIG.2 – TYPICAL FORWARD CHARACTERISTIC**



INSTANTANEOUS FORWARD VOLTAGE, VOLTS


INSTANTANEOUS FORWARD CURRENT  
AMPERES

**FIG.3 – FORWARD DERATING CURVE**



AMBIENT TEMPERATURE, °C


**FIG.4-TYPICAL JUNCTION CAPACITANCE**



REVERSE VOLTAGE, VOLTS

PEAK FORWARD SURGE CURRENT  
AMPERES

**FIG.5-PEAK FORWARD SURGE CURRENT**



NUMBER OF CYCLES AT 60 Hz