

# GAS GENERATOR SET

## GS 150-6S

150 kWe / 60 Hz / Standby  
208 - 600V

(Reference GP130N6S for Prime Rating Technical Data)



### SYSTEM RATINGS

Standby (NG) (LP)	GS 150N6SGA GS 150L6SGA	GS 150N6SDA GS 150L6SDA	GS 150N6SPA GS 150L6SPA	GS 150N6SJA GS 150L6SJA	GS 150N6SRA GS 150L6SRA	GS 150N6SNA GS 150L6SNA
<b>Voltage (L-L)</b>	<b>240V**</b>	<b>240V**</b>	<b>208V**</b>	<b>240V**</b>	<b>480V**</b>	<b>600V**</b>
Phase	1	1	3	3	3	3
PF	1.0	1.0	0.8	0.8	0.8	0.8
Hz	60	60	60	60	60	60
Natural Gas						
Ratings: Amps	625	625	520	451	225	180
Natural Gas						
Ratings: kW/kVA	150/150	150/150	150/187	150/187	150/187	150/187
LP Gas						
Ratings: Amps	416	416	346	300	150	120
LP Gas						
Ratings: kW/kVA	100/100	100/100	100/125	100/125	100/125	100/125
skVA@30%						
Voltage Dip	250	360	433	433	577	380
Generator Model*	432PSL6212	432PSL6228	431PSL6206	431PSL6206	431PSL6206	431PSL6242
Temp Rise	130 °C/40 °C	130 °C/40 °C	130 °C/40 °C	130 °C/40 °C	130 °C/40 °C	130 °C/40 °C
Connection	12 LEAD ZIG-ZAG	4 LEAD	12 LEAD LOW WYE	12 LEAD HI DELTA	12 LEAD HI WYE	4 LEAD WYE

\* Consult the factory for alternate configuration.

\*\* UL 2200 Offered

### CERTIFICATIONS AND STANDARDS

// **Generator set is designed and manufactured in facilities certified to standards ISO 9001:2008 and ISO 14001:2004**

// **Power Rating**  
- Accepts Rated Load in One Step Per NFPA 110

// **UL 2200 / CSA – Optional**

- UL 2200 Listed
- CSA Certified

// **Performance Assurance Certification (PAC)**

- Generator Set Tested to ISO 8528-5 for Transient Response
- Verified product design, quality and performance integrity
- All engine systems are prototype and factory tested

## STANDARD FEATURES\*

- // MTU Onsite Energy is a single source supplier
  - // Global Product Support
  - // 2 Year Standard Warranty
  - // 8.1 L Turbo Engine Charge Air Cooling
    - 8.1 Liter Displacement
    - 4-Cycle
  - // 3-Way Catalyst
  - // Optional Fuels: LP Liquid and Dual Fuel
  - // Engine-generator resilient mounted
  - // Complete Range of Accessories
- // Generator
    - Brushless, Rotating Field Generator
    - 2/3 Pitch Windings
    - 300% Short Circuit Capability with Optional PMG
  - // Digital Control Panel(s)
    - UL Recognized, CSA Certified, NFPA 110
    - Complete System Metering
    - LCD Display
  - // Cooling System
    - Integral Set-Mounted
    - Engine Driven Fan

## STANDARD EQUIPMENT\*

### // Engine

Air Cleaner  
 Oil Pump  
 Oil Drain Extension & S/O Valve  
 Full Flow Oil Filter  
 Jacket Water Pump  
 Thermostats  
 Blower Fan & Fan Drive  
 Radiator - Unit Mounted  
 Electric Starting Motor - 24V  
 Governor - Electronic Isochronous  
 Base - Formed Steel  
 SAE Flywheel & Bell Housing  
 Charging Alternator - 24V  
 Battery Box & Cables  
 Flexible Fuel Connectors  
 Flexible Exhaust Connection  
 EPA Certified Engine

### // Generator

NEMA MG1, IEEE and ANSI standards compliance for temperature rise and motor starting  
 Self Ventilated and Drip-proof  
 Superior Voltage Waveform  
 Solid State, Volts-per-hertz Regulator  
 ±1% Voltage Regulation No Load to Full Load  
 Brushless Alternator with Brushless Pilot Exciter  
 4 pole, Rotating Field

130 °C Maximum Standby Temperature Rise  
 1 Bearing, Sealed  
 Flexible Coupling  
 Full Amortisseur Windings  
 125% Rotor Balancing  
 3-phase Voltage Sensing  
 100% of Rated Load - One Step  
 5% Maximum Total Harmonic Distortion

### // Digital Control Panel(s)

Digital Metering  
 Engine Parameters  
 Generator Protection Functions  
 Engine Protection  
 SAE J1939 Engine ECU Communications  
 Windows®-Based Software  
 Multilingual Capability  
 Remote Communications to RDP-110 Remote Annunciator  
 16 Programmable Contact Inputs  
 Up to 11 Contact Outputs  
 UL Recognized, CSA Certified, CE Approved  
 Event Recording  
 IP 54 Front Panel Rating with Integrated Gasket  
 NFPA110 Compatible

\* Represents standard product only. Consult Factory/MTU Onsite Energy Distributor for additional configurations.

## APPLICATION DATA

### // Engine

Manufacturer	Doosan
Model	8.1L CAC
Type	4-Cycle
Arrangement	6-Inline
Displacement: L (in <sup>3</sup> )	8.1 (492)
Bore: cm (in)	11.1 (4.37)
Stroke: cm (in)	13.9 (5.97)
Compression Ratio	10.5:1
Rated RPM	1,800
Engine Governor	Bosch
Maximum Power (NG): kWm (bhp)	177 (237)
Maximum Power (LP): kWm (bhp)	122 (164)
Speed Regulation	±0.5%
Air Cleaner	Dry

### // Liquid Capacity (Lubrication)

Total Oil System: L (gal)	27.5 (7.2)
Engine Jacket Water Capacity: L (gal)	22.7 (5)
System Coolant Capacity: L (gal)	240 (63)

### // Electrical

Electric Volts DC	24
Cold Cranking Amps Under -17.8 °C (0 °F)	1,050

### // Fuel Inlet

Fuel Supply Connection Size	1 1/2" NPT
Fuel Supply Pressure: mm H <sub>2</sub> O (in. H <sub>2</sub> O)	178-279 (7-11)

### // Fuel Consumption (NG-1000 BTU/ft<sup>3</sup> / LP-2500 BTU/ft<sup>3</sup>)

	NG	LPG
At 100% of Power Rating: m <sup>3</sup> /hr (ft <sup>3</sup> /hr)	43.6 (1,539)	14.7 (517)
At 75% of Power Rating: m <sup>3</sup> /hr (ft <sup>3</sup> /hr)	33.7 (1,191)	11.1 (390)
At 50% of Power Rating: m <sup>3</sup> /hr (ft <sup>3</sup> /hr)	23.9 (845)	8 (283)

### // Cooling - Radiator System

Ambient Capacity of Radiator: °C (°F)	50 (122)*	
Maximum Restriction of Cooling Air, Intake, and Discharge Side of Rad.: kPa (in. H <sub>2</sub> O)	0.12 (0.5)	
Water Pump Capacity: L/min (gpm)	240 (63)	
Heat Rejection to Coolant: kW (BTUM)	164.4 (9,357)	
Heat Radiated to Ambient: kW (BTUM)	65.2 (3,710)	
Fan Power: kW (hp)	5.6 (7.5)	5.6 (7.5)

\* Installation of enclosures reduces the ambient capacity of the cooling system by 1 °C (1.8 °F). Gravity exhaust louvers reduce ambient capacity of the cooling system by an additional 3 °C (5.5 °F).

### // Air Requirements

Aspirating: *m <sup>3</sup> /min (SCFM)	9.3 (317)
Air Flow Required for Rad. Cooled Unit: **m <sup>3</sup> /min (SCFM)	428 (15,100)
Remote Cooled Applications; Air Flow Required for Dissipation of Radiated Gen-set Heat for a Max of 25 °F Rise: *m <sup>3</sup> /min (SCFM)	147 (5,175)


\* Air density = 1.184 kg/m<sup>3</sup> (0.0739 lbm/ft<sup>3</sup>)

\*\* At 0.25 kPa (1 in. H<sub>2</sub>O) static pressure and 52 °C (125 °F) at radiator

### // Exhaust System

Gas Temp. (Stack): °C (°F)	660 (1,220)
Gas Volume at Stack Temp: m <sup>3</sup> /min (CFM)	29.7 (1,050)
Maximum Allowable Back Pressure: kPa (in. H <sub>2</sub> O)	2.5 (10.25)

## WEIGHTS AND DIMENSIONS



Drawing above for illustration purposes only, based on standard open power 480 volt generator set. Lengths may vary with other voltages. Do not use for installation design. See website for unit specific template drawings.

System	Dimensions (L x W x H)	Weight (dry/less tank)
Open Power Unit (OPU)	3,607 x 1,591 x 1,788 mm (142 x 62.63 x 70.38 in)	2,562 kg (5,647 lb)

Weights and dimensions are based on open power units and are estimates only. Consult the factory for accurate weights and dimensions for your specific generator set.

## SOUND DATA

Unit Type	Standby Full Load (NG)	Standby Full Load (LP)
Level 0: Open Power Unit dB(A)	82	81.7

Sound data is provided at 7 m (23 ft). Generator set tested in accordance with ISO 8528-10 and with infinite exhaust.

## EMISSIONS DATA

Fuel Type	THC + NO <sub>x</sub>	CO
Natural Gas	0.63	0.13
Liquid Propane	0.08	0.39

All units are in g/hp-hr and are EPA D2 cycle values.

## RATING DEFINITIONS AND CONDITIONS

- // Ambient capability factor at 984 ft (300 m). Consult your local MTU Onsite Energy Power Generation Distributor for other altitudes.
- // Standby ratings apply to installations served by a reliable utility source. The standby rating is applicable to varying loads for the duration of a power outage. No overload capability for this rating. Ratings are in accordance with ISO 3046-1, BS 5514, AS 2789, and DIN 6271.
- // Deration Factor:  
Production tolerances in engines and installed components can account for power variations. Altitude, temperature and excessive exhaust and intake restrictions should be applied to power calculations. Consult your local MTU Onsite Energy Power Generation Distributor for derations.

Materials and specifications subject to change without notice.

C/F = Consult Factory/MTU Onsite Energy Distributor