









THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 BY AMP INCORPORATED. ALL RIGHTS RESERVED.


LOC	REV	DATE	DESCRIPTION	DATE	BY	CHK
A	40		ADDED -3 HEAD SUB-ASSEMBLIES	17MARGA	JJO	PLS

TOOL NUMBER 	WIRE SIZE mm ² [AWG] 	INSULATION DIAMETER mm [in.] 	STRIP LENGTH mm [in.] 	CRIMP HEIGHT mm [in.] 	CONTACT PART NUMBERS 		CONTACT DESCRIPTION	APPLICATION SPECIFICATION
					LOOSE PIECE 	STRIP FORM 		
91567-1 91567-3	0.12 [26]	1.3-1.6 [051-063]	3.5±0.5 [138±020]	0.69-0.83 [027-033]	179592-[] 179594-[]	177914-[] 177916-[]	POWER DOUBLE LOCK Contacts	114-5175
	0.22 [24]			0.69-0.88 [027-035]				
	0.30-0.35 [22]	1.3-2.0 [051-079]		0.77-0.94 [030-037]				
91569-1 91569-3	0.51 [20]	2.1-2.8 [083-110]	3.5±0.5 [138±020]	0.97-1.09 [048-056]	179593-[] 179595-[]	177915-[] 177917-[]	POWER DOUBLE LOCK Contacts	114-5175
	0.89 [18]			0.97-1.20 [038-047]				
	1.27 [16]	2.2-3.1 [087-122]		1.23-1.42 [048-056]				
91572-1 91572-3	0.12 [26]	0.90-1.40 [035-055]	2.1±0.2	0.60-0.73 [024-029]	179518-[] 179610-[]	179227-[] 179609-[]	CRIMP TYPE II CT 2mm Pitch Contacts	114-5179
	0.22 [24]			0.60-0.79 [024-031]				
	0.30-0.35 [22]	1.10-1.50 [043-059]		0.71-0.86 [028-034]				
91577-1 91577-3	0.30 [22]	1.80 [071]	4.0-4.5 [157-177]	0.74-0.90 [029-035]	175062-[] 175061-[] 175063-[]	173681-[] 173716-[] 173682-[]	.040 Series Contacts	114-5094 114-5108 114-5111
	0.50 [20]	2.00 [079]		0.90-1.07 [035-042]				
91579-1 91579-3	0.53-0.86 [20-18]	1.80-2.80 [071-110]	2.7-3.3 [106-130]	0.96-1.10 [038-043]	1318912-[]	1123721-[]	ECONOMY POWER CONN. (EP) Contacts	114-5303
	1.25-1.37 [16]	2.30-2.80 [091-110]		1.27-1.41 [050-054]				
91588-1 91588-3	0.30-0.56 [22]	1.1-2.0 [043-079]	4.0-4.5 [157-177]	0.78-0.94 [031-037]	179417-[] 179418-[] 179421-[]	175265-[] 175266-[] 175271-[]	.040 II Series Contacts	114-5159
	0.30-0.56 [20]	1.1-2.0 [043-079]		0.78-0.103 [031-041]				
	0.75-0.89 [18]	1.5-1.8 [059-071]		0.87-1.15 [034-045]				

 LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.







2. AMP & CERTI-CRIMP are trademarks.

 -1 IS A CERTICRIMP II HAND TOOL ASSEMBLY.
 -3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.

<small>THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION BY AMP INCORPORATED. ALL RIGHTS RESERVED. ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE.</small>		ENR J GULA 19FEB2002 CHK J GULA 19FEB2002 APD R SCHAFFNER 19FEB2002	AMP Tyco Electronics Harrisburg, PA 17105-3608
DIMENSIONS: mm 	TOLERANCES UNLESS OTHERWISE SPECIFIED: 8 PLS ± 7 PLS ± 6 PLS ± 5 PLS ± 4 PLS ± ANGLES ± FINISH -	PRODUCT SPEC APPLICATION SPEC WEIGHT CUSTOMER DRAWING	NAME CERTI-CRIMP II TOOL DATA SHEET .040 CT, EP, POWER DBL LOCK, & DRAWER CONTACTS SIZE A2 CASE CODE 00779 DRAWING NO. 1583010
MATERIAL: -		SCALE: -	SHEET 1 OF 2 REV A1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION. COPYRIGHT © BY AMP INCORPORATED. ALL RIGHTS RESERVED.


REV	DATE	DESCRIPTION	BY	CHK	APP
A	40	ADDED -3 HEAD SUB-ASSEMBLIES	JJG	RLS	

TOOL NUMBER	WIRE SIZE mm ² [AWG]	INSULATION DIAMETER mm [in.]	STRIP LENGTH mm [in.]	CRIMP HEIGHT mm [in.]	CONTACT PART NUMBERS		CONTACT DESCRIPTION	APPLICATION SPECIFICATION
					LOOSE PIECE	STRIP FORM		
 -1  -3	0.50-0.89 [20-18]	1.80-3.30 [.071-.130]	 3.8 ± 0.5 [.150 ± .020]	 $1.07-1.23$ [.042-.048]	 170485-[]	 170484-[]	DRAWER CONNECTOR CONTACTS	114-5044
	91590-1	1.25-1.42 [16]						
91591-1 91591-3	0.20-0.35 [24-22]	1.50-1.80 [.059-.071]	3.8 ± 0.5 [.150 ± .020]	0.87 ± 0.05 [.034 ± .002]	170313-[]	170311-[]	DRAWER CONNECTOR Contacts	114-5044
	91591-3	0.50-0.56 [20]						

⚠ LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER ; 1-800-722-1111.

2. AMP & CERTI-CRIMP are trademarks.

⚠ -1 IS A CERTICRIMP II HAND TOOL ASSEMBLY.
-3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.

<small>THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION. ALL RIGHTS RESERVED. IT IS SUBJECT TO CHANGE AND THE CONTROLLER FOR QUALITY ASSURANCE SHALL BE ADVISED OF ANY SUCH CHANGE.</small>		REV J. GULA 19FEB2002 DW J. GULA 19FEB2002 EDR B. SCHAEFER 19FEB2002	AMP Tyco Electronics Harrisburg, PA 17105-3400
DIMENSIONS (mm): 	TOLERANCES (UNLESS OTHERWISE SPECIFIED): D F.L.C. ± .01 F L.C. ± .01 D F.L.C. ± .01 D F.L.C. ± .01 F L.C. ± .01 ANGLES ± .5°	PRODUCT SPEC: - APPLICATION SPEC: - RETARY: -	NAME: CERTI-CRIMP II TOOL DATA SHEET .040, CT, EP, POWER DBL LOCK, & DRAWER CONTACTS SIZE: A2 DATE ISSUED: 00779 DRAWING NO: ©=1583010 SCALE: - SHEET: 2 OF 2 REV: A1
MATERIAL: - FINISH: -		CUSTOMER DRAWING	