

## 50N06

## Power MOSFET

50 Amps, 60 Volts  
N-CHANNEL POWER MOSFET

## ■ DESCRIPTION


The UTC **50N06** is three-terminal silicon device with current conduction capability of about 50A, fast switching speed. Low on-state resistance, breakdown voltage rating of 60V, and max threshold voltages of 4 volt.

It is mainly suitable electronic ballast, and low power switching mode power appliances.

## ■ FEATURES

- \*  $R_{DS(ON)} < 23m\Omega @ V_{GS} = 10 \text{ V}$
- \* Ultra low gate charge ( typical 30 nC )
- \* Low reverse transfer capacitance (  $C_{RSS} = \text{typical } 80 \text{ pF}$  )
- \* Fast switching capability
- \* 100% avalanche energy specified
- \* Improved dv/dt capability

## ■ SYMBOL



## ■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
50N06L-TA3-T	50N06G-TA3-T	TO-220	G	D	S	Tube
50N06L-TF3-T	50N06G-TF3-T	TO-220F	G	D	S	Tube
50N06L-TM3-T	50N06G-TM3-T	TO-251	G	D	S	Tube
50N06L-TN3-T	50N06G-TN3-T	TO-252	G	D	S	Tube
50N06L-TN3-R	50N06G-TN3-R	TO-252	G	D	S	Tape Reel
50N06L-TND-T	50N06G-TND-T	TO-252D	G	D	S	Tube
50N06L-TND-R	50N06G-TND-R	TO-252D	G	D	S	Tape Reel
50N06L-TQ2-T	50N06G-TQ2-T	TO-263	G	D	S	Tube
50N06L-TQ2-R	50N06G-TQ2-R	TO-263	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

50N06L-TA3-T	(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF3: TO-220F, TM3: TO-251, TN3: TO-252, TND: TO-252, TQ2: TO-263 (3) L: Lead Free, G: Halogen Free
--------------	--

### ■ ABSOLUTE MAXIMUM RATINGS

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V <sub>DSS</sub>	60	V
Gate-Source Voltage		V <sub>GSS</sub>	±20	V
Continuous Drain Current	T <sub>C</sub> = 25°C	I <sub>D</sub>	50	A
	T <sub>C</sub> = 100°C		35	A
Pulsed Drain Current (Note 2)		I <sub>DM</sub>	200	A
Avalanche Energy	Single Pulsed (Note 3)	E <sub>AS</sub>	480	mJ
	Repetitive (Note 2)	E <sub>AR</sub>	13	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	7	V/ns
Power Dissipation (T <sub>C</sub> =25°C)	TO-220/TO-263	P <sub>D</sub>	120	W
	TO-220F		70	W
	TO-251/TO-252		46	W
	TO-252D			
Junction Temperature		T <sub>J</sub>	+150	°C
Operation and Storage Temperature		T <sub>STG</sub>	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by T<sub>J</sub>

3. L=0.38mH, I<sub>AS</sub>=50A, V<sub>DD</sub>=25V, R<sub>G</sub>=20Ω, Starting T<sub>J</sub>=25°C

4. I<sub>SD</sub>≤50A, di/dt≤300A/μs, V<sub>DD</sub>≤BV<sub>DSS</sub>, Starting T<sub>J</sub>=25°C

### ■ THERMAL DATA

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	TO-220/TO-220F TO-263	θ <sub>JA</sub>	62	°C/W
	TO-251/TO-252 TO-252D		100	°C/W
Junction to Case	TO-220	θ <sub>JC</sub>	1.24	°C/W
	TO-220F		1.78	°C/W
	TO-251/TO-252		2.7	°C/W
	TO-263		1.24	°C/W

■ ELECTRICAL CHARACTERISTICS ( $T_c = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>OFF CHARACTERISTICS</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$V_{\text{GS}} = 0 \text{ V}, I_D = 250 \mu\text{A}$	60			V
Drain-Source Leakage Current	$I_{\text{DSS}}$	$V_{\text{DS}} = 60 \text{ V}, V_{\text{GS}} = 0 \text{ V}$		10		$\mu\text{A}$
Gate-Source Leakage Current	Forward	$V_{\text{GS}} = 20\text{V}, V_{\text{DS}} = 0 \text{ V}$		100		nA
	Reverse	$V_{\text{GS}} = -20\text{V}, V_{\text{DS}} = 0 \text{ V}$		-100		nA
Breakdown Voltage Temperature Coefficient	$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	$I_D = 250 \mu\text{A}$ , Referenced to $25^\circ\text{C}$		0.07		$\text{V}/^\circ\text{C}$
<b>ON CHARACTERISTICS</b>						
Gate Threshold Voltage	$V_{\text{GS(TH)}}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250 \mu\text{A}$	2.0		4.0	V
Static Drain-Source On-State Resistance	$R_{\text{DS(ON)}}$	$V_{\text{GS}} = 10 \text{ V}, I_D = 25 \text{ A}$		18	23	$\text{m}\Omega$
<b>DYNAMIC CHARACTERISTICS</b>						
Input Capacitance	$C_{\text{ISS}}$	$V_{\text{GS}} = 0 \text{ V}, V_{\text{DS}} = 25 \text{ V}$ $f = 1\text{MHz}$		900	1220	pF
Output Capacitance	$C_{\text{OSS}}$			430	550	pF
Reverse Transfer Capacitance	$C_{\text{RSS}}$			80	100	pF
<b>SWITCHING CHARACTERISTICS</b>						
Turn-On Delay Time	$t_{\text{D(ON)}}$	$V_{\text{DD}} = 30\text{V}, I_D = 25 \text{ A}$ , $R_G = 50\Omega$ (Note 1, 2)		40	60	ns
Turn-On Rise Time	$t_R$			100	200	ns
Turn-Off Delay Time	$t_{\text{D(OFF)}}$			90	180	ns
Turn-Off Fall Time	$t_F$			80	160	ns
Total Gate Charge	$Q_G$	$V_{\text{DS}} = 48\text{V}, V_{\text{GS}} = 10 \text{ V}$ $I_D = 50\text{A}$ (Note 1, 2)		30	40	nC
Gate-Source Charge	$Q_{\text{GS}}$			9.6		nC
Gate-Drain Charge	$Q_{\text{GD}}$			10		$\mu\text{C}$
<b>DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS</b>						
Drain-Source Diode Forward Voltage	$V_{\text{SD}}$	$I_S = 50\text{A}, V_{\text{GS}} = 0 \text{ V}$			1.5	V
Maximum Continuous Drain-Source Diode Forward Current	$I_S$				50	A
Maximum Pulsed Drain-Source Diode Forward Current	$I_{\text{SM}}$				200	A
Reverse Recovery Time	$t_{\text{RR}}$	$I_S = 50\text{A}, V_{\text{GS}} = 0 \text{ V}$ $dI_F/dt = 100 \text{ A}/\mu\text{s}$		54		ns
Reverse Recovery Charge	$Q_{\text{RR}}$			81		$\mu\text{C}$

Notes: 1. Pulse Test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$ 

2. Essentially independent of operating temperature

■ TEST CIRCUITS AND WAVEFORMS




Fig. 1A Peak Diode Recovery dv/dt Test Circuit




Fig. 1B Peak Diode Recovery dv/dt Waveforms

■ TEST CIRCUITS AND WAVEFORMS (Cont.)




Fig. 2A Switching Test Circuit




Fig. 2B Switching Waveforms




Fig. 3A Gate Charge Test Circuit




Fig. 3B Gate Charge Waveform




Fig. 4A Unclamped Inductive Switching Test Circuit















Fig. 4B Unclamped Inductive Switching Waveforms

■ TYPICAL CHARACTERISTICS



## ■ TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.

