

INDUSTRIAL GRADE BUILT-IN CAPACITANCE CERAMIC RESONATOR

AWSCR



4.7 x 4.1 x 1.2 mm

AWSCR-MG

Pb in ceramic
(exempt per RoHS 2002/95/EC Annex (7))

RoHS
Compliant

FEATURES:

- Low resonant impedance
- High stability type
- Excellent environmental resistance
- Reflow capable
- Industrial grade
- Built-in load capacitance

APPLICATIONS:

- Remote controls, Microprocessor clocks, Mobile phones, DVD & CD-Roms, Electric appliances, Industrial controllers

ELECTRICAL CHARACTERISTICS:

Item	Requirement
Oscillation Frequency (Fosc)	2.00~8.00 MHz±0.5%
Resonant Impedance (Ro)	See Table 2.1
Frequency Tolerance and stability	See Table 2.2
Withstanding Voltage (V)	50 (DC , 1 min)
Rating Voltage	
(1) D.C. Voltage	6 V.D.C. max
(2) A.C. Voltage	15 Vp-p. max
Insulation Resistance	100MΩ min. (at 10 VDC)
Operation Temperature	-20°C to +85°C
Storage Temperature	-55°C to +85°C
Aging Rate (Fosc)	±0.3% max. (10 years)

TEST CIRCUIT:

Parts shall be measured under a condition (Temp.: 20±15°C, Humidity: 65±20% R.H.) unless the standard condition (Temp: 25±3°C, Humidity: 65±5% R.H.) is regulated to measure




TABLE 2.1

Freq (MHz)	Zr max. (ohms)
2 - 2.99	100
3.0 - 3.49	50
3.5 - 8.00	30

TABLE 2.2

Part Number (XX.XX denotes freq. in MHz)	Frequency Tolerance at 25°C	Frequency Stability at -20°C to +80°C	Aging in 10 years	Operating temperature
AWSCR-XX.XXMGS 2.0 MHz - 8.00 MHz	± 0.5%	± 0.3%	± 0.3%	-25° to +85°C
AWSCR-XX.XXMGD 2.0 MHz - 8.00 MHz	± 0.5%	± 0.3% ± 0.5% (-40C to 85C)	± 0.3%	-40° to +85°C
AWSCR-XX.XXMGA 2.0 MHz - 8.00 MHz	± 0.5%	± 0.3% ± 0.7% (-40C to 125C)	± 0.3%	-40° to +125°C

OPTIONS & PART IDENTIFICATION:

[Left blank if standard]

AWSCR - XX.XXMGY - Packaging

XX.XX: Frequency in MHz

Y : S,D or A

INDUSTRIAL GRADE BUILT-IN CAPACITANCE CERAMIC RESONATOR

AWSCR




4.7 x 4.1 x 1.2 mm

AWSCR-MG

Pb in ceramic
(exempt per RoHS 2002/95/EC Annex (7))

RoHS
Compliant

OUTLINE DRAWING:



TAPE & REEL: Tape and reel 4,000pcs/reel

