

SFF130

14849 Firestone Boulevard · La Mirada, CA 90638
 Phone: (714) 670-SSDI (7734) · Fax: (714) 522-7424


Designer's Data Sheet

**14 AMP
 100 VOLTS
 0.16 Ω
 N-CHANNEL
 POWER MOSFET**

FEATURES:

- Rugged construction with poly silicon gate
- Low RDS(on) and high transconductance
- Excellent high temperature stability
- Very fast switching speed
- Fast recovery and superior dv/dt performance
- Increased reverse energy capability
- Low input and transfer capacitance for easy paralleling
- Hermetically sealed power surface mount package
- TX, TXV and Space Level screening available
- Replaces: IRF130 Types

MILPACK




MAXIMUM RATINGS:

CHARACTERISTIC	SYMBOL	VALUE	UNIT
Drain to Source Voltage	V _{DS}	100	Volts
Gate to Source Voltage	V _{GS}	± 20	Volts
Continuous Drain Current @ TC=25°C @ TC=100°C	I _D	14 9	Amps
Operating and Storage Temperature	T _{OP} & T _{STG}	-55 to +150	°C
Thermal Resistance, Junction to Case	R _{θJC}	2	°C/W
Total Device Dissipation @ TC=25°C Total Device Dissipation @ TC=55°C	P _D	63 48	Watts

PACKAGE OUTLINE: MILPACK

PIN OUT:
 DRAIN: PIN 1
 SOURCE: PIN 2
 GATE: PIN 3



NOTE: All specifications are subject to change without notification. SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: F00017 C

MED

