


1	FG	11	DB1
2	VSS	12	DB2
3	VDD	13	DB3
4	VO	14	DB4
5	WR	15	DB5
6	RD	16	DB6
7	CE	17	DB7
8	C/D	18	FS
9	RST	19	A
10	DB0	20	K



DETAIL A:

NOTES:

- | | |
|---------------------------------|------------------------|
| 1. DISPLAY TYPE: | STN/YELLOW-GREEN MODE |
| 2. VIEWING DIRECTION: | 6:00 |
| 3. POLARIZER MODE: | TRANSFLECTIVE/POSITIVE |
| 4. DRIVE METHOD: | 1/128 DUTY 1/12 BIAS |
| 5. OPERATING TEMP: | -20°C--+70C |
| 6. STORAGE TEMP: | -30°C--+80C |
| 7. LCD OPERATING VOLTAGE: | 18.0V |
| 8. WITH LED BACKLIGHT | |
| 9. CONTROLLER: | T6963C |
| 10. UNMARKED TOLERANCES: | ±0.3mm |
| 11. BEZEL IS TO BE PAINED BLACK | |



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM128128BBCW	
CHECKED BY:	DWG NO: G-2	
APPROVED BY:	DWG NAME: TM128128BBCWG-2	UNIT: mm
CONFIRMED BY:	SHEET NO: OF	