

Part/Keyword Search



Detailed Drawing



Printer Friendly Datasheet


TM5119 / SM5119*

* Part number for additional environmental screening.


Performance Data

Frequency	5.0 - 500.0 MHz
Gain	15.5 dB Typical 14.0 dB Min
Noise Figure	2.2 dB Typical 3.0 dB Max
P _{1dB}	16.0 dBm Typical 14.0 dBm Min
3 rd Order Intercept	32.0 dBm Typical
2 nd Order Intercept	44.0 dBm Typical
VSWR	1.8/2.0 Input Typ/Max 1.8/2.0 Output Typ/Max
Reverse Isolation	-19.0 dB Typical -18.0 dB Min
Power Supply	15.0 Volts 30.0 mA
Operating Temperature	-55.0 - 85.0 °C


Package Drawing



Gain



Noise Figure



Products

Amplifiers

VCOs

Limiting Amplifiers

Switches

Linearizers

Limiters


Analog Attenuators

Digital Attenuators

Detectors


Frequency (MHz)

P_{1dB} Compression Point




Frequency (MHz)

Reverse Isolation




Frequency (MHz)

Input VSWR



Frequency (MHz)

Output VSWR



Frequency (MHz)

S-Parameters

Frequency	S11 Mag	S11 Ang	S21 Mag	S21 Ang	S12 Mag	S12 Ang	S22 Mag	S22 Ang
5.0	0.110	-57.00	5.840	-164.00	0.090	-163.00	0.260	-14.00
50.0	0.050	-29.00	6.000	169.00	0.090	168.00	0.240	-12.00
100.0	0.060	-41.00	6.000	157.00	0.100	151.00	0.230	-22.00
200.0	0.110	-66.00	6.040	132.00	0.100	123.00	0.190	-44.00
300.0	0.180	-100.00	6.130	106.00	0.110	98.00	0.120	-77.00
400.0	0.230	-139.00	6.120	78.00	0.110	75.00	0.050	-150.00
500.0	0.260	178.00	5.890	48.00	0.110	52.00	0.120	104.00

Absolute Maximum Conditions

Maximum Operating Temperature	-55.0 - 100.0 °C	Maximum Storage Temperature	-62.0 - 125.0 °C
Maximum Case Temperature	125.0 °C	Maximum Supply Voltage	18.0 Volts
Continuous RF Input Power	13.0 dBm	Short Term RF Input Power (1 minute max)	50.0 mW
Maximum Peak Power (3 µsec max)	0.5 W		

Amplifonix | 2707 Black Lake Place | Philadelphia, PA 19154
Tel: 215.464.4000 | FAX: 215.464.4001 | Email: info@amplifonix.com

i2 Technologies US, Inc.

HTML Pages converted to PDF Document

This document contain component information from the manufacturer's website which are not available in a revision controlled document from the manufacturer. To facilitate the addition of these parts into the Electronics Database, we are converting the HTML pages related to that part, from the manufacturer's website into Adobe PDF format. The contents of this document is based on the information provided on the manufacturer's website, therefore the information may have been changed by the manufacturer since this was created.

