


SURFACE MOUNT MONOLITHIC CRYSTAL FILTER



7.2 x 5.2 x 1.5mm

ASCF45U



FEATURES:

- Surface-mount ceramic package.
- IR-reflow.
- Excellent attenuation bandwidth.
- Low height.(1.5mm max.)

APPLICATIONS:

- Mobile communication systems.
- Pagers.
- Cellular and cordless phones.
- Radios

ELECTRICAL SPECIFICATIONS:

ABRACON P/N:	ASCF45U
Center frequency:	45.0MHz
Operation mode:	Fundamental
Operating temperature:	- 20°C to + 70°C

P/N	Passband		Stopband		Ripple	Loss	Termination Z	Pole	Case quantity
	dB	kHz	dB	kHz	dB	dB	(Ω//pF)	----	----
ASCF45U8	3	±3.75	20	±25	1	2.5	650//3.5	2	1
ASCF45U12	3	±6.00	15	±20	1	2.5	650//5.0	2	1
ASCF45U15	3	±7.50	15	±25	1	2.5	650//3.5	2	1
ASCF45U30	3	±15.0	15	±60	1	2.5	800//1.5	2	1

OPTIONS & PART IDENTIFICATION:


(Left blank if standard)

ASCF45U□□ - □


P/N
8
12
15
30

Packaging	
T	Tape and Reel

REFLOW PROFILE:



SURFACE MOUNT MONOLITHIC CRYSTAL FILTER




ASCF45U

7.2 x 5.2 x 1.5mm


ASCF45U



OUTLINE DIMENSIONS:



TAPE & REEL: T= tape and reel (1,000pcs/reel)



NOTE: Abracon manufactured products are intended for general commercial and industrial use. For applications requiring high reliability and/or presenting extreme operating environment, written consent & authorization from Abracon is required.



Visit www.abracon.com for Terms & Conditions of Sale **Revised: 12.30.09**
 30332 Esperanza, Rancho Santa Margarita, California 92688
 tel 949-546-8000 | fax 949-546-8001 | www.abracon.com