

TECHNICAL DATA
DATA SHEET 5406, REV. -

HERMETIC RAD HARD POWER MOSFET

FEATURES:

- Low RDS(on)
- Single Event Effect (SEE) hardened,
 - LET 85, Range: 118 μ m
 - VGS = -10V, VDS = 250V
 - VGS = -15V, VDS = 120V
 - LET 55, Range: 90 μ m
 - VGS = -15V, VDS = 250V
 - VGS = -20V, VDS = 160V
- Total Ionization Dose (TID) hardened, 100kRad
- Isolated TO-257 package
- Near equivalent to IRHYS67234CM

MAXIMUM RATINGS

ALL RATINGS ARE AT T_C = 25°C UNLESS OTHERWISE SPECIFIED.


RATING	SYMBOL	MIN.	TYP.	MAX.	UNITS
DRAIN TO SOURCE VOLTAGE	V _{DS}	-	-	250	Volts
GATE TO SOURCE VOLTAGE	V _{GS}	-	-	±20	Volts
ON-STATE DRAIN CURRENT (T _C = 25°C)	I _D	-	-	12.4	Amps
ON-STATE DRAIN CURRENT (T _C = 100°C)	I _D	-	-	8	Amps
PULSED DRAIN CURRENT (LIMITED BY T _{JMAX})	I _{DM}	-	-	50	Amps
OPERATING AND STORAGE TEMPERATURE	T _{OP} /T _{STG}	-55	-	+150	°C
TOTAL DEVICE DISSIPATION	P _D	-	-	75	Watts
THERMAL RESISTANCE, JUNCTION TO CASE	R _{thJC}	-	-	1.66	°C/W
SINGLE PULSE AVALANCHE (LIMITED BY T _{JMAX})	E _{AS}	-	60	-	mJ

ELECTRICAL CHARACTERISTICS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNITS
DRAIN SOURCE BREAKDOWN V _{GS} = 0V, I _D = 250 μ A	B _{VDS}	250	-	-	Volts
STATIC DRAIN TO SOURCE ON STATE RESISTANCE V _{GS} = 10V, I _D = 8A	R _{DS(ON)}	-	-	0.13	Ω
GATE THRESHOLD VOLTAGE V _{DS} = V _{GS} , I _D = 1mA	V _{GS(th)}	2.0	-	4.0	Volts
ZERO GATE VOLTAGE DRAIN CURRENT V _{DS} = 200V, V _{GS} = 0V	I _{DSS}	-	-	25	μ A
GATE TO SOURCE LEAKAGE FORWARD V _{GS} = 20V	I _{GSS}	-	-	100	nA
GATE TO SOURCE LEAKAGE REVERSE V _{GS} = -20V		-	-	-100	
TURN ON DELAY TIME V _{DD} = 0.5V _{DS} , I _D = 8A,	t _{d(ON)}	-	-	25	nsec
RISE TIME	t _r	-	-	25	
TURN OFF DELAY TIME R _G = 4.7 Ω	t _{d(OFF)}	-	-	35	
FALL TIME	t _f	-	-	20	
DIODE FORWARD VOLTAGE I _S = 12.4A	V _{SD}	-	-	1.2	Volts
REVERSE RECOVERY TIME I _f = 12.4A, di/dt = 100A/ μ s	t _{rr}	-	-	400	nsec
INPUT CAPACITANCE V _{GS} = 0 V	C _{iss}	-	1600	-	pF
OUTPUT CAPACITANCE V _{DS} = 100 V	C _{oss}	-	120	-	
REVERSE TRANSFER CAPACITANCE f = 1.0MHz	C _{rss}	-	3	-	
TOTAL GATE CHARGE V _{DD} = 0.5V _{DS} , I _D = 12.4A, V _{GS} = 10V	Q _G	-	-	42	nC

TECHNICAL DATA
DATA SHEET 5406, REV. -

MECHANICAL DIMENSIONS: in Inches / mm



TO-257

DEVICE TYPE	PIN-1	PIN-2	PIN-3
N-CHANNEL MOSFET TO-257 PACKAGE	DRAIN	SOURCE	GATE

****NOTE:** This product is subject to the International Traffic in Arms Regulations (ITAR), 22 C.F.R. Parts 120 - 130, and may not be exported without the appropriate U.S. Department of State authorization.

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.