****TELEDYNE MEC**

11361 Sunrise Park Drive, Rancho Cordova, Calif. 95742-6587 Telephone (916) 638-3344 Fax (916) 636-7453 This model number is controlled by the International Traffic in Arms Regulations, and can only be exported via a U.S. Department of State export license. They may not be transferred, transshipped on a non-continuous voyage, or otherwise be disposed of in any other country, either in their original form or after being incorporated into other end-items, without the prior written approval of the U.S. Department of State.

MODEL NO. MEC 5411 (GR) MEC 5412 (FE)

6.5 to 18.0 GHz

TYPI	CAL ()PEF	rating con	POWER SUPPLY REQUIREMENTS			
ELEMENT		VOLTAGE	CURRENT	VOLTAGE MIN	VOLTAGE MAX	CURRENT MAX	
HEATER		-6.3 Vdc	1.6 A	-6.0 Vdc	-6.6 Vdc	2 A	
HELIX	W/	RF	GROUND	8 mA	GROUND		15 mA
	W/O	RF	GROUND	2 mA			
FE ON		-25 Vdc	0.1 mA	0	-75 Vdc	1 mA	
FE OFF		-1300 Vdc	0.1 mA	-1500 Vdc	-1700 Vdc	1 mA	
GRID ON			200 Vdc	1 mA	125 Vdc	250 Vdc	10 mA
GRID OFF		-200 Vdc	0.1 mA	-200 Vdc	-500 Vdc	1 mA	
CATHODE (Ek)		-10.3 kV	290 mA	-10 kV	-10.5 kV	300 mA	
COLLEC	TOR	#1	5.36 kV	50 mA	52% x E	k ± 2%	100 mA
W/R	F	#2	3.71 kV	232 mA	36% x Ek ± 2%		300 mA

NOTE 1: CATHODE VOLTAGE IS MEASURED WITH RESPECT TO GROUND.

NOTE 2: HEATER, COLLECTOR, GRID OR FOCUS ELECTRODE (FE) VOLTAGES ARE MEASURED WITH RESPECT TO CATHODE.

SELECTED PERFORMANCE	TYPICAL	SPECIFIED
INPUT VSWR	2:1	2.5:1
OUTPUT VSWR	2:1	2.25:1
MAXIMUM DUTY		CW
FE CAPACITANCE	50 pF	65 pF
GRID CAPACITANCE	37 pF	50 pF
MIN HARMONIC SEPARATION	-7 dBc	-5 dBc *
NOISE POWER DENSITY	-15 dBm/MHz	-10 dBm/MHz
PRIME POWER	1221 W	1400 W
TEMPERATURE RANGE	-40° to 85°C	

RF PERFORMANCE							
FREQ GHz	TYP SAT POWER OUTPUT (WATTS)	MIN SPEC POWER OUTPUT (WATTS)	TYP GAIN AT SPEC POWER dB				
6.5	310	300 *	35				
7.0	325	300	38				
8.0	350	300	41				
9.0	350	300	43				
10.0	325	300	45				
11.0	350	300	45				
12.0	375	300	45				
13.0	375	300	45				
14.0	375	300	45				
15.0	365	300	43				
16.0	350	300	41				
17.0	340	300	38				
18.0	325	300	35				

TYPICAL POWER OUTPUT IS SHOWN TO ILLUSTRATE CAPABILITY.

GAIN IS WITH EQUALIZER.

An ISO 9001:2000 Quality System Certified Company

01/06