


# CTCMD5D13F Series

From 3.3  $\mu\text{H}$  to 47  $\mu\text{H}$



## SPECIFICATIONS

Parts are available in  $\pm 20\%$  inductance tolerance only.  
\*Rated Current: Inductance drop = 35% typ.

Part Number	Inductance ( $\mu\text{H} \pm 20\%$ )	L Test Freq. (kHz)	DCR Max. ( $\Omega$ )	Rated Current* Max. (A)
CTCMD5D13F-3R3M	3.3	100	0.081	1.25
CTCMD5D13F-4R7M	4.7	100	0.106	1.20
CTCMD5D13F-6R8M	6.8	100	0.144	0.90
CTCMD5D13F-100M	10	100	0.187	0.85
CTCMD5D13F-150M	15	100	0.300	0.57
CTCMD5D13F-220M	22	100	0.431	0.54
CTCMD5D13F-330M	33	100	0.637	0.28
CTCMD5D13F-470M	47	100	0.875	0.35

## PHYSICAL DIMENSIONS

Size	A Max.	B Max.	C Max.	D	E	F	G
mm	5.8	7.4	1.5	6.0	0.6	4.2	4.5
inches	0.228	0.291	0.059	0.236	0.024	0.165	0.177

## CHARACTERISTICS

**Description:** SMD power inductor

**Applications:** Power supplies for VTR, OA equipment, LCD televisions, PC notebooks, portable communication equipment, DC/DC converters, etc.

**Operating Temperature:**  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$

**Inductance Tolerance:**  $\pm 20\%$

**Testing:** Tested on a HP4285A at 100 KHz , 0.1V

**Packaging:** Tape & Reel



**Marking:** Parts are marked with inductance code

**Miscellaneous:** RoHS Compliant

**Additional Information:** Additional electrical & physical information available upon request

**Samples available. See website for ordering information.**

## PAD LAYOUT



06.06.13