



RNB ¹		0.2G	0.2K	0.4G	0.4K	0.8G	0.8K	1.6G	1.6K
Static Torque [ft-lbs / N-m]		1.5 / 2		3 / 4		5.9 / 8		12 / 16	
Coil (20°C)	Voltage [DC-V]	24	90	24	90	24	90	24	90
	Current [A]	0.41	0.11	0.54	0.14	0.63	0.17	0.76	0.2
	Resistance [Ω]	59	815	45	630	38	540	32	445
	Wattage [W]	10		13		15		18	
Armature	Pull-In Time [ms]	35		45		55		70	
	Release Time [ms]	12		12		15		25	
Max Allowable Speed [rpm]		5000		4000		4000		3500	
Moment of Inertia (J) [kg-cm ²]		0.185		0.325		0.675		2.85	
Bore [mm]		dH7		12		12		14	
Key Way [mm]		bE9		4		4		5	
		t _{+0.15/-0}		13.5		13.5		16	
Dimensions [mm]		A		77		85		97	
		B		68		74		85	
		Ch9		77		85		97	
		D		3		4		4	
		E		20		20		25	
		F		4.5		5.5		5.5	
		G		10		11		11	
		L		30		32		35	
		M		25.5		27.5		29.5	
		N		15		16		17	
		P		18		16		14	
Q		8		12		16			
R		7		7.5		8.5			
S		0.15~0.3		0.15~0.3		0.15~0.3		0.15~0.3	
Weight [lbs / kg]		1.3 / 0.6		1.9 / 0.9		2.6 / 1.2		4.2 / 1.9	

[Note 1 : For holding and emergency-stop applications only]

[1 inch = 25.4 mm]