


PIN OUT

P1	WIRE COLOR	P2
1	ORANGE/WHITE	1
2	ORANGE	2
3	GREEN/WHITE	3
6	GREEN	6
4	BLUE	4
5	BLUE/WHITE	5
7	BROWN/WHITE	7
8	BROWN	8



Material:

- Conductor: 26AWG 7*0.16±0.015mm
- Conductor Insulation color coding: (1)White/Orange, (1)Orange, (1)White/Green, (1)Green, (1)Blue, (1)White/Blue, (1)White/Brown, (1)Brown
- Included printing on cable jacket: *CM (UL) C(UL) 4P 26AWG UTP CAT.6 PATCH CABLE ISO/IEC & EN & ANSI/TIA-568-C.2*
- Cable Assembly: White cable tie, Wiring T568B color, Plug RJ45 8P8C 3μ pc UL 94V-2
- Cable Jacket color: Grey
- Length: L±3%
 • Dielectric strength: 2.5KV dc-2seconds
 • Working temperatures: -20°C~60°C

Order Code: A-MCU60xxx-R
 Order lengths in meter: 0.5,1,2,3,5,7,10,15,20,30

Unit: mm



Scale					Date	Name	Title
TOLERANCE					Drawn	20.02.13	Wilson
X.	±X				Approved	20.02.13	Groll
X.X	±X						
X.XX	±X						
DIM	TOL						Drawing-No. rev01
X.°	±X°						
X.X°	±X°	①	Update	20.02.13			
Angle	TOL	Id.	Modification	Date	Name	Replace Sheet 1/1	

Title: Cat6 UTP Patch cable 26AWG, Grey
 ASSMANN WSW-No. A-MCU60xxx-R
 Drawing-No.
 rev01
 Sheet 1/1