


## HFS634 250V N-Channel MOSFET

### FEATURES

- Originative New Design
- Superior Avalanche Rugged Technology
- Robust Gate Oxide Technology
- Very Low Intrinsic Capacitances
- Excellent Switching Characteristics
- Unrivalled Gate Charge : 30 nC (Typ.)
- Extended Safe Operating Area
- Lower  $R_{DS(ON)}$  : 0.36 Ω (Typ.) @ $V_{GS}=10V$
- 100% Avalanche Tested

$BV_{DSS} = 250 V$   
 $R_{DS(on)\ typ} = 0.36 \Omega$   
 $I_D = 8.1 A$



### Absolute Maximum Ratings $T_C=25^\circ C$ unless otherwise specified

Symbol	Parameter	Value	Units
$V_{DSS}$	Drain-Source Voltage	250	V
$I_D$	Drain Current – Continuous ( $T_C = 25^\circ C$ )	8.1*	A
	Drain Current – Continuous ( $T_C = 100^\circ C$ )	5.1*	A
$I_{DM}$	Drain Current – Pulsed (Note 1)	32.4*	A
$V_{GS}$	Gate-Source Voltage	$\pm 30$	V
$E_{AS}$	Single Pulsed Avalanche Energy (Note 2)	200	mJ
$I_{AR}$	Avalanche Current (Note 1)	8.1	A
$E_{AR}$	Repetitive Avalanche Energy (Note 1)	7.4	mJ
$dv/dt$	Peak Diode Recovery $dv/dt$ (Note 3)	5.5	V/ns
$P_D$	Power Dissipation ( $T_C = 25^\circ C$ )	38	W
	– Derate above $25^\circ C$	0.3	W/ $^\circ C$
$T_J, T_{STG}$	Operating and Storage Temperature Range	-55 to +150	$^\circ C$
$T_L$	Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	300	$^\circ C$

\* Drain current limited by maximum junction temperature

### Thermal Resistance Characteristics

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case	--	3.29	$^\circ C/W$
$R_{\theta JA}$	Junction-to-Ambient	--	62.5	

**Electrical Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

**On Characteristics**

$V_{GS}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$ , $I_D = 250 \mu\text{A}$	2.0	--	4.0	V
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS} = 10 \text{ V}$ , $I_D = 4.05 \text{ A}$	--	0.36	0.45	$\Omega$

**Off Characteristics**

$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}$ , $I_D = 250 \mu\text{A}$	250	--	--	V
$\Delta BV_{DSS} / \Delta T_J$	Breakdown Voltage Temperature Coefficient	$I_D = 250 \mu\text{A}$ , Referenced to $25^\circ\text{C}$	--	0.27	--	$\text{V}/^\circ\text{C}$
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 250 \text{ V}$ , $V_{GS} = 0 \text{ V}$	--	--	1	$\mu\text{A}$
		$V_{DS} = 200 \text{ V}$ , $T_C = 125^\circ\text{C}$	--	--	10	$\mu\text{A}$
$I_{GSSF}$	Gate-Body Leakage Current, Forward	$V_{GS} = 30 \text{ V}$ , $V_{DS} = 0 \text{ V}$	--	--	100	nA
$I_{GSSR}$	Gate-Body Leakage Current, Reverse	$V_{GS} = -30 \text{ V}$ , $V_{DS} = 0 \text{ V}$	--	--	-100	nA

**Dynamic Characteristics**

$C_{iss}$	Input Capacitance	$V_{DS} = 25 \text{ V}$ , $V_{GS} = 0 \text{ V}$ , $f = 1.0 \text{ MHz}$	--	780	1000	pF
$C_{oss}$	Output Capacitance		--	95	125	pF
$C_{rss}$	Reverse Transfer Capacitance		--	20	25	pF

**Switching Characteristics**

$t_{d(on)}$	Turn-On Time	$V_{DS} = 125 \text{ V}$ , $I_D = 8.1 \text{ A}$ , $R_G = 25 \Omega$  (Note 4,5)	--	15	30	ns
$t_r$	Turn-On Rise Time		--	75	150	ns
$t_{d(off)}$	Turn-Off Delay Time		--	100	200	ns
$t_f$	Turn-Off Fall Time		--	65	130	ns
$Q_g$	Total Gate Charge	$V_{DS} = 200 \text{ V}$ , $I_D = 8.1 \text{ A}$ , $V_{GS} = 10 \text{ V}$  (Note 4,5)	--	30	38	nC
$Q_{gs}$	Gate-Source Charge		--	4.0	--	nC
$Q_{gd}$	Gate-Drain Charge		--	15	--	nC

**Source-Drain Diode Maximum Ratings and Characteristics**

$I_S$	Continuous Source-Drain Diode Forward Current	--	--	8.1	A	
$I_{SM}$	Pulsed Source-Drain Diode Forward Current	--	--	32.4		
$V_{SD}$	Source-Drain Diode Forward Voltage	$I_S = 8.1 \text{ A}$ , $V_{GS} = 0 \text{ V}$	--	--	1.5	V
$trr$	Reverse Recovery Time	$I_S = 8.1 \text{ A}$ , $V_{GS} = 0 \text{ V}$ $dI_F/dt = 100 \text{ A}/\mu\text{s}$ (Note 4)	--	170	--	ns
$Qrr$	Reverse Recovery Charge		--	0.9	--	$\mu\text{C}$

**Notes :**

- Repetitive Rating : Pulse width limited by maximum junction temperature
- $L=4.9\text{mH}$ ,  $I_{AS}=8.1\text{A}$ ,  $V_{DD}=50\text{V}$ ,  $R_G=25\Omega$ , Starting  $T_J=25^\circ\text{C}$
- $I_{SD}\leq 8.1\text{A}$ ,  $di/dt\leq 300\text{A}/\mu\text{s}$ ,  $V_{DD}\leq BV_{DSS}$ , Starting  $T_J=25^\circ\text{C}$
- Pulse Test : Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$
- Essentially Independent of Operating Temperature

## Typical Characteristics




Figure 1. On Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On Resistance Variation vs. Drain Current and Gate Voltage




Figure 4. Body Diode Forward Voltage Variation with Source Current and Temperature




Figure 5. Capacitance Characteristics






Figure 6. Gate Charge Characteristics


## Typical Characteristics (continued)




**Figure 7. Breakdown Voltage Variation  
vs Temperature**




**Figure 8. On-Resistance Variation  
vs Temperature**



**Figure 9. Maximum Safe Operating Area**



**Figure 10. Maximum Drain Current  
vs Case Temperature**



**Figure 11. Transient Thermal Response Curve**

Fig 12. Gate Charge Test Circuit &amp; Waveform




Fig 13. Resistive Switching Test Circuit &amp; Waveforms




Fig 14. Unclamped Inductive Switching Test Circuit &amp; Waveforms








Fig 15. Peak Diode Recovery dv/dt Test Circuit &amp; Waveforms



## Package Dimension

TO-220F

