


TUV MANAGEMENT SERVICE PARTIES



An ISO/TS 16949, ISO 9001 and ISO 14001 Certified Company

SILICON EPITAXIAL POWER TRANSISTORS



BD131 NPN BD132 PNP

TO-126 Plastic Package

General Purpose Medium Power Applications

ABSOLUTE MAXIMUM RATINGS

DESCRIPTION	SYMBOL	BD131	BD132	UNIT
Collector -Base Voltage	V_{CBO}	70	45	V
Collector -Emitter Voltage	V_{CEO}	45	45	V
Emitter-Base Voltage	V_{EBO}	6	4	V
Collector Current Continuous	I _C		3	А
Peak	I _{CM}	6		А
Base Current Peak	I _{BM}	0.5		А
Reverse Base Current Peak	-I _{BM}	0.5		А
Total Device Dissipation upto T _{amb} =60°C	P _{tot}	15		W
Junction Temperature	T _j	150		°C
Storage Temperature Range	T _{stg}	-65 to +150		

Thermal Resistance

From Junction to Mounting Base	$R_{th(j-mb)}$	6	K/W	
--------------------------------	----------------	---	-----	--

ELECTRICAL CHARACTERISTICS (T_a=25°C unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION		MAX	UNIT
Collector Cut-off Current		V _{CB} =50V _, I _E =0 BD13 1		50	nA
	1	$V_{CB}=40V_{,}I_{E}=0$ BD132	2	50	nA
	I _{CBO}	$V_{CB}=50V_{,}I_{E}=0, Tj = 150^{\circ}C$ BD13 1		10	μΑ
		$V_{CB}=40V_{,}I_{E}=0, Tj = 150^{\circ}C$ BD132	2	10	μΑ
Emitter Cut-off Current	I _{EBO}	$V_{EB} = 5V_{,} I_{C} = 0$ BD13 1		50	nA
		$V_{EB}=3V_{,}I_{C}=0$ BD132	2	50	nA
Collector-Emitter Saturation Voltage	V _{CE(sat)}	$I_{C} = 0.5A, I_{B} = 50mA$		0.3	V
		$I_{C} = 2A, I_{B} = 200mA$		0.7	V
Base-Emitter Saturation Voltage	V _{BE(sat)}	$I_{C} = 0.5A, I_{B} = 50mA$		1.2	V
		$I_C = 2A, I_B = 200mA$		1.5	V
DC Current Gain	h _{FE}	$V_{CE} = 12V, I_{C} = 0.5A$	40		
	''FE	$V_{CE} = 1V$, $I_C = 2A$	20		


Dynamic Characteristics

	1				
Collector Capacitance	C_C	$I_E = 0$, $V_{CB} = 5V$, $f = 1MHz$ BD131		60	pF
Transition Frequency	f _T	$I_{C} = 0.25A, V_{CE} = 5V, f = 35MHz,$ $T_{amb} = 25^{\circ}C$	60		MHz
DC Current Gain Ratio of the Complementary Pairs	h _{FE1} /h _{FE2}	$V_{CE} = 12V, I_{C} = 0.5A$		1.2	

BD131_132Rev_1 120403D


TO-126 Plastic Package

TO-126 (SOT-32) Plastic Package



•	,			
DIM	MIN	MAX		
А	7.4	7.8		
В	10.5	10.8		
С	2.4	2.7		
D	0.7	0.9		
E	2.25 TYP.			
F	0.49	0.75		
G	4.5 TYP.			
L	15.7 TYP.			
М	1.27 TYP.			
N	3.75 TYP.			
Р	3.0	3.2		
S	2.5 TYP.			
	•			


All dimensions in mm.



Pin Configuration

- 1. Emitter
- 2. Collector
- 3. Base

TO-126 TUBE PACKING



Packing Detail

			·				
PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-126 Bulk	500 pcs/polybag	340 gm/500 pcs	3" x 7.5" x 7.5"	2K	17" x 15" x 13.5"	32K	31 kgs
TO-126 Tube	50 pcs/tube	73 gm/50 pcs	3" x 3.7" x 21.5"	1K	19" x 19" x 19"	10K	15 kgs

BD131_132Rev_1 120403D

Notes BD131 NPN BD132 PNP

TO-126 Plastic Package

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited
C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-2579 6150 Fax + 91-11-2579 9569, 2579 5290
e-mail sales@cdil.com www.cdil.com, www.cdilsemi.com

BD131_132Rev_1 120403D